

Package ‘QR’

October 12, 2022

Type Package

Title QR Factorization without Pivoting

Version 0.1.3

Date 2022-07-15

Maintainer Juan Claramunt Gonzalez <j.claramunt.gonzalez@fsw.leidenuniv.nl>

Description This function performs QR factorization without pivoting to a real or complex matrix. It is based on Anderson. E. and ten others (1999) ``LAPACK Users' Guide". Third Edition. SIAM.

Depends tinytest

Suggests knitr, rmarkdown

VignetteBuilder knitr

License GPL-3

Encoding UTF-8

NeedsCompilation yes

RoxygenNote 7.2.0

URL http://www.netlib.org/lapack/explore-html/df/dc5/group__variants_g_ecomputational_ga3766ea903391b5cf9008132f7440ec7b.html

Author Juan Claramunt Gonzalez [aut, cre, cph]

Repository CRAN

Date/Publication 2022-07-17 09:50:02 UTC

R topics documented:

QR	2
QRcomp	3
Index	5

QR

QR factorization without pivoting

Description

This function performs QR factorization without pivoting to a numeric matrix A.

Usage

```
QR(A, complete = FALSE)
```

Arguments

A	a numeric matrix whose QR decomposition is to be computed.
complete	boolean that indicates if the R matrix should be completed with 0s to its full rank.

Details

This method is an alternative to the default `qr` function of base R. The default function returns a pivoted solution in many cases, which is not always the desired solution. In this function, we returned the unpivoted solution for the QR factorization using the LAPACK routine DGEQRF. Currently, the function only works for real numbers.

Value

Returns a list with the following components:

qr	a matrix with the same dimensions as A. The upper triangle contains the R of the decomposition and the lower triangle contains information on the Q of the decomposition (stored in compact form).
qraux	a vector of length <code>ncol(A)</code> which contains additional information on Q .
Q	an orthogonal matrix such that Q^*R is the input matrix.
R	an upper triangular matrix such that Q^*R is the input matrix.

Source

LAPACK routine DGEQRF is used for the QR factorization without pivoting.

References

Anderson. E. and ten others (1999) LAPACK Users' Guide. Third Edition. SIAM. Available on-line at http://www.netlib.org/lapack/lug/lapack_lug.html.

Examples

```

set.seed(2)
A<-matrix(sample(-20:20, size = 25, replace = TRUE),5,5)
qres<-QR(A)

#Inspect the main results of the factorization:
qres$Q
qres$R

```

QRcomp

QR factorization without pivoting

Description

This function performs QR factorization without pivoting to a complex matrix A.

Usage

```
QRcomp(A, complete = FALSE)
```

Arguments

A	a complex matrix whose QR decomposition is to be computed.
complete	boolean that indicates if the R matrix should be completed with 0s to its full rank.

Details

This method is an alternative to the default qr function of base R. The default function returns a pivoted solution in many cases, which is not always the desired solution. In this function, we returned the unpivoted solution for the QR factorization using the LAPACK routine ZGGEQRF. This function works with real and complex matrices.

Value

Returns a list with the following components:

qr	a matrix with the same dimensions as A. The upper triangle contains the R of the decomposition and the lower triangle contains information on the Q of the decomposition (stored in compact form).
qraux	a vector of length ncol(A) which contains additional information on Q .
Q	an orthogonal matrix such that Q^*R is the input matrix.
R	an upper triangular matrix such that Q^*R is the input matrix.

Source

LAPACK routine ZGEQRF is used for the QR factorization without pivoting.

References

Anderson. E. and ten others (1999) LAPACK Users' Guide. Third Edition. SIAM. Available on-line at http://www.netlib.org/lapack/lug/lapack_lug.html.

Examples

```
set.seed(2)
A<-matrix(c(complex(real=1,imaginary = 1),
complex(real=3,imaginary = -2), complex(real=2,imaginary = 1),
complex(real=0,imaginary = 3)),2,2)
qres<-QRcomp(A)

#Inspect the main results of the factorization:
qres$Q
qres$R
```

Index

* **QR**

QR, [2](#)

QRcomp, [3](#)

* **factorization**

QR, [2](#)

QRcomp, [3](#)

QR, [2](#)

QRcomp, [3](#)