

Package ‘DALEXtra’

May 9, 2021

Title Extension for 'DALEX' Package

Version 2.1.1

Description Provides wrapper of various machine learning models.

In applied machine learning, there is a strong belief that we need to strike a balance between interpretability and accuracy. However, in field of the interpretable machine learning, there are more and more new ideas for explaining black-box models, that are implemented in 'R'. 'DALEXtra' creates 'DALEX' Biecek (2018) <arXiv:1806.08915> explainer for many type of models including those created using 'python' 'scikit-learn' and 'keras' libraries, and 'java' 'h2o' library. Important part of the package is Champion-Challenger analysis and innovative approach to model performance across subsets of test data presented in Funnel Plot. Third branch of 'DALEXtra' package is aspect importance analysis that provides instance-level explanations for the groups of explanatory variables.

Depends R (>= 3.5.0), DALEX (>= 1.3)

License GPL

Encoding UTF-8

RoxygenNote 7.1.1

Imports reticulate, ggplot2

Suggests auditor, ingredients, gbm, ggrepel, h2o, iml, lime, localModel, mlr, mlr3, randomForest, recipes, rmarkdown, rpart, xgboost, testthat, tidymodels

URL <https://ModelOriented.github.io/DALEXtra/>,
<https://github.com/ModelOriented/DALEXtra>

BugReports <https://github.com/ModelOriented/DALEXtra/issues>

NeedsCompilation no

Author Szymon Maksymiuk [aut, cre] (<<https://orcid.org/0000-0002-3120-1601>>),
Przemyslaw Biecek [aut] (<<https://orcid.org/0000-0001-8423-1823>>),
Anna Kozak [ctb],
Hubert Baniecki [ctb]

Maintainer Szymon Maksymiuk <sz.maksymiuk@gmail.com>

Repository CRAN

Date/Publication 2021-05-09 07:30:13 UTC

R topics documented:

champion_challenger	2
create_env	4
explain_h2o	5
explain_keras	7
explain_mlr	10
explain_mlr3	12
explain_scikitlearn	14
explain_tidymodels	17
explain_xgboost	19
funnel_measure	22
model_info.WrappedModel	24
overall_comparison	25
plot.funnel_measure	26
plot.overall_comparison	28
plot.training_test_comparison	29
predict_surrogate	30
print.funnel_measure	31
print.overall_comparison	32
print.scikitlearn_set	33
print.training_test_comparison	34
training_test_comparison	35
yhat.WrappedModel	36
Index	39

champion_challenger *Compare machine learning models*

Description

Determining if one model is better than the other one is a difficult task. Mostly because there is a lot of fields that have to be covered to make such a judgement. Overall performance, performance on the crucial subset, distribution of residuals, those are only few among many ideas related to that issue. Following function allow user to create a report based on various sections. Each says something different about relation between champion and challengers. DALEXtra package share 3 base sections which are [funnel_measure](#) [overall_comparison](#) and [training_test_comparison](#) but any object that has generic plot function can be included at report.

Usage

```

champion_challenger(
  sections,
  dot_size = 4,
  output_dir_path = getwd(),
  output_name = "Report",
  model_performance_table = FALSE,
  title = "ChampionChallenger",
  author = Sys.info()[["user"]],
  ...
)

```

Arguments

sections	- list of sections to be attached to report. Could be sections available with DALEXtra which are funnel_measure training_test_comparison , overall_comparison or any other explanation that can work with <code>plot</code> function. Please provide name for not standard sections, that will be presented as section titles. Otherwise class of the object will be used.
dot_size	- <code>dot_size</code> argument passed to <code>plot.funnel_measure</code> if <code>funnel_measure</code> section present
output_dir_path	- path to directory where Report should be created. By default it is current working directory.
output_name	- name of the Report. By default it is "Report"
model_performance_table	- If TRUE and overall_comparison section present, table of scores will be displayed.
title	- Title for report, by default it is "ChampionChallenger".
author	- Author of , report. By default it is current user name.
...	- other parameters passed to <code>rmarkdown::render</code> .

Value

rmarkdown report

Examples

```

library("mlr")
library("DALEXtra")
task <- mlr::makeRegrTask(
  id = "R",
  data = apartments,
  target = "m2.price"
)
learner_lm <- mlr::makeLearner(

```

```

    "regr.lm"
  )
  model_lm <- mlr::train(learner_lm, task)
  explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")

  learner_rf <- mlr::makeLearner(
    "regr.randomForest"
  )
  model_rf <- mlr::train(learner_rf, task)
  explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")

  learner_gbm <- mlr::makeLearner(
    "regr.gbm"
  )
  model_gbm <- mlr::train(learner_gbm, task)
  explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "GBM")

  plot_data <- funnel_measure(explainer_lm, list(explainer_rf, explainer_gbm),
    nbins = 5, measure_function = DALEX::loss_root_mean_square)

  champion_challenger(list(plot_data), dot_size = 3)

```

 create_env

Create your conda virtual env with DALEX

Description

Python objects may be loaded into R. However, it requires versions of the Python and libraries to match between both machines. This functions allow user to create conda virtual environment based on provided .yaml file.

Usage

```
create_env(yml, condaenv)
```

Arguments

yml	a path to the .yaml file. If OS is Windows conda has to be added to the PATH first
condaenv	path to main conda folder. If OS is Unix You may want to specify it. When passed with windows, param will be omitted.

Value

Name of created virtual env.

Author(s)

Szymon Maksymiuk

Examples

```
## Not run:
  create_env(system.file("extdata", "testing_environment.yml", package = "DALEXtra"))

## End(Not run)
```

`explain_h2o`*Create explainer from your h2o model*

Description

DALEX is designed to work with various black-box models like tree ensembles, linear models, neural networks etc. Unfortunately R packages that create such models are very inconsistent. Different tools use different interfaces to train, validate and use models. One of those tools, we would like to make more accessible is H2O.

Usage

```
explain_h2o(
  model,
  data = NULL,
  y = NULL,
  weights = NULL,
  predict_function = NULL,
  predict_function_target_column = NULL,
  residual_function = NULL,
  ...,
  label = NULL,
  verbose = TRUE,
  precalculate = TRUE,
  colorize = TRUE,
  model_info = NULL,
  type = NULL
)
```

Arguments

<code>model</code>	object - a model to be explained
<code>data</code>	data.frame or matrix - data that was used for fitting. If not provided then will be extracted from the model. Data should be passed without target column (this shall be provided as the <code>y</code> argument). NOTE: If target variable is present in the data, some of the functionalities may not work properly.

<code>y</code>	numeric vector with outputs / scores. If provided then it shall have the same size as data
<code>weights</code>	numeric vector with sampling weights. By default it's NULL. If provided then it shall have the same length as data
<code>predict_function</code>	function that takes two arguments: model and new data and returns numeric vector with predictions
<code>predict_function_target_column</code>	Character or numeric containing either column name or column number in the model prediction object of the class that should be considered as positive (ie. the class that is associated with probability 1). If NULL, the second column of the output will be taken for binary classification. For a multiclass classification setting that parameter cause switch to binary classification mode with 1 vs others probabilities.
<code>residual_function</code>	function that takes three arguments: model, data and response vector y. It should return a numeric vector with model residuals for given data. If not provided, response residuals ($y - \hat{y}$) are calculated.
<code>...</code>	other parameters
<code>label</code>	character - the name of the model. By default it's extracted from the 'class' attribute of the model
<code>verbose</code>	if TRUE (default) then diagnostic messages will be printed
<code>precalculate</code>	if TRUE (default) then 'predicted_values' and 'residuals' are calculated when explainer is created.
<code>colorize</code>	if TRUE (default) then WARNINGS, ERRORS and NOTES are colorized. Will work only in the R console.
<code>model_info</code>	a named list (package, version, type) containg information about model. If NULL, DALEX will seek for information on it's own.
<code>type</code>	type of a model, either classification or regression. If not specified then type will be extracted from model_info.

Value

explainer object ([explain](#)) ready to work with DALEX

Examples

```
# load packages and data
library(h2o)
library(DALEXtra)

# data <- DALEX::titanic_imputed

# init h2o
```

```

    cluster <- try(h2o::h2o.init())
    if (!inherits(cluster, "try-error")) {
      # stop h2o progress printing
      h2o.no_progress()

      # split the data
      # h2o_split <- h2o.splitFrame(as.h2o(data))
      # train <- h2o_split[[1]]
      # test <- as.data.frame(h2o_split[[2]])
      # h2o automl takes target as factor
      # train$survived <- as.factor(train$survived)

      # fit a model
      # automl <- h2o.automl(y = "survived",
      #                     training_frame = train,
      #                     max_runtime_secs = 30)

      # create an explainer for the model
      # explainer <- explain_h2o(automl,
      #                          data = test,
      #                          y = test$survived,
      #                          label = "h2o")

      titanic_test <- read.csv(system.file("extdata", "titanic_test.csv", package = "DALEXtra"))
      titanic_train <- read.csv(system.file("extdata", "titanic_train.csv", package = "DALEXtra"))
      titanic_h2o <- h2o::as.h2o(titanic_train)
      titanic_h2o["survived"] <- h2o::as.factor(titanic_h2o["survived"])
      titanic_test_h2o <- h2o::as.h2o(titanic_test)
      model <- h2o::h2o.gbm(
        training_frame = titanic_h2o,
        y = "survived",
        distribution = "bernoulli",
        ntrees = 500,
        max_depth = 4,
        min_rows = 12,
        learn_rate = 0.001
      )
      explain_h2o(model, titanic_test[,1:17], titanic_test[,18])

      h2o.shutdown(prompt = FALSE)
    }

```

Description

Keras models may be loaded into R environment like any other Python object. This function helps to inspect performance of Python model and compare it with other models, using R tools like DALEX. This function creates an object that is easily accessible R version of Keras model exported from Python via pickle file.

Usage

```
explain_keras(
  path,
  yml = NULL,
  condaenv = NULL,
  env = NULL,
  data = NULL,
  y = NULL,
  weights = NULL,
  predict_function = NULL,
  predict_function_target_column = NULL,
  residual_function = NULL,
  ...,
  label = NULL,
  verbose = TRUE,
  precalculate = TRUE,
  colorize = TRUE,
  model_info = NULL,
  type = NULL
)
```

Arguments

path	a path to the pickle file. Can be used without other arguments if you are sure that active Python version match pickle version.
yml	a path to the yml file. Conda virtual env will be recreated from this file. If OS is Windows conda has to be added to the PATH first
condaenv	If yml param is provided, a path to the main conda folder. If yml is null, a name of existing conda environment.
env	A path to python virtual environment.
data	test data set that will be passed to explain .
y	vector that will be passed to explain .
weights	numeric vector with sampling weights. By default it's NULL. If provided then it shall have the same length as data
predict_function	predict function that will be passed into explain . If NULL, default will be used.
predict_function_target_column	Character or numeric containing either column name or column number in the model prediction object of the class that should be considered as positive (ie.

the class that is associated with probability 1). If NULL, the second column of the output will be taken for binary classification. For a multiclass classification setting that parameter cause switch to binary classification mode with 1 vs others probabilities.

residual_function	residual function that will be passed into <code>explain</code> . If NULL, default will be used.
...	other parameters
label	label that will be passed into <code>explain</code> . If NULL, default will be used.
verbose	bool that will be passed into <code>explain</code> . If NULL, default will be used.
precalculate	if TRUE (default) then 'predicted_values' and 'residuals' are calculated when explainer is created.
colorize	if TRUE (default) then WARNINGS, ERRORS and NOTES are colorized. Will work only in the R console.
model_info	a named list (package, version, type) containg information about model. If NULL, DALEX will seek for information on it's own.
type	type of a model, either classification or regression. If not specified then type will be extracted from model_info.

Value

An object of the class 'explainer'.

Example of Python code avialble at documentation [explain_scikitlearn](#)

Errors use case

Here is shortened version of solution for specific errors

There already exists environment with a name specified by given .yml file

If you provide .yml file that in its header contatins name exact to name of environment that already exists, existing will be set active without changing it.

You have two ways of solving that issue. Both connected with anaconda prompt. First is removing conda env with command:

```
conda env remove --name myenv
```

And execute function once again. Second is updating env via:

```
conda env create -f environment.yml
```

Conda cannot find specified packages at channels you have provided.

That error may be casued by a lot of things. One of those is that specified version is too old to be avaialble from offcial conda repo. Edit Your .yml file and add link to proper repository at channels section.

Issue may be also connected with the platform. If model was created on the platform with different OS yo may need to remove specific version from .yml file.

```
-numpy=1.16.4=py36h19fb1c0_0
```

```
-numpy-base=1.16.4=py36hc3f5095_0
```

In the example above You have to remove =py36h19fb1c0_0 and =py36hc3f5095_0

If some packages are not available for anaconda at all, use pip statement

If .yml file seems not to work, virtual env can be created manually using anaconda prompt.

```
conda create -n name_of_env python=3.4
conda install -n name_of_env name_of_package=0.20
```

Author(s)

Szymon Maksymiuk

Examples

```
library("DALEXtra")
## Not run:
# Explainer build (Keep in mind that 9th column is target)
test_data <-
  read.csv(
    "https://raw.githubusercontent.com/jbrownlee/Datasets/master/pima-indians-diabetes.data.csv",
    sep = ",")
# Keep in mind that when pickle is being built and loaded,
# not only Python version but libraries versions has to match aswell
explainer <- explain_keras(system.file("extdata", "keras.pkl", package = "DALEXtra"),
  conda = "myenv",
  data = test_data[,1:8], y = test_data[,9])
plot(model_performance(explainer))

# Predictions with newdata
predict(explainer, test_data[1:10,1:8])

## End(Not run)
```

explain_mlr

Create explainer from your mlr model

Description

DALEX is designed to work with various black-box models like tree ensembles, linear models, neural networks etc. Unfortunately R packages that create such models are very inconsistent. Different tools use different interfaces to train, validate and use models. One of those tools, which is one of the most popular one is mlr package. We would like to present dedicated explain function for it.

Usage

```
explain_mlr(
  model,
  data = NULL,
```

```

    y = NULL,
    weights = NULL,
    predict_function = NULL,
    predict_function_target_column = NULL,
    residual_function = NULL,
    ...,
    label = NULL,
    verbose = TRUE,
    precalculate = TRUE,
    colorize = TRUE,
    model_info = NULL,
    type = NULL
)

```

Arguments

model	object - a model to be explained
data	data.frame or matrix - data that was used for fitting. If not provided then will be extracted from the model. Data should be passed without target column (this shall be provided as the y argument). NOTE: If target variable is present in the data, some of the functionalities may not work properly.
y	numeric vector with outputs / scores. If provided then it shall have the same size as data.
weights	numeric vector with sampling weights. By default it's NULL. If provided then it shall have the same length as data
predict_function	function that takes two arguments: model and new data and returns numeric vector with predictions
predict_function_target_column	Character or numeric containing either column name or column number in the model prediction object of the class that should be considered as positive (ie. the class that is associated with probability 1). If NULL, the second column of the output will be taken for binary classification. For a multiclass classification setting that parameter cause switch to binary classification mode with 1 vs others probabilities.
residual_function	function that takes three arguments: model, data and response vector y. It should return a numeric vector with model residuals for given data. If not provided, response residuals ($y - \hat{y}$) are calculated.
...	other parameters
label	character - the name of the model. By default it's extracted from the 'class' attribute of the model
verbose	if TRUE (default) then diagnostic messages will be printed
precalculate	if TRUE (default) then 'predicted_values' and 'residuals' are calculated when explainer is created.

colorize	if TRUE (default) then WARNINGS, ERRORS and NOTES are colorized. Will work only in the R console.
model_info	a named list (package, version, type) containing information about model. If NULL, DALEX will seek for information on its own.
type	type of a model, either classification or regression. If not specified then type will be extracted from model_info.

Value

explainer object ([explain](#)) ready to work with DALEX

Examples

```
library("DALEXtra")
titanic_test <- read.csv(system.file("extdata", "titanic_test.csv", package = "DALEXtra"))
titanic_train <- read.csv(system.file("extdata", "titanic_train.csv", package = "DALEXtra"))
library("mlr")
task <- mlr::makeClassifTask(
  id = "R",
  data = titanic_train,
  target = "survived"
)
learner <- mlr::makeLearner(
  "classif.gbm",
  par.vals = list(
    distribution = "bernoulli",
    n.trees = 500,
    interaction.depth = 4,
    n.minobsinnode = 12,
    shrinkage = 0.001,
    bag.fraction = 0.5,
    train.fraction = 1
  ),
  predict.type = "prob"
)
gbm <- mlr::train(learner, task)
explain_mlr(gbm, titanic_test[,1:17], titanic_test[,18])
```

Description

DALEX is designed to work with various black-box models like tree ensembles, linear models, neural networks etc. Unfortunately R packages that create such models are very inconsistent. Different tools use different interfaces to train, validate and use models. One of those tools, which is one of the most popular one is mlr3 package. We would like to present dedicated explain function for it.

Usage

```

explain_mlr3(
  model,
  data = NULL,
  y = NULL,
  weights = NULL,
  predict_function = NULL,
  predict_function_target_column = NULL,
  residual_function = NULL,
  ...,
  label = NULL,
  verbose = TRUE,
  precalculate = TRUE,
  colorize = TRUE,
  model_info = NULL,
  type = NULL
)

```

Arguments

<code>model</code>	object - a fitted learner created with <code>mlr3</code> .
<code>data</code>	data.frame or matrix - data that was used for fitting. If not provided then will be extracted from the model. Data should be passed without target column (this shall be provided as the <code>y</code> argument). NOTE: If target variable is present in the data, some of the functionalities may not work properly.
<code>y</code>	numeric vector with outputs / scores. If provided then it shall have the same size as data
<code>weights</code>	numeric vector with sampling weights. By default it's NULL. If provided then it shall have the same length as data
<code>predict_function</code>	function that takes two arguments: model and new data and returns numeric vector with predictions
<code>predict_function_target_column</code>	Character or numeric containing either column name or column number in the model prediction object of the class that should be considered as positive (ie. the class that is associated with probability 1). If NULL, the second column of the output will be taken for binary classification. For a multiclass classification setting that parameter cause switch to binary classification mode with 1 vs others probabilities.
<code>residual_function</code>	function that takes three arguments: model, data and response vector <code>y</code> . It should return a numeric vector with model residuals for given data. If not provided, response residuals ($y - \hat{y}$) are calculated.
<code>...</code>	other parameters
<code>label</code>	character - the name of the model. By default it's extracted from the 'class' attribute of the model

verbose	if TRUE (default) then diagnostic messages will be printed.
precalculate	if TRUE (default) then 'predicted_values' and 'residuals' are calculated when explainer is created.
colorize	if TRUE (default) then WARNINGS, ERRORS and NOTES are colorized. Will work only in the R console.
model_info	a named list (package, version, type) containing information about model. If NULL, DALEX will seek for information on its own.
type	type of a model, either classification or regression. If not specified then type will be extracted from model_info.

Value

explainer object ([explain](#)) ready to work with DALEX

Examples

```
library("DALEXtra")
library(mlr3)
titanic_imputed$survived <- as.factor(titanic_imputed$survived)
task_classif <- TaskClassif$new(id = "1", backend = titanic_imputed, target = "survived")
learner_classif <- lrn("classif.rpart", predict_type = "prob")
learner_classif$train(task_classif)
explain_ml3(learner_classif, data = titanic_imputed,
            y = as.numeric(as.character(titanic_imputed$survived)))

task_regr <- TaskRegr$new(id = "2", backend = apartments, target = "m2.price")
learner_regr <- lrn("regr.rpart")
learner_regr$train(task_regr)
explain_ml3(learner_regr, data = apartments, apartments$m2.price)
```

explain_scikitlearn *Wrapper for Python Scikit-Learn Models*

Description

scikit-learn models may be loaded into R environment like any other Python object. This function helps to inspect performance of Python model and compare it with other models, using R tools like DALEX. This function creates an object that is easily accessible R version of scikit-learn model exported from Python via pickle file.

Usage

```
explain_scikitlearn(
  path,
  yml = NULL,
```

```

condaenv = NULL,
env = NULL,
data = NULL,
y = NULL,
weights = NULL,
predict_function = NULL,
predict_function_target_column = NULL,
residual_function = NULL,
...,
label = NULL,
verbose = TRUE,
precalculate = TRUE,
colorize = TRUE,
model_info = NULL,
type = NULL
)

```

Arguments

path	a path to the pickle file. Can be used without other arguments if you are sure that active Python version match pickle version.
yml	a path to the yml file. Conda virtual env will be recreated from this file. If OS is Windows conda has to be added to the PATH first
condaenv	If yml param is provided, a path to the main conda folder. If yml is null, a name of existing conda environment.
env	A path to python virtual environment.
data	test data set that will be passed to explain .
y	vector that will be passed to explain .
weights	numeric vector with sampling weights. By default it's NULL. If provided then it shall have the same length as data
predict_function	predict function that will be passed into explain . If NULL, default will be used.
predict_function_target_column	Character or numeric containing either column name or column number in the model prediction object of the class that should be considered as positive (ie. the class that is associated with probability 1). If NULL, the second column of the output will be taken for binary classification. For a multiclass classification setting that parameter cause switch to binary classification mode with 1 vs others probabilities.
residual_function	residual function that will be passed into explain . If NULL, default will be used.
...	other parameters
label	label that will be passed into explain . If NULL, default will be used.
verbose	bool that will be passed into explain . If NULL, default will be used.

precalculate	if TRUE (default) then 'predicted_values' and 'residuals' are calculated when explainer is created.
colorize	if TRUE (default) then WARNINGS, ERRORS and NOTES are colorized. Will work only in the R console.
model_info	a named list (package, version, type) containg information about model. If NULL, DALEX will seek for information on it's own.
type	type of a model, either classification or regression. If not specified then type will be extracted from model_info.

Value

An object of the class 'explainer'. It has additional field param_set when user can check parameters of scikitlearn model

Example of Python code

```
from pandas import DataFrame, read_csv
import pandas as pd
import pickle
import sklearn.ensemble
model = sklearn.ensemble.GradientBoostingClassifier()
model = model.fit(titanic_train_X, titanic_train_Y)
pickle.dump(model, open("gbm.pkl", "wb"), protocol = 2)
```

In order to export environment into .yaml, activating virtual env via activate name_of_the_env and execution of the following shell command is necessary
conda env export > environment.yaml

Errors use case

Here is shortened version of solution for specific errors

There already exists environment with a name specified by given .yaml file

If you provide .yaml file that in its header contains name exact to name of environment that already exists, existing will be set active without changing it.

You have two ways of solving that issue. Both connected with anaconda prompt. First is removing conda env with command:

```
conda env remove --name myenv
```

And execute function once again. Second is updating env via:

```
conda env create -f environment.yaml
```

Conda cannot find specified packages at channels you have provided.

That error may be caused by a lot of things. One of those is that specified version is too old to be available from official conda repo. Edit Your .yaml file and add link to proper repository at channels section.

Issue may be also connected with the platform. If model was created on the platform with different OS you may need to remove specific version from .yaml file.

```
-numpy=1.16.4=py36h19fb1c0_0
```

```
-numpy-base=1.16.4=py36hc3f5095_0
```

In the example above you have to remove =py36h19fb1c0_0 and =py36hc3f5095_0

If some packages are not available for anaconda at all, use pip statement

If .yaml file seems not to work, virtual env can be created manually using anaconda prompt.

```
conda create -n name_of_env python=3.4
```

```
conda install -n name_of_env name_of_package=0.20
```

Author(s)

Szymon Maksymiuk

Examples

```
## Not run:
# Explainer build (Keep in mind that 18th column is target)
titanic_test <- read.csv(system.file("extdata", "titanic_test.csv", package = "DALEXtra"))
# Keep in mind that when pickle is being built and loaded,
# not only Python version but libraries versions has to match as well
explainer <- explain_scikitlearn(system.file("extdata", "scikitlearn.pkl", package = "DALEXtra"),
  yaml = system.file("extdata", "testing_environment.yaml", package = "DALEXtra"),
  data = titanic_test[,1:17], y = titanic_test$survived)
plot(model_performance(explainer))

# Predictions with newdata
predict(explainer, titanic_test[1:10,1:17])

## End(Not run)
```

explain_tidymodels *Create explainer from your tidymodels workflow.*

Description

DALEX is designed to work with various black-box models like tree ensembles, linear models, neural networks etc. Unfortunately R packages that create such models are very inconsistent. Different tools use different interfaces to train, validate and use models. One of those tools, which is one of the most popular one is tidymodels package. We would like to present dedicated explain function for it.

Usage

```

explain_tidymodels(
  model,
  data = NULL,
  y = NULL,
  weights = NULL,
  predict_function = NULL,
  predict_function_target_column = NULL,
  residual_function = NULL,
  ...,
  label = NULL,
  verbose = TRUE,
  precalculate = TRUE,
  colorize = TRUE,
  model_info = NULL,
  type = NULL
)

```

Arguments

<code>model</code>	object - a fitted workflow created with <code>mlr3</code> .
<code>data</code>	data.frame or matrix - data that was used for fitting. Data should be passed without target column (this shall be provided as the <code>y</code> argument). NOTE: If target variable is present in the data, some of the functionalities may not work properly. Tibble will be converted into data.frame
<code>y</code>	numeric vector with outputs / scores. If provided then it shall have the same size as data
<code>weights</code>	numeric vector with sampling weights. By default it's NULL. If provided then it shall have the same length as data
<code>predict_function</code>	function that takes two arguments: model and new data and returns numeric vector with predictions
<code>predict_function_target_column</code>	Character or numeric containing either column name or column number in the model prediction object of the class that should be considered as positive (ie. the class that is associated with probability 1). If NULL, the second column of the output will be taken for binary classification. For a multiclass classification setting that parameter cause switch to binary classification mode with 1 vs others probabilities.
<code>residual_function</code>	function that takes three arguments: model, data and response vector <code>y</code> . It should return a numeric vector with model residuals for given data. If not provided, response residuals ($y - \hat{y}$) are calculated.
<code>...</code>	other parameters
<code>label</code>	character - the name of the model. By default it's extracted from the 'class' attribute of the model

verbose	if TRUE (default) then diagnostic messages will be printed.
precalculate	if TRUE (default) then 'predicted_values' and 'residuals' are calculated when explainer is created.
colorize	if TRUE (default) then WARNINGS, ERRORS and NOTES are colorized. Will work only in the R console.
model_info	a named list (package, version, type) containing information about model. If NULL, DALEX will seek for information on its own.
type	type of a model, either classification or regression. If not specified then type will be extracted from model_info.

Value

explainer object ([explain](#)) ready to work with DALEX

Examples

```
library("DALEXtra")
library("tidymodels")
library("recipes")
data <- titanic_imputed
data$survived <- as.factor(data$survived)
rec <- recipe(survived ~ ., data = data) %>%
  step_normalize(fare)
model <- decision_tree(tree_depth = 25) %>%
  set_engine("rpart") %>%
  set_mode("classification")

wflow <- workflow() %>%
  add_recipe(rec) %>%
  add_model(model)

model_fitted <- wflow %>%
  fit(data = data)

explain_tidymodels(model_fitted, data = titanic_imputed, y = titanic_imputed$survived)
```

explain_xgboost

Create explainer from your xgboost model

Description

DALEX is designed to work with various black-box models like tree ensembles, linear models, neural networks etc. Unfortunately R packages that create such models are very inconsistent. Different tools use different interfaces to train, validate and use models. One of those tools, we would like to make more accessible is xgboost.

Usage

```

explain_xgboost(
  model,
  data = NULL,
  y = NULL,
  weights = NULL,
  predict_function = NULL,
  predict_function_target_column = NULL,
  residual_function = NULL,
  ...,
  label = NULL,
  verbose = TRUE,
  precalculate = TRUE,
  colorize = TRUE,
  model_info = NULL,
  type = NULL,
  encode_function = NULL,
  true_labels = NULL
)

```

Arguments

model	object - a model to be explained
data	data.frame or matrix - data that was used for fitting. If not provided then will be extracted from the model. Data should be passed without target column (this shall be provided as the y argument). NOTE: If target variable is present in the data, some of the functionalities may not work properly.
y	numeric vector with outputs / scores. If provided then it shall have the same size as data. For classif task has to be numeric in range [0, nclasses)
weights	numeric vector with sampling weights. By default it's NULL. If provided then it shall have the same length as data
predict_function	function that takes two arguments: model and new data and returns numeric vector with predictions
predict_function_target_column	Character or numeric containing either column name or column number in the model prediction object of the class that should be considered as positive (ie. the class that is associated with probability 1). If NULL, the second column of the output will be taken for binary classification. For a multiclass classification setting that parameter cause switch to binary classification mode with 1 vs others probabilities.
residual_function	function that takes three arguments: model, data and response vector y. It should return a numeric vector with model residuals for given data. If not provided, response residuals ($y - \hat{y}$) are calculated.
...	other parameters

label	character - the name of the model. By default it's extracted from the 'class' attribute of the model
verbose	if TRUE (default) then diagnostic messages will be printed
precalculate	if TRUE (default) then 'predicted_values' and 'residuals' are calculated when explainer is created.
colorize	if TRUE (default) then WARNINGS, ERRORS and NOTES are colorized. Will work only in the R console.
model_info	a named list (package, version, type) containg information about model. If NULL, DALEX will seek for information on it's own.
type	type of a model, either classification or regression. If not specified then type will be extracted from model_info.
encode_function	fuction(data, ...) that if executed with data parameters returns encoded dataframe that was used to fit model. Xgboost does not handle factors on it's own so such function is needed to aquire better explanations.
true_labels	vecotr of y before encoding.

Value

explainer object ([explain](#)) ready to work with DALEX

Examples

```
library("xgboost")
library("DALEXtra")
library("mlr")
# 8th column is target that has to be omitted in X data
data <- as.matrix(createDummyFeatures(titanic_imputed[,-8]))
model <- xgboost(data, titanic_imputed$survived, nrounds = 10,
  params = list(objective = "binary:logistic"),
  prediction = TRUE)
# explainer with encode functiom
explainer_1 <- explain_xgboost(model, data = titanic_imputed[,-8],
  titanic_imputed$survived,
  encode_function = function(data) {
  as.matrix(createDummyFeatures(data))
})
plot(predict_parts(explainer_1, titanic_imputed[1,-8]))

# explainer without encode function
explainer_2 <- explain_xgboost(model, data = data, titanic_imputed$survived)
plot(predict_parts(explainer_2, data[1,],drop = FALSE))
```

funnel_measure	<i>Caluculate difference in performance in models across different categories</i>
----------------	---

Description

Function `funnel_measure` allows users to compare two models based on their explainers. It partitions dataset on which models were built and creates categories according to quantiles of columns in partition data. `nbins` parameter determinates number of qunatiles. For each category difference in provided measure is being calculated. Positive value of that differnece means that Champion model has better performance in specified category, while negative value means that one of the Challengers was better. Function allows to compare multiple Challengers at once.

Usage

```
funnel_measure(  
  champion,  
  challengers,  
  measure_function = NULL,  
  nbins = 5,  
  partition_data = champion$data,  
  cutoff = 0.01,  
  cutoff_name = "Other",  
  factor_conversion_threshold = 7,  
  show_info = TRUE,  
  categories = NULL  
)
```

Arguments

<code>champion</code>	- explainer of champion model.
<code>challengers</code>	- explainer of challenger model or list of explainers.
<code>measure_function</code>	- measure function that calculates performance of model based on true observation and prediction. Order of parameters is important and should be (y, y_hat). The measure calculated by the function should have the property that lower score value indicates better model. If NULL, RMSE will be used for regression, one minus auc for classification and crossentropy for multiclass classification.
<code>nbins</code>	- Number of qunatiles (partition points) for numeric columns. In case when more than one qunatile have the same value, there will be less partition points.
<code>partition_data</code>	- Data by which test dataset will be partitioned for computation. Can be either data.frame or character vector. When second is passed, it has to indicate names of columns that will be extracted fromm test data. By default full test data. If data.frame, number of rows has to be equal to number of rows in test data.
<code>cutoff</code>	- Threshold for categorical data. Entries less frequent than specified value will be merged into one category.

cutoff_name	- Name for new category that arised after merging entries less frequent than cutoff
factor_conversion_threshold	- Numeric columns with lower number of unique values than value of this parameter will be treated as factors
show_info	- Logical value indicating if progress bar should be shown.
categories	- a named list of variable names that will be plotted in a different colour. By deafault it is partitioned on Explanatory, External and Target.

Value

An object of the class `funnel_measure`

It is a named list containing following fields:

- `data` `data.frame` that consists of columns:
 - Variable Variable according to which partitions were made
 - Measure Difference in measures. Positive value indicates that champion was better, while negative that challenger.
 - Label String that defines subset of Variable values (partition rule).
 - Challenger Label of challenger explainer that was used in Measure
 - Category a category of the variable passed to function
- `models_info` `data.frame` containig inforamtion about models used in analysys

Examples

```
library("mlr")
library("DALEXtra")
task <- mlr::makeRegrTask(
  id = "R",
  data = apartments,
  target = "m2.price"
)
learner_lm <- mlr::makeLearner(
  "regr.lm"
)
model_lm <- mlr::train(learner_lm, task)
explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")

learner_rf <- mlr::makeLearner(
  "regr.randomForest"
)
model_rf <- mlr::train(learner_rf, task)
explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")

learner_gbm <- mlr::makeLearner(
  "regr.gbm"
)
model_gbm <- mlr::train(learner_gbm, task)
```

```
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "GBM")

plot_data <- funnel_measure(explainer_lm, list(explainer_rf, explainer_gbm),
                           nbins = 5, measure_function = DALEX::loss_root_mean_square)
plot(plot_data)
```

model_info.WrappedModel

Extract info from model

Description

This generic function let user extract base information about model. The function returns a named list of class `model_info` that contain about package of model, version and task type. For wrappers like `mlr` or `caret` both, package and wrapper information are stored

Usage

```
## S3 method for class 'WrappedModel'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'H2ORegressionModel'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'H2OBinomialModel'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'H2OMultinomialModel'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'scikitlearn_model'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'keras'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'LearnerRegr'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'LearnerClassif'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'GraphLearner'
model_info(model, is_multiclass = FALSE, ...)
```



```

## S3 method for class 'xgb.Booster'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'workflow'
model_info(model, is_multiclass = FALSE, ...)

```

Arguments

model - model object
is_multiclass - if TRUE and task is classification, then multitask classification is set. Else is omitted. If `model_info` was executed withing `explain` function. DALEX will recognize subtype on it's own. @param is_multiclass
... - another arguments
 Currently supported packages are:

- mlr models created with mlr package
- h2o models created with h2o package
- scikit-learn models created with scikit-learn python library and accessed via reticulate
- keras models created with keras python library and accessed via reticulate
- mlr3 models created with mlr3 package
- xgboost models created with xgboost package
- tidymodels models created with tidymodels package

Value

A named list of class `model_info`

overall_comparison *Compare champion with challengers globally*

Description

The function creates objects that present global model performance using various measures. Those data can be easily plotted with `plot` function. It uses `auditor` package to create [model_performance](#) of all passed explainers. Keep in mind that type of task has to be specified.

Usage

```
overall_comparison(champion, challengers, type)
```

Arguments

champion - explainer of champion model.
challengers - explainer of challenger model or list of explainers.
type - type of the task. Either classification or regression

Value

An object of the class overall_comparison

It is a named list containing following fields:

- radar list of `model_performance` objects and other parameters that will be passed to generic plot function
- accordance data.frame object of champion responses and challenger's corresponding to them. Used to plot accordance.
- models_info data.frame containig information about models used in analysys.

Examples

```
library("DALEXtra")
library("mlr")
task <- mlr::makeRegrTask(
  id = "R",
  data = apartments,
  target = "m2.price"
)
learner_lm <- mlr::makeLearner(
  "regr.lm"
)
model_lm <- mlr::train(learner_lm, task)
explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")

learner_rf <- mlr::makeLearner(
  "regr.randomForest"
)
model_rf <- mlr::train(learner_rf, task)
explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")

learner_gbm <- mlr::makeLearner(
  "regr.gbm"
)
model_gbm <- mlr::train(learner_gbm, task)
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "gbm")

data <- overall_comparison(explainer_lm, list(explainer_gbm, explainer_rf), type = "regression")
plot(data)
```

plot.funnel_measure *Funnel plot for difference in measures*

Description

Function `plot.funnel_measure` creates funnel plot of differences in measures for two models across variable areas. It uses data created with `'funnel_measure'` function.

Usage

```
## S3 method for class 'funnel_measure'  
plot(x, ..., dot_size = 0.5)
```

Arguments

x - funnel_measure object created with `funnel_measure` function.
... - other parameters
dot_size - size of the dot on plots. Passed to `geom_point`.

Value

ggplot object

Examples

```
library("mlr")  
library("DALEXtra")  
task <- mlr::makeRegrTask(  
  id = "R",  
  data = apartments,  
  target = "m2.price"  
)  
learner_lm <- mlr::makeLearner(  
  "regr.lm"  
)  
model_lm <- mlr::train(learner_lm, task)  
explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")  
  
learner_rf <- mlr::makeLearner(  
  "regr.randomForest"  
)  
model_rf <- mlr::train(learner_rf, task)  
explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")  
  
learner_gbm <- mlr::makeLearner(  
  "regr.gbm"  
)  
model_gbm <- mlr::train(learner_gbm, task)  
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "GBM")  
  
plot_data <- funnel_measure(explainer_lm, list(explainer_rf, explainer_gbm),  
  nbins = 5, measure_function = DALEX::loss_root_mean_square)  
plot(plot_data)
```

`plot.overall_comparison`*Plot function for overall_comparison*

Description

The function plots data created with `overall_comparison`. For radar plot it uses auditor's `plot_radar`. Keep in mind that the function creates two plots returned as list.

Usage

```
## S3 method for class 'overall_comparison'  
plot(x, ...)
```

Arguments

`x` - data created with `overall_comparison`
`...` - other parameters

Value

A named list of ggplot objects.

It consists of:

- `radar_plot` plot created with `plot_radar`
- `accordance_plot` accordance plot of responses. OX axis stand for champion response, while OY for one of challengers responses. Colour indicates on challenger.

Examples

```
library("DALEXtra")  
library("mlr")  
task <- mlr::makeRegrTask(  
  id = "R",  
  data = apartments,  
  target = "m2.price"  
)  
learner_lm <- mlr::makeLearner(  
  "regr.lm"  
)  
model_lm <- mlr::train(learner_lm, task)  
explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")  
  
learner_rf <- mlr::makeLearner(  
  "regr.randomForest"  
)  
model_rf <- mlr::train(learner_rf, task)
```

```

explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")

learner_gbm <- mlr::makeLearner(
  "regr.gbm"
)
model_gbm <- mlr::train(learner_gbm, task)
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "GBM")

data <- overall_comparison(explainer_lm, list(explainer_gbm, explainer_rf), type = "regression")
plot(data)

```

```
plot.training_test_comparison
```

Plot and compare performance of model between training and test set

Description

Function `plot.training_test_comparison` plots dependency between model performance on test and training dataset based on `training_test_comparison` object. Green line indicates $y = x$ line.

Usage

```

## S3 method for class 'training_test_comparison'
plot(x, ...)

```

Arguments

`x` - object created with `training_test_comparison` function.
`...` - other parameters

Value

ggplot object

Examples

```

library("mlr")
library("DALEXtra")
task <- mlr::makeRegrTask(
  id = "R",
  data = apartments,
  target = "m2.price"
)
learner_lm <- mlr::makeLearner(
  "regr.lm"
)
model_lm <- mlr::train(learner_lm, task)

```

```

explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")

learner_rf <- mlr::makeLearner(
  "regr.randomForest"
)
model_rf <- mlr::train(learner_rf, task)
explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")

learner_gbm <- mlr::makeLearner(
  "regr.gbm"
)
model_gbm <- mlr::train(learner_gbm, task)
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "GBM")

data <- training_test_comparison(explainer_lm, list(explainer_gbm, explainer_rf),
                                training_data = apartments,
                                training_y = apartments$m2.price)

plot(data)

```

predict_surrogate *Instance Level Surrogate Models*

Description

Interface to different implementations of the LIME method. Find information how the LIME method works here: <https://ema.drwhy.ai/LIME.html>.

Usage

```

predict_surrogate(explainer, new_observation, ..., type = "localModel")

predict_surrogate_local_model(
  explainer,
  new_observation,
  size = 1000,
  seed = 1313,
  ...
)

predict_model.dalex_explainer(x, newdata, ...)

model_type.dalex_explainer(x, ...)

predict_surrogate_lime(
  explainer,
  new_observation,
  n_features = 4,

```

```

    n_permutations = 1000,
    labels = unique(explainer$y)[1],
    ...
)

## S3 method for class 'predict_surrogate_lime'
plot(x, ...)

predict_surrogate_uml(explainer, new_observation, k = 4, ...)

```

Arguments

explainer	a model to be explained, preprocessed by the 'explain' function
new_observation	a new observation for which predictions need to be explained
...	other parameters that will be passed to
type	which implementation of the LIME method should be used. Either localModel (default), lime or iml.
size	will be passed to the localModel implementation, by default 1000
seed	seed for random number generator, by default 1313
x	an object to be plotted
newdata	alias for new_observation
n_features	will be passed to the lime implementation, by default 4
n_permutations	will be passed to the lime implementation, by default 1000
labels	will be passed to the lime implementation, by default first value in the y vector
k	will be passed to the iml implementation, by default 4

Value

Depending on the type there are different classes of the resulting object.

References

Explanatory Model Analysis. Explore, Explain and Examine Predictive Models. <https://ema.drwhy.ai/>

print.funnel_measure *Print funnel_measure object*

Description

Print funnel_measure object

Usage

```
## S3 method for class 'funnel_measure'
print(x, ...)
```

Arguments

```
x          an object of class funnel_measure
...        other parameters
```

Examples

```
library("DALEXtra")
library("mlr")
task <- mlr::makeRegrTask(
  id = "R",
  data = apartments,
  target = "m2.price"
)
learner_lm <- mlr::makeLearner(
  "regr.lm"
)
model_lm <- mlr::train(learner_lm, task)
explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")

learner_rf <- mlr::makeLearner(
  "regr.randomForest"
)
model_rf <- mlr::train(learner_rf, task)
explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")

learner_gbm <- mlr::makeLearner(
  "regr.gbm"
)
model_gbm <- mlr::train(learner_gbm, task)
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "GBM")

plot_data <- funnel_measure(explainer_lm, list(explainer_rf, explainer_gbm),
  nbins = 5, measure_function = DALEX::loss_root_mean_square)
print(plot_data)
```

```
print.overall_comparison
```

```
Print overall_comparison object
```

Description

```
Print overall_comparison object
```


Usage

```
## S3 method for class 'overall_comparison'  
print(x, ...)
```

Arguments

```
x                an object of class overall_comparison  
...             other parameters
```

Examples

```
library("DALEXtra")  
library("mlr")  
task <- mlr::makeRegrTask(  
  id = "R",  
  data = apartments,  
  target = "m2.price"  
)  
learner_lm <- mlr::makeLearner(  
  "regr.lm"  
)  
model_lm <- mlr::train(learner_lm, task)  
explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")  
  
learner_rf <- mlr::makeLearner(  
  "regr.randomForest"  
)  
model_rf <- mlr::train(learner_rf, task)  
explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")  
  
learner_gbm <- mlr::makeLearner(  
  "regr.gbm"  
)  
model_gbm <- mlr::train(learner_gbm, task)  
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "gbm")  
  
data <- overall_comparison(explainer_lm, list(explainer_gbm, explainer_rf), type = "regression")  
print(data)
```

print.scikitlearn_set *Prints scikitlearn_set class*

Description

Prints scikitlearn_set class

Usage

```
## S3 method for class 'scikitlearn_set'
print(x, ...)
```

Arguments

x a list from explainer created with [explain_scikitlearn](#)
 ... other arguments

```
print.training_test_comparison
                                  Print funnel_measure object
```

Description

Print funnel_measure object

Usage

```
## S3 method for class 'training_test_comparison'
print(x, ...)
```

Arguments

x an object of class funnel_measure
 ... other parameters

Examples

```
library("mlr")
library("DALEXtra")
task <- mlr::makeRegrTask(
  id = "R",
  data = apartments,
  target = "m2.price"
)
learner_lm <- mlr::makeLearner(
  "regr.lm"
)
model_lm <- mlr::train(learner_lm, task)
explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")

learner_rf <- mlr::makeLearner(
  "regr.randomForest"
)
model_rf <- mlr::train(learner_rf, task)
explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")
```

```

learner_gbm <- mlr::makeLearner(
  "regr.gbm"
)
model_gbm <- mlr::train(learner_gbm, task)
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "GBM")

data <- training_test_comparison(explainer_lm, list(explainer_gbm, explainer_rf),
                                training_data = apartments,
                                training_y = apartments$m2.price)

print(data)

```

training_test_comparison

Compare performance of model between training and test set

Description

Function `training_test_comparison` calculates performance of the provided model based on specified measure function. Response of the model is calculated based on test data, extracted from the explainer and training data, provided by the user. Output can be easily shown with `print` or `plot` function.

Usage

```

training_test_comparison(
  champion,
  challengers,
  training_data,
  training_y,
  measure_function = NULL
)

```

Arguments

`champion` - explainer of champion model.

`challengers` - explainer of challenger model or list of explainers.

`training_data` - data without target column that will be passed to predict function and then to measure function. Keep in mind that they have to differ from data passed to an explainer.

`training_y` - target column for `training_data`

`measure_function` - measure function that calculates performance of model based on true observation and prediction. Order of parameters is important and should be `(y, y_hat)`. By default it is RMSE.

Value

An object of the class `training_test_comparison`.

It is a named list containing:

- `data` `data.frame` with following columns
 - `measure_test` performance on test set
 - `measure_train` performance on training set
 - `label` label of explainer
 - `type` flag that indicates if explainer was passed as champion or as challenger.
- `models_info` `data.frame` containing information about models used in analysis

Examples

```
library("mlr")
library("DALEXtra")
task <- mlr::makeRegrTask(
  id = "R",
  data = apartments,
  target = "m2.price"
)
learner_lm <- mlr::makeLearner(
  "regr.lm"
)
model_lm <- mlr::train(learner_lm, task)
explainer_lm <- explain_mlr(model_lm, apartmentsTest, apartmentsTest$m2.price, label = "LM")

learner_rf <- mlr::makeLearner(
  "regr.randomForest"
)
model_rf <- mlr::train(learner_rf, task)
explainer_rf <- explain_mlr(model_rf, apartmentsTest, apartmentsTest$m2.price, label = "RF")

learner_gbm <- mlr::makeLearner(
  "regr.gbm"
)
model_gbm <- mlr::train(learner_gbm, task)
explainer_gbm <- explain_mlr(model_gbm, apartmentsTest, apartmentsTest$m2.price, label = "GBM")

data <- training_test_comparison(explainer_lm, list(explainer_gbm, explainer_rf),
                                training_data = apartments,
                                training_y = apartments$m2.price)

plot(data)
```

Description

These functions are default predict functions. Each function returns a single numeric score for each new observation. Those functions are very important since information from many models has to be extracted with various techniques.

Usage

```
## S3 method for class 'WrappedModel'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'H2ORegressionModel'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'H2OBinomialModel'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'H2OMultinomialModel'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'scikitlearn_model'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'keras'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'LearnerRegr'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'LearnerClassif'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'GraphLearner'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'xgb.Booster'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'workflow'  
yhat(X.model, newdata, ...)
```

Arguments

X.model	object - a model to be explained
newdata	data.frame or matrix - observations for prediction
...	other parameters that will be passed to the predict function

Details

Currently supported packages are:

- mlr see more in [explain_mlr](#)
- h2o see more in [explain_h2o](#)
- scikit-learn see more in [explain_scikitlearn](#)
- keras see more in [explain_keras](#)
- mlr3 see more in [explain_mlr3](#)
- xgboost see more in [explain_xgboost](#)
- tidymodels see more in [explain_tidymodels](#)

Value

An numeric vector of predictions

Index

champion_challenger, 2
create_env, 4

explain, 6, 8, 9, 12, 14, 15, 19, 21
explain_h2o, 5, 38
explain_keras, 7, 38
explain_mlr, 10, 38
explain_mlr3, 12, 38
explain_scikitlearn, 9, 14, 34, 38
explain_tidymodels, 17, 38
explain_xgboost, 19, 38

funnel_measure, 2, 3, 22, 27

geom_point, 27

model_info.GraphLearner
(model_info.WrappedModel), 24
model_info.H2OBinomialModel
(model_info.WrappedModel), 24
model_info.H2OMultinomialModel
(model_info.WrappedModel), 24
model_info.H2ORegressionModel
(model_info.WrappedModel), 24
model_info.keras
(model_info.WrappedModel), 24
model_info.LearnerClassif
(model_info.WrappedModel), 24
model_info.LearnerRegr
(model_info.WrappedModel), 24
model_info.scikitlearn_model
(model_info.WrappedModel), 24
model_info.workflow
(model_info.WrappedModel), 24
model_info.WrappedModel, 24
model_info.xgb.Booster
(model_info.WrappedModel), 24
model_performance, 25, 26
model_type.dalex_explainer
(predict_surrogate), 30

overall_comparison, 2, 3, 25, 28

plot.funnel_measure, 3, 26
plot.overall_comparison, 28
plot.predict_surrogate_lime
(predict_surrogate), 30
plot.training_test_comparison, 29
plot_radar, 28
predict_model.dalex_explainer
(predict_surrogate), 30
predict_parts (predict_surrogate), 30
predict_parts_break_down
(predict_surrogate), 30
predict_parts_ibreak_down
(predict_surrogate), 30
predict_parts_shap (predict_surrogate),
30
predict_surrogate, 30
predict_surrogate_aml
(predict_surrogate), 30
predict_surrogate_lime
(predict_surrogate), 30
predict_surrogate_local_model
(predict_surrogate), 30
print.funnel_measure, 31
print.overall_comparison, 32
print.scikitlearn_set, 33
print.training_test_comparison, 34

training_test_comparison, 2, 3, 29, 35

yhat.GraphLearner (yhat.WrappedModel),
36
yhat.H2OBinomialModel
(yhat.WrappedModel), 36
yhat.H2OMultinomialModel
(yhat.WrappedModel), 36
yhat.H2ORegressionModel
(yhat.WrappedModel), 36
yhat.keras (yhat.WrappedModel), 36

yhat.LearnerClassif
 (yhat.WrappedModel), 36
yhat.LearnerRegr (yhat.WrappedModel), 36
yhat.scikitlearn_model
 (yhat.WrappedModel), 36
yhat.workflow (yhat.WrappedModel), 36
yhat.WrappedModel, 36
yhat.xgb.Booster (yhat.WrappedModel), 36