

Package ‘rcosmo’

December 1, 2021

URL <https://github.com/frycast/rcosmo>

BugReports <https://github.com/frycast/rcosmo/issues>

Title Cosmic Microwave Background Data Analysis

Version 1.1.3

Description Handling and Analysing Spherical,
HEALPix and Cosmic Microwave Background data on a HEALPix grid.

Depends R (>= 3.4.0)

License GPL-3 | file LICENSE

Encoding UTF-8

Imports FITSio (>= 2.1-0), Rcpp (>= 0.12.11), mmap (>= 0.6-17), tibble
(>= 1.4.2), rgl (>= 0.99.16), cli (>= 1.0.0), entropy (>=
1.2.1), geoR (>= 1.7-5.2.1), nnls (>= 1.4)

Suggests knitr, rmarkdown, testthat, R.rsp, gsl

LinkingTo Rcpp

RoxygenNote 7.1.2

NeedsCompilation yes

Author Daniel Fryer [aut, cre] (<<https://orcid.org/0000-0001-6032-0522>>),
Andriy Olenko [aut] (<<https://orcid.org/0000-0002-0917-7000>>),
Ming Li [aut] (<<https://orcid.org/0000-0002-1218-2804>>),
Yuguang Wang [aut]

Maintainer Daniel Fryer <d.fryer@latrobe.edu.au>

Repository CRAN

Date/Publication 2021-12-01 09:30:02 UTC

R topics documented:

| | |
|-------------------------------|---|
| ancestor | 4 |
| areCompatibleCMBDFs | 4 |
| as.CMBDataFrame | 5 |
| assumedConvex | 6 |

| | |
|----------------------------------|----|
| assumedUniquePix | 7 |
| baseNeighbours | 8 |
| cbind.CMBDataFrame | 8 |
| chi2CMB | 9 |
| children | 10 |
| CMBDat | 10 |
| CMBDataFrame | 11 |
| CMBWindow | 13 |
| coords | 14 |
| coords.CMBDataFrame | 15 |
| coords.CMBWindow | 16 |
| coords.data.frame | 17 |
| coords.HPDataFrame | 18 |
| corrCMB | 19 |
| covCMB | 21 |
| covmodelCMB | 22 |
| covPwSp | 24 |
| displayPixelBoundaries | 25 |
| displayPixels | 26 |
| downloadCMBMap | 27 |
| downloadCMBPS | 29 |
| entropyCMB | 30 |
| exprob | 31 |
| extrCMB | 32 |
| fmf | 33 |
| fRen | 34 |
| geo2sph | 35 |
| geoAngle | 36 |
| geoArea | 36 |
| geoArea.CMBDataFrame | 37 |
| geoArea.CMBWindow | 38 |
| geoArea.HPDataFrame | 38 |
| geoDist | 39 |
| header | 40 |
| healpixCentered | 41 |
| HPDataFrame | 41 |
| ibp2p | 44 |
| is.CMBDat | 45 |
| is.CMBDataFrame | 46 |
| is.CMBWindow | 46 |
| is.HPDataFrame | 47 |
| linesCMB | 47 |
| maxDist | 49 |
| maxWindowDist | 50 |
| minDist | 50 |
| neighbours | 51 |
| nest2ring | 52 |
| nestSearch | 53 |

| | |
|---------------------------------|----|
| inside | 54 |
| inside.CMBDataFrame | 55 |
| inside.HPDataFrame | 55 |
| numeric2col | 56 |
| ordering | 56 |
| ordering.CMBDataFrame | 57 |
| ordering.HPDataFrame | 58 |
| p2bp | 58 |
| p2ibp | 59 |
| parent | 59 |
| pix | 60 |
| pix.CMBDataFrame | 60 |
| pix.HPDataFrame | 61 |
| pix2coords | 62 |
| pixelArea | 62 |
| pixelWindow | 63 |
| plot.CMBCorrelation | 64 |
| plot.CMBCovariance | 65 |
| plot.CMBDataFrame | 65 |
| plot.CMBWindow | 67 |
| plot.HPDataFrame | 68 |
| plot.variogram | 70 |
| plotAngDis | 71 |
| plotcovmodelCMB | 72 |
| plotvariogram | 73 |
| practicalRangeCMB | 74 |
| print.CMBDataFrame | 75 |
| print.HPDataFrame | 75 |
| pwSpCorr | 76 |
| qqnormWin | 77 |
| qqplotWin | 78 |
| qstat | 79 |
| rbind.CMBDataFrame | 80 |
| rcosmo | 81 |
| resolution | 82 |
| ring2nest | 82 |
| sampleCMB | 83 |
| siblings | 84 |
| sphericalHarmonics | 84 |
| summary.CMBDataFrame | 85 |
| summary.CMBWindow | 86 |
| summary.HPDataFrame | 87 |
| triangulate | 87 |
| variofitCMB | 88 |
| variogramCMB | 91 |
| window | 92 |
| window.CMBDat | 93 |
| window.CMBDataFrame | 94 |

| | |
|------------------------------|----|
| window.data.frame | 97 |
| window.HPDataFrame | 98 |
| winType | 99 |

Index 101

ancestor *Return index of kth ancestor pixel*

Description

Gives the pixel at resolution $j - k$ that contains p , where p is specified at resolution j (notice it does not depend on j).

Usage

```
ancestor(p, k)
```

Arguments

| | |
|---|--|
| p | A pixel index specified in nested order. |
| k | A generation of an ancestor pixel. |

Examples

```
ancestor(4,2)
ancestor(17,2)
```

areCompatibleCMBDFs *Check compatibleness of CMBDataFrames*

Description

Compare attributes to decide if two CMBDataFrames are compatible

Usage

```
areCompatibleCMBDFs(cmbdf1, cmbdf2, compare.pix = FALSE)
```

Arguments

| | |
|-------------|---|
| cmbdf1 | a CMBDataFrame |
| cmbdf2 | a CMBDataFrame |
| compare.pix | A boolean. If TRUE then cmbdf1 and cmbdf2 must share the same pixel indices to be considered compatible |

Details

If the CMBDataFrames do not have compatible attributes then a message is printed indicating the attributes that do not match. To suppress this use the `suppressMessages` function

Examples

```
a <- CMBDataFrame(inside = 2, ordering = "ring", coords = "cartesian")
b <- CMBDataFrame(inside = 1, ordering = "nested", coords = "spherical")
areCompatibleCMBDFs(a,b)

suppressMessages(areCompatibleCMBDFs(a,b))
```

as.CMBDataFrame *Convert objects to CMBDataFrame*

Description

Safely converts a `data.frame` to a CMBDataFrame. The rows of the data.frame are assumed to be in the HEALPix order given by `ordering`, and at the HEALPix resolution given by `inside`. Coordinates, if present, are assumed to correspond to HEALPix pixel centers. The coordinates must be named either `x,y,z` (cartesian) or `theta, phi` (spherical colatitude and longitude respectively). If `df` is a HPDataFrame then it is possible that `df` has attribute `healpixCentered = TRUE`, in which case `as.CMBDataFrame` will perform HEALPix centering of coordinates.

Usage

```
as.CMBDataFrame(df, ordering, inside, spix, drop.coords = FALSE)
```

Arguments

| | |
|--------------------------|--|
| <code>df</code> | Any <code>data.frame</code> or HPDataFrame whose rows are in HEALPix order |
| <code>ordering</code> | character string that specifies the ordering scheme ("ring" or "nested") |
| <code>inside</code> | an integer 2^k that specifies the Nside (resolution) HEALPix parameter |
| <code>spix</code> | an integer vector that specifies the HEALPix pixel index corresponding to each row of <code>df</code> . If <code>spix</code> is left blank and <code>df</code> is a <code>data.frame</code> , then <code>df</code> is assumed to contain data for every pixel at resolution parameter <code>inside</code> (the full sky). In other words, in this case, the number of rows of <code>df</code> must be equal to $12 * \text{inside}^2$. However, if <code>spix</code> is left blank and <code>df</code> is a CMBDataFrame, then <code>spix</code> is set equal to <code>pix(df)</code> |
| <code>drop.coords</code> | A logical. If <code>df</code> is a HPDataFrame then it is possible that <code>df</code> has attribute <code>healpixCentered = TRUE</code> , in which case <code>as.CMBDataFrame</code> will perform HEALPix centering of coordinates. If <code>drop.coords = TRUE</code> then this will be done by dropping existing coordinates entirely (quicker) to rely only on HEALPix pixel indices. Otherwise if <code>drop.coords = FALSE</code> this will be done by replacing existing coordinates with locations of HEALPix pixel centers. |

Value

A CMBDataFrame

Examples

```
## Example 1: Create df with no coords, then create CMBDataFrames cmbdf and
## df2 with spherical coords

df <- data.frame(I=rnorm(12))
df

cmbdf <- as.CMBDataFrame(df,ordering= "ring", nside=1)
summary(cmbdf)
pix(cmbdf)
coords(cmbdf)

df2 <- coords(cmbdf, new.coords = "spherical")
df2

## Example 2: Create CMBDataFrames for first 10 Healpix centers

df <- data.frame(I=rnorm(10))
df
cmbdf <- as.CMBDataFrame(df,ordering= "ring", nside=2, spix=1:10)
summary(cmbdf)
pix(cmbdf)
```

assumedConvex

Check if a [CMBWindow](#) is assumed convex.

Description

Initially any [CMBWindow](#) is not assumed convex. The assumedConvex attribute can be change for any [CMBWindow](#).

Usage

```
assumedConvex(win, assume.convex)
```

Arguments

win a CMBWindow object
assume.convex optionally change the assumedConvex attribute to TRUE or FALSE

Examples

```
win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
assumedConvex(win1)
win2 <- assumedConvex(win1, assume.convex = TRUE)
assumedConvex(win2)
assumedConvex(win1) <- TRUE
assumedConvex(win1)
```

| | |
|------------------|---|
| assumedUniquePix | <i>Check if object was assumed to have unique HEALPix indices</i> |
|------------------|---|

Description

The function checks object's attribute `assumedUniquePix`. The attribute is `True` if the object was assumed to have rows that correspond to unique HEALPix pixel indices.

Usage

```
assumedUniquePix(obj)
```

Arguments

`obj` Any object.

Value

A boolean. This is `TRUE` if `obj` is a `CMBDataFrame` or a `HPDataFrame` whose rows were assumed to correspond to unique HEALPix pixel indices.

Examples

```
hp1 <- HPDataFrame(I=rnorm(5), nside = 1, spix = c(1,1,2,2,3))
pix(hp1)
coords(hp1, new.coords = "cartesian")
assumedUniquePix(hp1)

sky <- CMBDataFrame(nside = 32, coords = "cartesian", ordering = "nested")
sky.s <- CMBDataFrame(sky, sample.size = 100)
hpdf <- HPDataFrame(sky.s, auto.spix = TRUE)
assumedUniquePix(hpdf)
```

| | |
|----------------|---|
| baseNeighbours | <i>Return neighbours of base pixels</i> |
|----------------|---|

Description

The base-resolution comprises twelve pixels. `baseNeighbours` returns a map from the base pixel index `bp` to the vector of base pixels that are neighbours of `bp`, in counterclockwise order of direction: S,SE,E,NE,N,NW,W,SW. The presence of -1 indicates that the corresponding direction is empty.

Usage

```
baseNeighbours(bp)
```

Arguments

| | |
|-----------------|----------------------|
| <code>bp</code> | The base pixel index |
|-----------------|----------------------|

Examples

```
## Return neighbours of base pixel 1
baseNeighbours(1)

## There is no base pixel 14, so baseNeighbours returns NULL
baseNeighbours(14)
```

| | |
|--------------------|--------------------------------|
| cbind.CMBDataFrame | <i>cbind for CMBDataFrames</i> |
|--------------------|--------------------------------|

Description

Add a new column or columns (vector, matrix or data.frame) to a `CMBDataFrame`. Note that method dispatch occurs on the first argument. So, the `CMBDataFrame` must be the first argument

Usage

```
## S3 method for class 'CMBDataFrame'
cbind(..., deparse.level = 1)
```

Arguments

| | |
|----------------------------|--|
| <code>...</code> | (generalized) vectors or matrices. Columns to bind. |
| <code>deparse.level</code> | Integer controlling the construction of labels in the case of non-matrix-like arguments. |

Details

See the documentation for [cbind](#)

Examples

```
cmbdf <- CMBDataFrame(nside = 1, ordering = "nested", coords = "spherical")
cmbdf2 <- cbind(cmbdf, myData = rep(1, 12))
cmbdf2
```

| | |
|---------|---|
| chi2CMB | <i>Chi-squared statistic for two CMBWindows</i> |
|---------|---|

Description

This function returns the empirical chi-squared statistic for intensities observations from two [CMBWindows](#) of the specified [CMBDataFrame](#). The functions employs the function [chi2.empirical](#) and uses histogram counts of intensities for computations.

Usage

```
chi2CMB(cmbdf, win1, win2, intensities = "I")
```

Arguments

| | |
|-------------|---|
| cmbdf | A CMBDataFrame . |
| win1 | A CMBWindow |
| win2 | A CMBWindow |
| intensities | A CMBDataFrame column with measured values. |

Value

Estimated Chi-squared statistic for observations in two [CMBWindows](#). For small sample sizes and many zero counts Chi-squared statistic is inefficient.

References

[chi2.empirical](#)

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 1000)
#
# win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
# win2 <- CMBWindow(theta = c(pi/2,pi,pi/2), phi = c(0,0,pi/2))
# plot(win1)
# plot(win2,col="green")
#
# chi2CMB(cmbdf, win1, win2)
```

| | |
|----------|-----------------------------------|
| children | <i>Return children of a pixel</i> |
|----------|-----------------------------------|

Description

Gives four pixels at resolution $j + 1$ that are contained in p , where p is a pixel specified at resolution j (notice it does not depend on j).

Usage

```
children(p)
```

Arguments

`p` A pixel index specified in nested order.

Examples

```
children(11)
```

| | |
|--------|---------------------|
| CMBDat | <i>CMBDat class</i> |
|--------|---------------------|

Description

The function CMBDat creates objects of class CMBDat. These are lists containing header information and other metadata as well as an element called data, whose columns may include, for example, the intensity (I), polarisation (Q, U), PMASK and TMASK. It also may contain an `mmap` object that points to the CMB map data table in the FITS file.

Usage

```
CMBDat(filename, mmap = FALSE, spix)
```

Arguments

| | |
|----------|--|
| filename | The path to the fits file. |
| mmap | A boolean indicating whether to use memory mapping. |
| spix | The sample pixels (rows) to read from the FITS file binary data table (optional) |

Value

A list containing header information and other metadata as well as an element called data where: If `mmap = FALSE` then a `data.frame` is included, named `data`, whose columns may include, for example, the intensity (I), polarisation (Q, U), PMASK and TMASK. If `mmap = TRUE` then a [mmap](#) object is returned that points to the CMB map data table in the FITS file.

Examples

```
## Ensure you have a FITS file with the correct path
## before running the example:
## download a FITS file and use real data
# downloadCMBMap()
# cmbdat <- CMBDat("CMB_map_smica1024.fits", mmap = TRUE)
# class(cmbdat)
# str(cmbdat)

## View metadata
# cmbdat$header1
# cmbdat$header2
# cmbdat$resoln
# cmbdat$method
# cmbdat$coordsys
# cmbdat$nside
# cmbdat$hdr
```

CMBDataFrame

CMBDataFrame class

Description

The function `CMBDataFrame` creates objects of class `CMBDataFrame`. These are a special type of [data.frame](#) that carry metadata about, e.g., the HEALPix ordering scheme, coordinate system, and `nside` parameter.

Usage

```
CMBDataFrame(
  CMBData,
  coords,
  win,
  include.polar = FALSE,
  include.masks = FALSE,
  spix,
  sample.size,
  nside,
  ordering,
  I,
  ...
)
```

Arguments

| | |
|---------------|---|
| CMBData | Can be a string location of FITS file, another CMBDataFrame, a CMBData object, a HPDataFrame or unspecified. |
| coords | Can be "spherical," "cartesian", or unspecified (HEALPix only). |
| win | optional CMBWindow object that specifies a spherical polygon within which to subset the full sky CMB data. |
| include.polar | TRUE if polarisation data is required, otherwise FALSE. |
| include.masks | TRUE if TMASK and PMASK are required, otherwise FALSE. |
| spix | Optional vector of sample pixel indices, or a path to a file containing comma delimited sample pixel indices. The ordering scheme is given by ordering. If ordering is unspecified then CMBData must be either a CMBDataFrame or a FITS file and the ordering scheme is then assumed to match that of CMBData. |
| sample.size | If a positive integer is given, a simple random sample of size equal to sample.size will be taken from CMBData. If spix is specified then sample.size must be unspecified. |
| nside | Optionally specify the nside parameter manually $nside=2^k$ (usually 1024 or 2048). |
| ordering | Specifies the desired HEALPix ordering scheme ("ring" or "nested") for the output CMBDataFrame. If ordering is unspecified then the ordering scheme will be taken from the CMBData object. If ordering information cannot be found the default will be "nested". This parameter also specifies the ordering scheme of spix. |
| I | A vector of intensities to be included if CMBData is unspecified. Note that $\text{length}(I)$ must equal $12 * nside^2$ if either spix or sample.size are unspecified. |
| ... | Optional names data columns of length $\text{nrow}(\text{CMBData})$ to add to the CMBDataFrame. |

Value

A CMBDataFrame whose row.names attribute contains HEALPix indices.

Examples

```
## Method 1: Read the data while constructing the CMBDataFrame
## download a FITS file and use real data
# downloadCMBMap()
# df <- CMBDataFrame("CMB_map_smica1024.fits")
df <- CMBDataFrame(nside = 16, I = rnorm(12 * 16 ^ 2),
                  ordering = "nested")

# Specify a sample size for a random sample
df.sample <- CMBDataFrame(df, sample.size = 80)
plot(df.sample)

# Specify a vector of pixel indices using spix
df.subset <- CMBDataFrame(df, spix = c(2,4,6))

# Take a look at the summary
summary(df)

# Access HEALPix pixel indices using pix function
# (these are stored in the row.names attribute)
pix(df.subset)
```

CMBWindow

CMBWindow class.

Description

The function CMBWindow creates objects of class CMBWindow. It is either a polygon or a disc type.

Usage

```
CMBWindow(..., r, set.minus = FALSE, assume.convex = FALSE)
```

Arguments

| | |
|---------------|---|
| ... | these arguments are compulsory and must be labelled either x, y, z (cartesian) or theta, phi (spherical, colatitude and longitude respectively). Alternatively, a single data.frame may be passed in with columns labelled x, y, z or theta, phi. |
| r | if a disc type window is required then this specifies the radius of the disc |
| set.minus | when TRUE the window will be the unit sphere minus the window specified |
| assume.convex | when TRUE the window is assumed to be convex resulting in a faster computation time when the window is used with functions such as subWindow . This argument is irrelevant when the window is not a polygon |

Details

If `r` is unspecified then the rows of `...` correspond to counter-clockwise ordered vertices defining a spherical polygon lying entirely within one open hemisphere on the unit sphere. Counter-clockwise is understood from the perspective outside the sphere, facing the hemisphere that contains the polygon, looking toward the origin. Note that there must be at least 3 rows (vertices) to define a polygon (we exclude bygones). On the other hand, if `r` is specified then `...` must specify just one row, and this row is taken to be the center of a disc of radius `r`

Examples

```
win <- CMBWindow(theta = c(pi/2,pi/2,pi/3, pi/3), phi = c(0,pi/3,pi/3,0))
plot(win)

## Create a disc type window
win1<- CMBWindow(x=0,y=3/5,z=4/5,r=0.8, set.minus =TRUE)
plot(win1)

## Apply a disc type window to CMBDataFrame
cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian", ordering = "nested")
window(cmbdf) <- CMBWindow(x=0,y=3/5,z=4/5,r=0.8, set.minus =TRUE)
plot(cmbdf)
```

| | |
|--------|--------------------------------------|
| coords | <i>Coordinate conversion generic</i> |
|--------|--------------------------------------|

Description

Detailed descriptions and examples can be found in documentation for specific `coords` functions [coords.CMBDataFrame](#), [coords.CMBWindow](#), [coords.HPDataFrame](#), [coords.data.frame](#)

Usage

```
coords(x, ...)
```

Arguments

| | |
|------------------|-------------------|
| <code>x</code> | An object. |
| <code>...</code> | Unused arguments. |

See Also

[coords.CMBDataFrame](#) [coords.CMBWindow](#) [coords.HPDataFrame](#) [coords.data.frame](#)

coords.CMBDataFrame *Coordinate system from a CMBDataFrame*

Description

If `new.coords` is unspecified then this function returns the coordinate system used in the CMBDataFrame `cmbdf`. The coordinate system is either "cartesian" or "spherical". If a new coordinate system is specified, using e.g. `new.coords = "spherical"`, then this function instead returns a new CMBDataFrame whose coordinates are of the specified type. The original CMBDataFrame, `cmbdf`, is unaffected. If you would like to change `cmbdf` without creating a new variable, then use `coords<- .CMBDataFrame` (see examples below).

Usage

```
## S3 method for class 'CMBDataFrame'  
coords(x, new.coords, ...)
```

Arguments

| | |
|-------------------------|---|
| <code>x</code> | A CMBDataFrame, <code>cmbdf</code> . |
| <code>new.coords</code> | Specifies the new coordinate system ("spherical" or "cartesian") if a change of coordinate system is desired. |
| <code>...</code> | Unused arguments. |

Value

If `new.coords` is unspecified, then the name of the coordinate system of `cmbdf` is returned. Otherwise a new CMBDataFrame is returned equivalent to `cmbdf` but having the desired change of coordinates

Examples

```
## Create df with no coords, then create df2 with cartesian coords  
df <- CMBDataFrame(nside = 16)  
df  
coords(df)  
df2 <- coords(df, new.coords = "cartesian")  
coords(df2)  
  
## Change the coords of df directly (to spherical)  
coords(df) <- "spherical"  
coords(df)
```

coords.CMBWindow *Coordinate system from a CMBWindow*

Description

This function returns the coordinate system used in a `CMBWindow`. The coordinate system is either "cartesian" or "spherical"

Usage

```
## S3 method for class 'CMBWindow'  
coords(x, new.coords, ...)
```

Arguments

| | |
|------------|--|
| x | a <code>CMBWindow</code> , win. |
| new.coords | specifies the new coordinate system ("spherical" or "cartesian") if a change of coordinate system is desired |
| ... | Unused arguments. |

Details

If a new coordinate system is specified, using e.g. `new.coords = "spherical"`, the coordinate system of the `CMBWindow` will be converted

Value

If `new.coords` is unspecified, then the name of the coordinate system of win is returned. Otherwise a new `CMBWindow` is returned equivalent to win but having the desired change of coordinates

Examples

```
## Create win with sperical coords, then change it to win1 with cartesian coords  
win <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))  
coords(win)  
win1 <- coords(win, new.coords = "cartesian")  
coords(win1)  
  
## Change back to spherical coordinates  
  
coords(win1) <- "spherical"  
coords(win1)
```

coords.data.frame *Create a new data.frame with a given coordinate system*

Description

This does not affect the original object unless new coordinate system is directly assigned.

Usage

```
## S3 method for class 'data.frame'  
coords(x, new.coords, ...)
```

Arguments

| | |
|------------|--|
| x | a data.frame with columns labelled x, y, z (for cartesian) or theta, phi (for spherical colatitude and longitude respectively) |
| new.coords | specifies the new coordinate system ("spherical" or "cartesian"). |
| ... | Unused arguments. |

Value

A new data.frame whose coordinates are as specified by new.coords

Examples

```
## Create df with no coords, then create df2 with spherical coords  
df <- data.frame(x = c(1,0,0), y = c(0,1,0), z = c(0,0,1))  
df  
  
df2 <- coords(df, new.coords = "spherical")  
df2  
  
## The function coords does not affect the original object.  
## To change the coords assign a new value ("spherical" or "cartesian")  
  
coords(df, new.coords = "spherical")  
df  
coords(df) <- "spherical"  
df
```

coords.HPDataFrame *Coordinate system from a HPDataFrame*

Description

Add or change coordinates in a [HPDataFrame](#). This does not affect the argument object `hpdf`. Instead it returns a new [HPDataFrame](#) with the desired coordinates. To change `hpdf` directly see [coords<- .HPDataFrame](#).

Usage

```
## S3 method for class 'HPDataFrame'
coords(x, new.coords, healpixCentered = FALSE, ...)
```

Arguments

| | |
|------------------------------|--|
| <code>x</code> | a HPDataFrame , <code>hpdf</code> . |
| <code>new.coords</code> | specifies the new coordinate system ("spherical" or "cartesian") |
| <code>healpixCentered</code> | boolean. If TRUE then columns <code>x,y,z</code> or <code>theta, phi</code> will be ignored and removed if present. This forces the coordinates to be found from HEALPix pixel indices only. Then the <code>HEALPixCentered</code> attribute of <code>hpdf</code> will be set to TRUE. |
| <code>...</code> | Unused arguments. |

Details

If columns exist labelled `x,y,z` (cartesian) or `theta, phi` (colatitude and longitude respectively), then these will be treated as the coordinates of `hpdf` and converted accordingly. If columns `x,y,z` or `theta,phi` are not present then the healpix pixel indices as given by `pix(hpdf)` are used for assigning coordinates.

Value

A [HPDataFrame](#) with columns `x,y,z` (cartesian) or `theta, phi` (colatitude and longitude respectively)

Examples

```
df <- HPDataFrame(I = rep(0,12), nside = 1)
coords(df, new.coords = "cartesian")
# Notice that df is unchanged
df

# Instead, change df directly
coords(df) <- "spherical"

## specify cartesian coordinates then convert to spherical
hp1 <- HPDataFrame(x = c(1,0,0), y = c(0,1,0), z = c(0,0,1),
                  nside = 1, auto.spix = TRUE)
```

```

hp1 <- coords(hp1, new.coords = "spherical")

## Instead, ignore/drop existing coordinates and use HEALPix only
hp2 <- HPDataFrame(x = c(1,0,0), y = c(0,1,0), z = c(0,0,1),
                  nside = 1, auto.spix = TRUE)
hp2 <- coords(hp1, new.coords = "spherical", healpixCentered = TRUE)

```

corrCMB

*Sample correlation function***Description**

This function provides an empirical correlation function for data in a [CMBDataFrame](#) or `data.frame`. It assumes that data are from a stationary spherical random field and the correlation depends only on a geodesic distance between locations. Output is a binned correlation.

Usage

```

corrCMB(
  cmbdf,
  num.bins = 10,
  sample.size,
  max.dist = pi,
  breaks,
  equiareal = TRUE,
  calc.max.dist = FALSE
)

```

Arguments

| | |
|----------------------------|--|
| <code>cmbdf</code> | is a CMBDataFrame or <code>data.frame</code> |
| <code>num.bins</code> | specifies the number of bins |
| <code>sample.size</code> | optionally specify the size of a simple random sample to take before calculating correlation. This may be useful if the full correlation computation is too slow. |
| <code>max.dist</code> | an optional number between 0 and π specifying the maximum geodesic distance to use for calculating correlation. Only used if <code>breaks</code> are unspecified. |
| <code>breaks</code> | optionally specify the breaks manually using a vector giving the break points between cells. This vector has length <code>num.bins</code> since the last break point is taken as <code>max.dist</code> . If <code>equiareal = TRUE</code> then these breaks should be $\cos(r_i)$ where r_i are radii. If <code>equiareal = FALSE</code> then these breaks should be r_i . |
| <code>equiareal</code> | if <code>TRUE</code> then the bins have equal spherical area. If <code>false</code> then the bins have equal annular widths. Default is <code>TRUE</code> . |
| <code>calc.max.dist</code> | if <code>TRUE</code> then the <code>max.dist</code> will be calculated from the locations in <code>cmbdf</code> . Otherwise either <code>max.dist</code> must be specified or <code>max.dist</code> will default to π . |

Value

#' An object of the class `CMBCorrelation` that is a modification of `variog` from the package `geoR` with variogram values replaced by correlation.

The attribute "breaks" contains the break points used to create bins. The result has `num.bins + 1` values since the first value at distance 0 is not counted as a bin.

u a vector with distances.

v a vector with estimated correlation values at distances given in `u`.

n number of pairs in each bin

sd standard deviation of the values in each bin

bins.lim limits defining the interval spanned by each bin

ind.bin a logical vector indicating whether the number of pairs in each bin is greater or equal to the value in the argument `pairs.min`

var.mark variance of the data

beta.ols parameters of the mean part of the model fitted by ordinary least squares

output.type echoes the option argument

max.dist maximum distance between pairs allowed in the correlation calculations

n.data number of data

direction direction for which the correlation was computed

call the function call

References

`geoR` package, `variog`, `variogramCMB`, `covCMB`

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 100000)
# corcmb <- corrCMB(cmbdf, max.dist = 0.03, num.bins = 10, sample.size=1000)
# corcmb
```

| | |
|--------|-----------------------------------|
| covCMB | <i>Sample covariance function</i> |
|--------|-----------------------------------|

Description

This function provides an empirical covariance function for data in a [CMBDataFrame](#) or `data.frame`. It assumes that data are from a stationary spherical random field and the covariance depends only on a geodesic distance between locations. Output is a binned covariance.

Usage

```
covCMB(
  cmbdf,
  num.bins = 10,
  sample.size,
  max.dist = pi,
  breaks,
  equiareal = TRUE,
  calc.max.dist = FALSE
)
```

Arguments

| | |
|----------------------------|--|
| <code>cmbdf</code> | is a CMBDataFrame or <code>data.frame</code> |
| <code>num.bins</code> | specifies the number of bins |
| <code>sample.size</code> | optionally specify the size of a simple random sample to take before calculating covariance. This may be useful if the full covariance computation is too slow. |
| <code>max.dist</code> | an optional number between 0 and pi specifying the maximum geodesic distance to use for calculating covariance. Only used if breaks are unspecified. |
| <code>breaks</code> | optionally specify the breaks manually using a vector giving the break points between cells. This vector has length <code>num.bins</code> since the last break point is taken as <code>max.dist</code> . If <code>equiareal = TRUE</code> then these breaks should be $\cos(r_i)$ where r_i are radii. If <code>equiareal = FALSE</code> then these breaks should be r_i . |
| <code>equiareal</code> | if TRUE then the bins have equal spherical area. If false then the bins have equal annular widths. Default is TRUE. |
| <code>calc.max.dist</code> | if TRUE then the <code>max.dist</code> will be calculated from the locations in <code>cmbdf</code> . Otherwise either <code>max.dist</code> must be specified or <code>max.dist</code> will default to pi. |

Value

An object of the class `CMBCovariance` that is a modification of [variog](#) from the package **geoR** with variogram values replaced by covariances.

The attribute "breaks" contains the break points used to create bins. The result has `num.bins + 1` values since the first value, the sample variance, is not counted as a bin.

u a vector with distances.
v a vector with estimated covariance values at distances given in u.
n number of pairs in each bin
sd standard deviation of the values in each bin
bins.lim limits defining the interval spanned by each bin
ind.bin a logical vector indicating whether the number of pairs in each bin is greater or equal to the value in the argument pairs.min
var.mark variance of the data
beta.ols parameters of the mean part of the model fitted by ordinary least squares
output.type echoes the option argument
max.dist maximum distance between pairs allowed in the covariance calculations
n.data number of data
direction direction for which the covariance was computed
call the function call

References

geoR package, [variog](#), [variogramCMB](#), [corrCMB](#)

Examples

```

## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 100000)
# Cov <- covCMB(cmbdf, max.dist = 0.03, num.bins = 10)
# Cov

```

covmodelCMB

Computes values of covariance functions

Description

This function computes the covariances given the separation distance of locations. Options for different covariance functions on spheres are available. The function extends the function [cov.spatial](#) for additional covariance models on spheres.

Usage

```

covmodelCMB(
  obj,
  cov.model = "matern",
  cov.pars = stop("no cov.pars argument provided"),
  kappa = 0.5
)

```

Arguments

| | |
|-----------|---|
| obj | Vector of distances between pairs of spatial locations. |
| cov.model | A type of the correlation function. Available choices are: "matern", "exponential", "spherical", "powered.exponential", "cauchy", "gencauchy", "pure.nugget", "askey", "c2wendland", "c4wendland", "sinepower", "multiquadric". Default is "matern" |
| cov.pars | A vector with two covariance parameters. The first parameter corresponds to the variance σ^2 . The second parameter corresponds to the range ϕ of the correlation function. |
| kappa | A smoothness parameter of the correlation function. |

Details

The function returns the value of the covariance $C(h)$ at the distance h . The covariance function has the form

$$C(h) = \sigma^2 * \rho(h/\phi).$$

The parameters of the covariance are positive numbers σ^2 , ϕ and κ .

Expressions for the correlation functions which are not included in the package **geoR**:

askey

$$\rho(h/\phi) = (1 - h/\phi)^{\kappa}, \text{ if } h < \phi;$$

$$0, \text{ otherwise.}$$

c2wendland

$$\rho(h/\phi) = (1 + \kappa * h/\phi) * (1 - h/\phi)^{\kappa}, \text{ if } h < \phi;$$

$$0, \text{ otherwise.}$$

c4wendland

$$\rho(h/\phi) = (1 + \kappa * h/\phi + (\kappa^2 - 1) * (h/\phi)^2 / 3) * (1 - h/\phi)^{\kappa}, \text{ if } h < \phi;$$

$$0, \text{ otherwise.}$$

sinepower

$$\rho(h/\phi) = 1 - (\sin(h/(2\phi)))^{\kappa}$$

multiquadric

$$C(h) = (1 - \phi)^{(2*\kappa)} / (1 + \phi^2 - 2 * \phi * \cos(h))^{\kappa}, 0 < \phi < 1$$

Additional information can be found in the section Details in [cov.spatial](#).

Value

Values of a covariance function for the given distances.

References

geoR package, [cov.spatial](#)

T. Gneiting. Strictly and non-strictly positive definite functions on spheres. *Bernoulli* 19 (2013), no. 4, 1327-1349.

Examples

```
## Compute Askey variogram at x = pi/4

1 - covmodelCMB(pi/4, cov.pars = c(1, pi), kappa = 3, cov.model = "askey" )

## Plot of the Askey covariance function

v1.f <- function(x, ...) {covmodelCMB(x, ...)}
curve( v1.f(x, cov.pars = c(1, 0.03), kappa = 3, cov.model = "askey"),
  from = 0, to = 0.1, xlab = "distance", ylab = expression(cov(h)), lty = 2,
  main = "covariance")
```

covPwSp

Covariance estimate via power spectra

Description

This function provides a covariance estimate using the values of the estimated power spectra.

Usage

```
covPwSp(PowerSpectra, Ns)
```

Arguments

PowerSpectra A data frame which first column lists values of multipole moments and the second column gives the corresponding values of CMB power spectra.

Ns A number of points in which the covariance estimate is computed on the interval $[-1,1]$

Value

A data frame which first column is 1-d grid starting at $-1+1/Ns$ and finishing at 1 with the step $2/Ns$. The second column is the values of estimated covariances on this grid.

References

Formula (2.1) in Baran A., Terdik G. Power spectrum estimation of spherical random fields based on covariances. *Annales Mathematicae et Informaticae* 44 (2015) pp. 15–22.

Power Spectra data are from Planck Legacy Archive <http://pla.esac.esa.int/pla/#cosmology>

Examples

```
## Download the power spectrum first
# N <- 20000
# COM_PowerSpectra <- downloadCMBPS(link=1)
#
# Cov_est <- covPwSp(COM_PowerSpectra[,1:2], N)
# plot(Cov_est, type="l")

## Plot the covariance estimate as a function of angular distances
# plot(acos(Cov_est[,1]), Cov_est[,2], type="l",
#       xlab="angular distance", ylab="Estimated Covariance")
```

```
displayPixelBoundaries
```

Plot HEALPix pixel boundaries

Description

Plot the HEALPix pixel boundaries at nside

Usage

```
displayPixelBoundaries(
  nside,
  eps = pi/90,
  col = "gray",
  lwd = 1,
  ordering,
  incl.labels = 1:(12 * nside^2),
  nums.col = col,
  nums.size = 1,
  font = 2,
  depth_test = "always",
  ...
)
```

Arguments

| | |
|----------|--|
| nside | the HEALPix nside parameter (integer number 2^k) |
| eps | controls the smoothness of the plot, smaller eps implies more samples |
| col | the colour of plotted boundary lines |
| lwd | the thickness of the plotted boundary lines |
| ordering | optionally specify an ordering scheme from which to plot HEALPix pixel numbers. Can be either "ring" or "nested" |

| | |
|--------------------------|--|
| <code>incl.labels</code> | If ordering is specified then this parameter sets the pixel indices that will be displayed (default is all indices at <code>nside</code>) |
| <code>nums.col</code> | specifies the colour of pixel numbers if ordering is specified |
| <code>nums.size</code> | specifies the size of pixel numbers if ordering is specified |
| <code>font</code> | A numeric font number from 1 to 5, used if ordering is specified |
| <code>depth_test</code> | The depth test to be applied. This controls how resistant the plotted object is to being obscured. See <code>rgl.material</code> |
| <code>...</code> | arguments passed to <code>rgl::plot3d</code> |

Value

Produces a plot of the HEALPix pixel boundaries.

Examples

```
displayPixelBoundaries(1, eps = pi/90, col = "red")
displayPixelBoundaries(2, eps = pi/90, col = "green")
```

| | |
|----------------------------|---|
| <code>displayPixels</code> | <i>Display the pixels and grandchildren</i> |
|----------------------------|---|

Description

Display the pixels `spix` at resolution `j` by colouring in the grandchildren of `spix` at resolution `plot.j`

Usage

```
displayPixels(
  boundary.j,
  j,
  plot.j = 5,
  spix,
  boundary.col = "gray",
  boundary.lwd = 1,
  incl.labels = 1:(12 * 4^boundary.j),
  col = "blue",
  size = 3
)
```

Arguments

| | |
|-------------------------|--|
| <code>boundary.j</code> | The resolution to display boundaries at. If this is missing then boundaries will not be plotted. |
| <code>j</code> | The resolution that <code>spix</code> are specified at. |
| <code>plot.j</code> | The resolution to plot grandchildren at |

| | |
|--------------|--|
| spix | Integer vector. The pixel indices to display. These must be in nested order. |
| boundary.col | The boundary colour. |
| boundary.lwd | The boundary line width. |
| incl.labels | Integer vector of pixel indices to label at resolution j. |
| col | The colour to make the grandchildren. |
| size | The size to make the grandchildren. |

Examples

```
## Example 1

## Plot base pixels 1,2,3 by colouring their grandchildren at resolution
## 5 (by default). No pixel boundaries.
displayPixels(j=0, spix=c(1,2,3))

## Plot base pixels 1,2,3 display and their boundaries (boundary.j=0)
displayPixels(0,0, spix=c(1,2,3))

## Plot base pixels 1,2,3 by colouring their grandchildren at resolution 2
displayPixels(0,0, plot.j = 2, spix=c(1,2,3))

## Example 2

demoNeighbours <- function(p,j) {
  neighbours(p, j)
  displayPixels(boundary.j = j, j = j, plot.j = 5,
               spix = neighbours(p, j),
               boundary.col = "gray",
               boundary.lwd = 1,
               incl.labels = neighbours(p, j),
               col = "blue",
               size = 3)
  rcosmo::displayPixelBoundaries(nside = 1, col = "blue", lwd = 3)
}

demoNeighbours(1,2)
```

downloadCMBMap

Download CMB Maps from Planck Public Data Release.

Description

The function `downloadCMBMap` downloads CMB maps from https://irsa.ipac.caltech.edu/data/Planck/release_2/all-sky-maps/matrix_cmb.html.

Usage

```
downloadCMBMap(foreground = "smica", nside = 1024, destfile, release = 2)
```

Arguments

| | |
|------------|--|
| foreground | A string naming the foreground separation method pipeline. Please choose one of "COMMANDER", "NILC", "SEVEM" or "SMICA" (not case sensitive). |
| nside | An integer. The nside parameter (resolution) required. The available options are 1024 or 2048. |
| destfile | An optional character string with the path and file name for the downloaded file to be saved. Defaults to the working directory. Tilde-expansion is performed. |
| release | An integer. Indicates the Planck map release to download. Currently only 2 and 3 are supported. |

Details

CMB maps have been produced by the COMMANDER, NILC, SEVEM, and SMICA pipelines, respectively.

For each pipeline, the intensity maps are provided at Nside = 2048, at 5 arcmin resolution, and the polarization maps are provided at Nside = 1024 at 10 arcmin resolution.

Value

CMB Map FITS File (Flexible Image Transport System). The FITS file can be loaded into a `CMBDataFrame` using the `CMBDataFrame` function (see examples).

References

Planck Public Data Release 2 Maps https://irsa.ipac.caltech.edu/data/Planck/release_2/all-sky-maps/matrix_cmb.html

Other fits maps can also be downloaded using the general command `download.file`.

Examples

```
## Download SMICA with \code{nside = 1024}
## and save in working directory
## as "CMB_map_smica1024.fits"
# downloadCMBMap(foreground = "smica", nside = 1024)
## Load the downloaded map into a CMBDataFrame
# sky <- CMBDataFrame("CMB_map_smica1024.fits")

## Download SMICA with Nside=2048 and save in the working directory
## as "CMB_map_smica2048.fits"
# downloadCMBMap(foreground = "smica", nside = 2048)

## Download COMMANDER with Nside=1024 and save in a specified folder,
## for example,
# dest <- "CMB_map_commander1024.fits"
# downloadCMBMap(foreground = "commander", nside = 1024, destfile = dest)
```

`downloadCMBPS`*Download CMB Power Spectra from Planck Legacy Archive.*

Description

The function `downloadCMBPS` downloads CMB power spectra components from <https://pla.esac.esa.int/pla/#cosmology>.

Usage

```
downloadCMBPS(link = 1, destfile, save = TRUE)
```

Arguments

| | |
|-----------------------|--|
| <code>link</code> | The link code (an integer from 1 to 6) for the URL to download the file. See code details in this help file. |
| <code>destfile</code> | A character string with the file name for the downloaded file to be saved. Tilde-expansion is performed. |
| <code>save</code> | A boolean indicating whether to save or not (since the downloaded data is returned anyway). |

Details

`link = 1`: Best-fit LCDM CMB power spectra from the baseline Planck TT, TE, EE+lowE+lensing ($2 \leq \ell \leq 2508$).

`link = 2`: Baseline high- ℓ Planck TT power spectra ($2 \leq \ell \leq 2508$).

`link = 3`: Baseline high- ℓ Planck EE power spectra ($2 \leq \ell \leq 1996$).

`link = 4`: Baseline high- ℓ Planck TE power spectra ($2 \leq \ell \leq 1996$).

`link = 5`: Low- ℓ Planck EB power spectra ($2 \leq \ell \leq 29$).

`link = 6`: Low- ℓ Planck BB power spectra ($2 \leq \ell \leq 29$).

Value

The Data Frame with CMB Power Spectra and, if `save = TRUE` a txt file is saved in `destfile`

References

Planck Legacy Archive <https://pla.esac.esa.int/pla/#cosmology>

Examples

```
## Download the Low- $l$  Planck BB power spectra ( $2 \leq l \leq 29$ ) and
## save it to C:/PW.txt
# downloadCMBPS(link=6, destfile="C:/PW.txt")

## Download the Best-fit LCDM CMB power spectra
## and plot it
# CMBPS <- downloadCMBPS(link=1, save = FALSE)
# plot(CMBPS$L,CMBPS$TT, type="o",col="red",cex=0.3,
#      main="CMB Angular Power Spectra",xlab=expression(l),
#      ylab=expression(paste(D[l],"(",mu,K^2,")")))

```

entropyCMB

CMB Entropy

Description

This function returns an estimated entropy for the specified [CMBDataFrame](#) column intensities and [CMBWindow](#) region. The function employs the function [entropy](#) and uses histogram counts of intensities for computations. All arguments of the standard [entropy](#) can be used.

Usage

```
entropyCMB(cmbdf, win, intensities = "I", method)
```

Arguments

| | |
|-------------|---|
| cmbdf | A CMBDataFrame . |
| win | A CMBWindow |
| intensities | A CMBDataFrame column with measured values. |
| method | A method to estimate entropy, see entropy |

Value

Estimated Shannon entropy for observations in [CMBWindow](#)

References

[entropy](#)

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 10000)
# win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
# entropyCMB(cmbdf, win1)
```

| | |
|--------|---|
| exprob | <i>Threshold exceedance probability</i> |
|--------|---|

Description

This function returns an estimated exceedance probability for the specified `CMBDataFrame` column intensities, threshold level *alpha* and `CMBWindow` region.

Usage

```
exprob(cmbdf, win, alpha, intensities = "I")
```

Arguments

| | |
|--------------------------|---|
| <code>cmbdf</code> | A <code>CMBDataFrame</code> . |
| <code>win</code> | A <code>CMBWindow</code> |
| <code>alpha</code> | A numeric threshold level. |
| <code>intensities</code> | The name of the column in <code>cmbdf</code> that contains the measured values. |

Value

Estimated threshold exceedance probability

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 1000)

# intensities <- "I"
# alpha <- mean(cmbdf[,intensities, drop = TRUE])
# alpha

# win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
# exprob(cmbdf, win1, alpha)
```

| | |
|---------|-----------------------|
| extrCMB | <i>Extreme values</i> |
|---------|-----------------------|

Description

This function returns n largest extreme values for the specified `CMBDataFrame` column intensities and `CMBWindow` region.

Usage

```
extrCMB(cmbdf, win, n, intensities = "I")
```

Arguments

| | |
|--------------------------|--|
| <code>cmbdf</code> | A <code>CMBDataFrame</code> . |
| <code>win</code> | A <code>CMBWindow</code> |
| <code>n</code> | An integer value. |
| <code>intensities</code> | A <code>CMBDataFrame</code> column with measured values. |

Value

A `CMBDataFrame` with n largest extreme values

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 1000)
#
# win1 <- CMBWindow(theta = c(pi/2,pi,pi/2), phi = c(0,0,pi/2))
# extrCMB(cmbdf, win1,5)
#
## Plotting the window and 5 top extreme values
# plot(win1)
# plot(extrCMB(cmbdf, win1,5), col = "blue", size = 4, add = TRUE)
```

| | |
|-----|-----------------------------------|
| fmf | <i>First Minkowski functional</i> |
|-----|-----------------------------------|

Description

This function returns an area of the spherical region where measured values are above of the specified threshold level *alpha*.

Usage

```
fmf(cmbdf, alpha, intensities = "I")
```

Arguments

| | |
|-------------|---|
| cmbdf | A CMBDataFrame . |
| alpha | A numeric threshold level. |
| intensities | A CMBDataFrame column with measured values. |

Value

The area of the exceedance region

References

Leonenko N., Olenko A. (2014) Sojourn measures of Student and Fisher-Snedecor random fields. *Bernoulli*, 20:1454-1483.

Examples

```
n <- 64
cmbdf <- CMBDataFrame(nside=n, I = rnorm(12*n^2),
                      coords = "cartesian",
                      ordering = "nested")

fmf(cmbdf, 0, 4)
fmf(cmbdf, 2, 4)

win <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
cmbdf.win <- window(cmbdf, new.window = win)
fmf(cmbdf.win, 0, 4)
```

fRen *Sample Renyi function*

Description

This function computes values of the sample Renyi function. Returns the estimated values of $T(q)$ for q taking values on a grid. For large data sets could be rather time consuming.

Usage

```
fRen(
  cmbdf,
  q.min = 1.01,
  q.max = 10,
  N = 20,
  k.box = log2(nside(cmbdf)) - 3,
  intensities = "I"
)
```

Arguments

| | |
|-------------|--|
| cmbdf | A CMBDataFrame . |
| q.min | Left endpoint of the interval to compute the Renyi function. The default value is 1.01, |
| q.max | Right endpoint of the interval to compute the Renyi function. The default value is 10 |
| N | Number of points to compute the Renyi function. The default value is 20. |
| k.box | A dyadic decomposition level in computing the Renyi function, see the references in Details. The default value is $\log_2(\text{nside}(\text{cmbdf})) - 3$ |
| intensities | A CMBDataFrame column with measured values |

Value

Data frame which first column is the sampling grid $\text{seq}(q.\text{min}, q.\text{max}, \text{length.out} = N)$ of q values. Another column consists of values of the sample Renyi function $T(q)$ computed on the grid using the $k.\text{box}$ th level dyadic decomposition of the unit ball.

References

- (1) Leonenko, N., and Shieh, N. 2013. Rényi function for multifractal random fields. *Fractals* 21, Article No. 1350009.
- (2) <http://mathworld.wolfram.com/RenyiEntropy.html>

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
#
# cmbdf <- CMBDataFrame("CMB_map_smica1024.fits")
# win <- CMBWindow(theta = c(pi/4,pi/2,pi/2), phi = c(0,0,pi/2))
# cmbdf<- window(cmbdf, new.window = win)
# Tq <- fRen(cmbdf)
#
# plot(Tq[,1], Tq[,2], ylab =expression(D[q]), xlab = "q",
# main = "Sample Renyi function", pch = 20, col = "blue")
```

geo2sph

Convert geographic to spherical coordinates

Description

Convert latitude (lat) and longitude (lon) to spherical coordinates (theta, phi) with theta in $[0, \pi]$ and phi in $[0, 2 * \pi]$. All values lat, lon, theta, phi are assumed to be in radians.

Usage

```
geo2sph(...)
```

Arguments

... A data.frame with columns lat and lon, or named vectors of lat and lon.

Value

A data.frame with columns theta and phi.

Examples

```
geo <- data.frame( lat = c(0, pi/3, pi/2), lon = c(0, pi/3, pi))
geo
sph <- geo2sph(geo)
sph
```

| | |
|----------|---|
| geoAngle | <i>Angle between two spherical directions</i> |
|----------|---|

Description

Get an angle between two directions defined by arcs on the unit sphere

Usage

```
geoAngle(p1)
```

Arguments

`p1` A [data.frame](#) with rows specifying numeric points located on the unit sphere. It should have columns labelled x,y,z for Cartesian or theta, phi for spherical colatitude and longitude respectively.

Value

Let $p1[1,]$, $p1[2,]$, and $p1[3,]$ denote the rows of `p1`. Then the returned object is an angle in radians between two arcs determined by # the pairs # of spherical points ($p1[1,]$, $p1[2,]$) and ($p1[2,]$, $p1[3,]$) respectively.

Examples

```
p1 <- data.frame(diag(3))
p1
colnames(p1) <- c("x", "y", "z")
geoAngle(p1)

geo <- data.frame( lat = c(30, 0, 20), lon = c(30, 60, 10))*(pi/180)
geo
p2 <- geo2sph(geo)
p2
geoAngle(p2)
```

| | |
|---------|------------------------|
| geoArea | <i>geoArea generic</i> |
|---------|------------------------|

Description

Detailed descriptions and examples can be found in documentation for specific `geoArea` functions [geoArea.CMBDataFrame](#), [geoArea.HPDataFrame](#), [geoArea.CMBWindow](#)

Usage

```
geoArea(x)
```

Arguments

x An object.

See Also

[geoArea.CMBDataFrame](#) [geoArea.HPDataFrame](#) [geoArea.CMBWindow](#)

geoArea.CMBDataFrame *Geodesic area covered by a CMBDataFrame*

Description

Gives the surface on the unit sphere that is encompassed by all pixels in cmbdf

Usage

```
## S3 method for class 'CMBDataFrame'  
geoArea(x)
```

Arguments

x a CMBDataFrame.

Value

The sum of the areas of all pixels (rows) in x.

Examples

```
## At low resolution, a few data points can  
## occupy a large pixel area, e.g.:  
  
cmbdf <- CMBDataFrame(nside = 1, spix = c(1,2,3))  
pix(cmbdf)  
  
## The total number of Healpix points at nside=1 equals 12. As cmbdf has 3 Healpix  
## it occupies pi = 1/4*(surface area of unit sphere)  
  
geoArea(cmbdf)  
plot(cmbdf, size = 5, hp.boundaries = 1)
```

geoArea.CMBWindow *Geodesic area of a CMBWindow*

Description

Geodesic area of a [CMBWindow](#)

Usage

```
## S3 method for class 'CMBWindow'
geoArea(x)
```

Arguments

x A CMBWindow.

Value

The spherical area inside the CMBWindow x.

Examples

```
## A window that covers 1/8 of the unit sphere is constructed and its area is
## pi/2 = 1/8*(surface area of unit sphere)

win <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
geoArea(win)
```

geoArea.HPDataFrame *Geodesic area covered by a HPDataFrame*

Description

Gives the surface on the unit sphere that is encompassed by all pixels in x.

Usage

```
## S3 method for class 'HPDataFrame'
geoArea(x)
```

Arguments

x A HPDataFrame.

Value

The sum of the areas of all pixels (rows) in x .

Examples

```
## Generate random I for HPDataFrame
hp1 <- HPDataFrame(I=rnorm(5), nside = 1, spix = c(1,1,2,2,3))
pix(hp1)

## The total number of Healpix points at nside=1 equals 12. As hp1 has five
## I values at 3 Healpix points, then the occupied area is
## pi = 1/4*(surface area of unit sphere)

geoArea(hp1)
plot(hp1, size = 5, hp.boundaries = 1)
```

 geoDist

Geodesic distance on the unit sphere

Description

Get geodesic distance between points on the unit sphere

Usage

```
geoDist(p1, p2, include.names = FALSE)
```

Arguments

| | |
|---------------|---|
| p1 | A data.frame with rows specifying numeric points located on the unit sphere. It should have columns labelled x,y,z for Cartesian or theta, phi for spherical colatitude and longitude respectively. |
| p2 | Same as p1. |
| include.names | Boolean. If TRUE then the row and column names of the returned matrix will be taken from the points in p1 and p2 (see examples below). |

Value

Let n denote the number of rows of p1 and let m denote the number of rows of p2. Then the returned object is an n by m matrix whose entry in position ij is the geodesic distance from the i th row of p1 to the j th row of p2.

Examples

```
p1 <- data.frame(diag(3))
colnames(p1) <- c("x", "y", "z")
p1
p2 <- data.frame(x=c(1,0), y=c(0,3/5), z=c(0,4/5))
p2
geoDist(p1, p2, include.names = FALSE)
```

header

Get the FITS headers from a [CMBDataFrame](#)

Description

Get the FITS headers from a [CMBDataFrame](#)

Usage

```
header(cmbdf)
```

Arguments

cmbdf a [CMBDataFrame](#).

Value

The FITS headers belonging to the FITS file from which cmbdf data was imported

Examples

```
## First download the map
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# df.sample <- CMBDataFrame(df, sample.size = 10000)
# header(df.sample)
```

| | |
|-----------------|--|
| healpixCentered | <i>Check if object is assumed to have HEALPix centered coordinates</i> |
|-----------------|--|

Description

The function checks object's attribute `healpixCentered`. The attribute is TRUE if the object was assumed to have rows that correspond to unique HEALPix pixel indices.

Usage

```
healpixCentered(obj)
```

Arguments

`obj` Any object.

Value

A boolean. This is TRUE if `obj` is a [CMBDataFrame](#) or a [HPDataFrame](#) whose coordinates were assumed to correspond to HEALPix pixel center locations.

Examples

```
hp1 <- HPDataFrame(I=rnorm(5), nside = 1, spix = c(1,1,2,2,3))
pix(hp1)
coords(hp1, new.coords = "cartesian")
healpixCentered(hp1)

sky <- CMBDataFrame(nside = 32, coords = "cartesian", ordering = "nested")
sky.s <- CMBDataFrame(sky, sample.size = 100)
hpdf <- HPDataFrame(sky.s, auto.spix = TRUE)
healpixCentered(hpdf)
```

| | |
|-------------|--------------------------|
| HPDataFrame | <i>HPDataFrame class</i> |
|-------------|--------------------------|

Description

HPDataFrames are a type of data.frame designed to carry data located on the unit sphere. Each row of a HPDataFrame is associated with a HEALPix pixel index. The HPDataFrame also holds an attribute called `nside` which stores the HEALPix Nside parameter (i.e., the resolution of the HEALPix grid that is being used). Unlike [CMBDataFrame](#), HPDataFrames may have repeated pixel indices. They are made this way so that multiple data points falling within a given pixel can be stored in different rows of any given HPDataFrame.

Usage

```
HPDataFrame(
  ...,
  nside,
  ordering = "nested",
  auto.spix = FALSE,
  spix,
  assumedUniquePix = FALSE,
  delete.duplicates = FALSE,
  save.dots = FALSE,
  save.duplicate.indices = FALSE
)
```

Arguments

| | |
|------------------------|--|
| ... | Data. Can be named vectors or a data.frame. May include columns (x,y,z) or (theta, phi) representing Cartesian or spherical coordinates of points on the unit sphere. |
| nside | Integer number 2^k , the nside parameter, i.e, resolution. If nside is unspecified, then the an attempt is made to use columns x,y and z from the provided data, as Cartesian coordinates, to calculate an nside that is sufficient to ensure all points belong to unique pixels. |
| ordering | The HEALPix ordering scheme ("ring" or "nested"). |
| auto.spix | Boolean. If TRUE then spix will be found from the coordinates provided in the data. That is, each row of data will be assigned the pixel index of its closest HEALPix pixel center. There must be columns x,y,z for cartesian or theta, phi for spherical colatitude and longitude respectively. If auto.spix = FALSE then nside must be specified. |
| spix | A vector of HEALPix pixel indices indicating the pixel locations of the data. Note that spix is ignored if auto.spix = TRUE. |
| assumedUniquePix | A boolean. Sets the assumedUniquePix attribute of the HPDataFrame. This attribute indicates whether or not the rows of a HPDataFrame can be assumed to belong to unique pixels. |
| delete.duplicates | Boolean. If TRUE then rows corresponding to duplicate pixel indices will be dropped from the returned HPDataFrame, and assumedUniquePix will be set to TRUE. |
| save.dots | A logical. If TRUE then the dot product of each observation with the nearest child HEALPix pixel center will be stored as a column called "distance" in the returned HPDataFrame, provided that auto.spix = TRUE. Note that a 'child' pixel is any one of the four pixels contained in the current pixel, in the nested scheme, at the next highest resolution. See children . |
| save.duplicate.indices | A logical. If TRUE and delete.duplicates is also TRUE, then the row indices of duplicated pixels will be retained as an attribute called "duplicates". Note |

that row index refers to the row position of the duplicated pixel in the original HPDataFrame, and not the actual pixel index itself.

Details

HPDataFrame with `auto.spix = TRUE` can be used to transform any spherical data (not necessarily CMB) to the Healpix representation, see Example 3 below.

Examples

```
##Example 1.

hp1 <- HPDataFrame(I=rnorm(5), nside = 1, spix = c(1,1,2,2,3))
pix(hp1)
coords(hp1, new.coords = "cartesian")
class(hp1)
assumedUniquePix(hp1)

##Example 2.

# Where nside is not specified
sky <- CMBDataFrame(nside = 32, coords = "cartesian", ordering = "nested")
sky.s <- CMBDataFrame(sky, sample.size = 100)
hpdf <- HPDataFrame(sky.s, auto.spix = TRUE)
class(hpdf)
assumedUniquePix(hpdf)

# ## Example 3.
# ## Create a HPDataFrame with NON-UNIQUE pixel indices
#
# ## With earth data.
# ## Download World Cities Database from
# ## https://simplemaps.com/static/data/world-cities/basic/simplemaps\_worldcities\_basicv1.4.zip
# ## unpack the file worldcities.csv
#
# worldcities <- read.csv("worldcities.csv")
#
# ## Prepare a data frame with cities' coordinates
# sph <- geo2sph(data.frame(lon = pi/180*worldcities$lng,
#                           lat = pi/180*worldcities$lat))
#
# df <- data.frame(phi = sph$phi,
#                  theta = sph$theta,
#                  I = rep(1,nrow(sph)))
#
# ## Create and plot the corresponding HPDataFrame with
# ## pixel indices that are not necessarily unique
# ## by choosing your desired resolution (nside)
# hp <- HPDataFrame(df, auto.spix = TRUE, nside = 1024)
# plot(hp, size = 3, col = "darkgreen", back.col = "white")
# ## Add some pixels to visualise the sphere
```

```

# plot(CMBDataFrame(nside = 64), add = TRUE, col = "gray")

# ## Example 4.
# ## Create a HPDataFrame with UNIQUE pixel indices.
#
# ## With earth data.
# ## Download World Cities Database from
# ## https://simplemaps.com/static/data/world-cities/basic/simplemaps_worldcities_basicv1.4.zip
# ## unpack the file worldcities.csv
#
# worldcities <- read.csv("worldcities.csv")
# uscities <- worldcities[worldcities$country == "United States",]
#
# ## Prepare a data frame with cities' coordinates
# sph <- geo2sph(data.frame(lon = pi/180*uscities$lng,
#                           lat = pi/180*uscities$lat))
# usdf <- data.frame(phi = sph$phi,
#                   theta = sph$theta,
#                   I = rep(1,nrow(sph)))
#
# ## Select k cities with unique coordinates. The
# ## coordinates must be unique otherwise the
# ## automatically chosen separating nside
# ## will be infinite.
# k <- 1000
# usdf <- usdf[sample(nrow(usdf), k), ]
# plot(usdf$phi, usdf$theta)
# usdf[duplicated(usdf), ]
# usdf <- usdf[!duplicated(usdf), ]
# usdf[duplicated(usdf), ]
# usdf <- coords(usdf, new.coords = "cartesian")
#
# ## Create and plot the corresponding HPDataFrame . To make
# ## sure the pixels are unique, do not select a resolution
# ## resolution (nside), since it will be chosen automatically.
# ushp <- HPDataFrame(usdf, auto.spix = TRUE)
# nside(ushp)
# assumedUniquePix(ushp)
# plot(ushp, size = 3, col = "darkgreen", back.col = "white")
# ## Add some pixels to visualise the sphere
# plot(CMBDataFrame(nside = 64), add = TRUE, col = "gray")

```

ibp2p

Computes pixel's index using its subindex within base resolution

Description

Find the pixel index p of a given pixel with index ibp in base pixel bp .

Usage

```
ibp2p(ibp, bp, j)
```

Arguments

| | |
|-----|---|
| ibp | The pixel index within base pixel bp, at resolution j, in nested order. |
| bp | The base pixel index |
| j | The resolution parameter $n_{\text{side}} = 2^j$ |

Examples

```
ibp2p(1, 1, 2)
ibp2p(1, 2, 2)
```

| | |
|-----------|--|
| is.CMBDat | <i>Check if an object is of class CMBDat</i> |
|-----------|--|

Description

Check if an object is of class CMBDat

Usage

```
is.CMBDat(cmbdf)
```

Arguments

| | |
|-------|--------------|
| cmbdf | Any R object |
|-------|--------------|

Value

TRUE if cmbdf is a CMBDat object, otherwise FALSE

Examples

```
## First download the map
# downloadCMBMap(foreground = "smica", nside = 1024)
# cmbdat <- CMBDat("CMB_map_smica1024.fits", mmap = TRUE)
# class(cmbdat)
# is.CMBDat(cmbdat)
```

is.CMBDataFrame *Check if an object is of class CMBDataFrame*

Description

Check if an object is of class CMBDataFrame

Usage

```
is.CMBDataFrame(cmbdf)
```

Arguments

cmbdf Any R object

Value

TRUE if cmbdf is a CMBDataFrame, otherwise FALSE

Examples

```
df <- CMBDataFrame(nside = 16)
is.CMBDataFrame(df)
df2 <- coords(df, new.coords = "cartesian")
is.CMBDataFrame(df2)
```

is.CMBWindow *Check if an object is a CMBWindow*

Description

Check if an object is a CMBWindow

Usage

```
is.CMBWindow(win)
```

Arguments

win any object

Value

TRUE or FALSE depending if win is a CMBWindow

Examples

```
win <- CMBWindow(x=0,y=3/5,z=4/5,r=0.8, set.minus = TRUE)
is.CMBWindow(win)
```

| | |
|----------------|---|
| is.HPDataFrame | <i>Check if an object is of class HPDataFrame</i> |
|----------------|---|

Description

Check if an object is of class [HPDataFrame](#)

Usage

```
is.HPDataFrame(hpdf)
```

Arguments

hpdf Any R object

Value

TRUE if hpdf is a [HPDataFrame](#), otherwise FALSE

Examples

```
df <- CMBDataFrame(nside = 16)
is.HPDataFrame(df)

df <- HPDataFrame(I = rep(0,12), nside = 1)
is.HPDataFrame(df)
```

| | |
|----------|---|
| linesCMB | <i>Adds lines of fitted variograms to variogram plots</i> |
|----------|---|

Description

This function adds a line with the variogram model fitted by the function [variofitCMB](#) to a current variogram plot. The function modifies [lines.variomodel.variofit](#) from the package **geoR** for additional covariance models on spheres.

Usage

```
linesCMB(x, max.dist, scaled = FALSE, ...)
```

Arguments

| | |
|-----------------------|---|
| <code>x</code> | An object of the class <code>variofit</code> containing information about the fitted model obtained as an output of the function <code>variofitCMB</code> . |
| <code>max.dist</code> | A maximum distance to draw the variogram line. The default is <code>x\$max.dist</code> . |
| <code>scaled</code> | logical. If TRUE the sill in the plot is 1. |
| <code>...</code> | other plotting parameters passed to <code>curve</code> |

Details

The function adds a line with fitted variogram model to a plot. It is used to compare empirical variograms against fitted models returned by `variofitCMB`.

Available models are: "matern", "exponential", "spherical", "powered.exponential", "cauchy", "gen-cauchy", "pure.nugget", "askey", "c2wendland", "c4wendland", "sinepower", "multiquadric".

Value

A line with a fitted variogram model is added to a plot.

References

geoR package, `lines.variomodel.variofit`, `covmodelCMB`, `variofitCMB`

Examples

```
## Plot the fitted Matern variogram versus its empirical variogram
#
# df <- CMBDataFrame("../CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 10000)
# varcmb <- variogramCMB(cmbdf, max.dist = 0.1, num.bins = 30)
# varcmb
# ols <- variofitCMB(varcmb, fix.nug=FALSE, wei="equal", cov.model= "matern")
# plot(varcmb)
# lines(ols, lty=2)
#
## Plot the fitted Askey variogram versus its empirical variogram
#
# ols <- variofitCMB(vario1, ini.cov.pars = c(1, 0.03), fix.nug = TRUE,
#   kappa = 3, wei = "equal", cov.model = "askey")
# plot(varcmb, main = ols$cov.model)
# linesCMB(ols, lty = 2)
```

| | |
|---------|---|
| maxDist | <i>Get the maximum geodesic distance between points</i> |
|---------|---|

Description

Get the maximum geodesic distance either between all points in a `data.frame` pairwise, or between all points in a `data.frame` and one target point.

Usage

```
maxDist(df, point)
```

Arguments

| | |
|--------------------|---|
| <code>df</code> | A <code>data.frame</code> with columns <code>x,y,z</code> for cartesian or <code>theta, phi</code> for spherical colatitude and longitude respectively. The rows must correspond to points on the unit sphere. If this is a HPDataFrame or CMBDataFrame and coordinate columns are missing, then coordinates will be assigned based on HEALPix pixel indices. |
| <code>point</code> | An optional target point on the unit sphere in cartesian coordinates, in which case all distances are calculated between point and the points in <code>df</code> . |

Value

If `point` is specified: the longest geodesic distance from `point` to the points specified by the rows of `df`. If `point` is not specified: the longest geodesic distance pairwise between points in `df`.

Examples

```
## Using a CMBDataFrame with HEALPix coordinates only
cmbdf <- CMBDataFrame(nside = 1, spix = c(1,5,12), ordering = "ring")
plot(cmbdf, hp.boundaries = 1, col = "blue", size = 5)
p <- c(0,0,1)
maxDist(cmbdf, p) # no need to have coordinates

## Using a HPDataFrame with HEALPix coordinates only
hp <- HPDataFrame(nside = 1, I = rep(0,3), spix = c(1,5,12) )
maxDist(hp, p) # notice no need to have coordinates

## Using a data.frame with cartesian coordinates
coords(hp) <- "cartesian"
df <- data.frame(x = hp$x, y = hp$y, z = hp$z)
maxDist(df, p)

## Using a data.frame with spherical coordinates
coords(hp) <- "spherical"
df <- data.frame(theta = hp$theta, phi = hp$phi)
maxDist(df, p)
```

```
## max distance between points in cmdf
maxDist(cmbdf)
```

| | |
|---------------|---|
| maxWindowDist | <i>Get the maximum distance between all points in a CMBWindow</i> |
|---------------|---|

Description

Get the maximum distance between all points in a [CMBWindow](#)

Usage

```
maxWindowDist(x)
```

Arguments

x A [CMBWindow](#) object.

Value

The maximum distance between window's points.

Examples

```
## win is a equilateral spherical triangle which sides are pi/2
win <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
maxWindowDist(win)
```

| | |
|---------|---|
| minDist | <i>Get the minimum geodesic distance between points</i> |
|---------|---|

Description

Get the minimum geodesic distance either between all points in a data.frame pairwise, or between all points in a data.frame and one target point.

Usage

```
minDist(df, point)
```

Arguments

| | |
|-------|--|
| df | A data.frame with columns x,y,z for cartesian or theta, phi for spherical colatitude and longitude respectively. The rows must correspond to points on the unit sphere. If this is a HPDataFrame or CMBDataFrame and coordinate columns are missing, then coordinates will be assigned based on HEALPix pixel indices. |
| point | An optional target point on the unit sphere in cartesian coordinates, in which case all distances are calculated between point and the points in df. |

Value

If point is specified: the shortest distance from point to the points specified by the rows of df. If point is not specified: the shortest distance pairwise between points in df.

Examples

```
## Using a CMBDataFrame with HEALPix coordinates only
cmbdf <- CMBDataFrame(nside = 1, spix = c(1,5,12), ordering = "ring")
plot(cmbdf, hp.boundaries = 1, col = "blue", size = 5)
p <- c(0,0,1)
minDist(cmbdf, p) # no need to have coordinates

## Using a HPDataFrame with HEALPix coordinates only
hp <- HPDataFrame(nside = 1, I = rep(0,3), spix = c(1,5,12) )
minDist(hp, p) # notice no need to have coordinates

## Using a data.frame with cartesian coordinates
coords(hp) <- "cartesian"
df <- data.frame(x = hp$x, y = hp$y, z = hp$z)
minDist(df, p)

## Using a data.frame with spherical coordinates
coords(hp) <- "spherical"
df <- data.frame(theta = hp$theta, phi = hp$phi)
minDist(df, p)

## min distance between points in cmdf
minDist(cmbdf)
```

neighbours

Return neighbouring pixels

Description

Return the neighbouring pixels to a given pixel p that is specified at resolution j , in the nested order.

Usage

```
neighbours(p, j)
```

Arguments

p Pixel index *p* at resolution *j*.
j The resolution parameter with $n_{\text{side}} = 2^j$.

Examples

```
## Return the neighbouring pixels for base pixel 1
neighbours(1, 0)

## Plot the neighbouring pixels for base pixel 1
demoNeighbours <- function(p,j) {
  neighbours(p, j)
  displayPixels(boundary.j = j, j = j, plot.j = j+3,
               spix = neighbours(p, j),
               boundary.col = "gray",
               boundary.lwd = 1,
               incl.labels = neighbours(p, j),
               col = "blue",
               size = 3)
  rcosmo::displayPixelBoundaries(nside = 1, col = "blue", lwd = 3)
}

demoNeighbours(1,2)
demoNeighbours(1,0)
```

 nest2ring

Convert nest to ring ordering

Description

Convert from "nested" to "ring" ordering

nest2ring computes the HEALPix pixel index in the "ring" ordering scheme from the pixel index in the "nested" ordering scheme.

Usage

```
nest2ring(nside, pix)
```

Arguments

nside is the HEALPix nside parameter.
pix is the set or subset of pixel indices at nside. If pix is left blank then all pixels are converted.

Value

the output is the corresponding set of pixel in the ring ordering scheme.

Examples

```
# compute HEALPix indices in the ring ordering scheme
nside <- 8
pix <-c(1,2,23)
nest2ring(nside,pix)
```

| | |
|------------|--|
| nestSearch | <i>Finds the closest pixel center to a point</i> |
|------------|--|

Description

Finds the closest HEALPix pixel center to a given target point, specified in Cartesian coordinates, using an efficient nested search algorithm. HEALPix indices are all assumed to be in the "nested" ordering scheme.

Usage

```
nestSearch(target, nside, index.only = FALSE, save.dots = FALSE)
```

Arguments

| | |
|------------|--|
| target | A data.frame, matrix or vector of Cartesian (x,y,z) coordinates for the target point. If a data.frame is used then spherical coordinates can be specified with row names theta and phi. |
| nside | An integer, the target resolution at which the resulting pixels are returned. |
| index.only | A boolean indicating whether to return only the pixel index (TRUE), or cartesian coordinates as well (FALSE). |
| save.dots | A logical. A If TRUE then the dot product of each observation with the nearest child HEALPix pixel center will be returned as an attribute called "dot". Note that a 'child' pixel is any one of the four pixels contained in the current pixel in the nested scheme, at the next highest resolution. See children . |

Value

if `index.only = TRUE` then the output will be a HEALPix index. If `index.only FALSE` then the output is the list containing the HEALPix index and Cartesian coordinate vector of the HEALPix point closest to target at resolution nside.

Examples

```
## Find the closest HEALPix pixel center at resolution j=2 for
## the point (0.6,0.8,0)

point <- c(0.6,0.8,0)
j <- 2
cpoint <- nestSearch(point, nside = 2^j)

## Plot the closest pixel center in blue and the point (0.6,0.8,0) in red
displayPixels(j, j, plot.j=j, spix=c(cpoint$pix),
              size=5, incl.labels =FALSE)
rgl::plot3d(point[1], point[2], point[3],
            col="red", size = 5, add = TRUE)

## Repeat the above for 4 points in a data.frame
points <- data.frame(x = c(1,0,0,0.6),
                    y = c(0,1,0,0.8),
                    z = c(0,0,1,0))

points
j <- 2
cpoints <- nestSearch(points, nside = 2^j)

## Plot the closest pixel center in blue and the point (0.6,0.8,0) in red
displayPixels(j, j, plot.j=j, spix=c(cpoints$pix),
              size=5, incl.labels =FALSE)
rgl::plot3d(points[,1], points[,2], points[,3],
            col="red", size = 5, add = TRUE)
```

nside

nside generic

Description

Detailed descriptions and examples can be found in documentation for specific nside functions [nside.CMBDataFrame](#), [nside.HPDataFrame](#)

Usage

```
nside(x)
```

Arguments

x An object.

See Also

[nside.CMBDataFrame](#) [nside.HPDataFrame](#)

nside.CMBDataFrame *HEALPix Nside parameter from a CMBDataFrame*

Description

This function returns the HEALPix Nside parameter of a CMBDataFrame

Usage

```
## S3 method for class 'CMBDataFrame'  
nside(x)
```

Arguments

x A [CMBDataFrame](#).

Value

The HEALPix Nside parameter.

Examples

```
df <- CMBDataFrame(nside = 16)  
nside(df)
```

nside.HPDataFrame *HEALPix Nside parameter from a [HPDataFrame](#)*

Description

This function returns the HEALPix Nside parameter of a [HPDataFrame](#)

Usage

```
## S3 method for class 'HPDataFrame'  
nside(x)
```

Arguments

x A [HPDataFrame](#).

Value

The HEALPix Nside parameter.

Examples

```
df <- HPDataFrame(I = rep(0,12), nside = 1)
nside(df)
```

 numeric2col

numeric2col

Description

Map numeric values to a colour map

Usage

```
numeric2col(
  num,
  colmap = grDevices::terrain.colors(100),
  breaks.length = length(colmap)
)
```

Arguments

`num` A numeric vector. The numbers which will be mapped to colours.

`colmap` A colour map. See [palette](#).

`breaks.length` A single integer. Controls the number of breaks in the discretisation of `num`.

Examples

```
ns <- 16
sky <- CMBDataFrame(I = rnorm(12*ns^2), nside = ns)
plot(sky, col = numeric2col(sky$I))
```

 ordering

ordering generic

Description

Detailed descriptions and examples can be found in documentation for specific ordering functions [ordering.CMBDataFrame](#), [ordering.HPDataFrame](#)

Usage

```
ordering(x, ...)
```


Arguments

x An object.
 ... Extra arguments.

See Also

[ordering.CMBDataFrame](#) [ordering.HPDataFrame](#)

ordering.CMBDataFrame *HEALPix ordering scheme from a CMBDataFrame*

Description

This function returns the HEALPix ordering scheme from a CMBDataFrame. The ordering scheme is either "ring" or "nested".

Usage

```
## S3 method for class 'CMBDataFrame'
ordering(x, new.ordering, ...)
```

Arguments

x A [CMBDataFrame](#).
 new.ordering Specifies the new ordering ("ring" or "nest") if a change of ordering scheme is desired.
 ... Unused arguments.

Details

If a new ordering is specified, using e.g. new.ordering = "ring", the ordering scheme of the CMBDataFrame will be converted.

Value

The name of the HEALPix ordering scheme that is used in the CMBDataFrame x.

Examples

```
df <- CMBDataFrame(nside = 1, ordering = "nested")
ordering(df)
df1 <- ordering(df, new.ordering = "ring")
ordering(df1)
```

ordering.HPDataFrame *HEALPix ordering scheme from a HPDataFrame*

Description

This function returns the HEALPix ordering scheme from a HPDataFrame. The ordering scheme is either "ring" or "nested". If a new ordering is specified, using e.g. `new.ordering = "ring"`, the ordering scheme of the HPDataFrame will be converted.

Usage

```
## S3 method for class 'HPDataFrame'
ordering(x, new.ordering, ...)
```

Arguments

| | |
|---------------------------|--|
| <code>x</code> | a HPDataFrame . |
| <code>new.ordering</code> | Specifies the new ordering ("ring" or "nest") if a change of ordering scheme is desired. |
| <code>...</code> | Unused arguments. |

Value

The name of the HEALPix ordering scheme that is used in the HPDataFrame `x`, or a new HP-DataFrame with the desired `new.ordering`

Examples

```
df <- HPDataFrame(I = rep(0,12), nside = 1, ordering = "nested")
ordering(df)
df1 <- ordering(df, new.ordering = "ring")
ordering(df1)
```

p2bp *Return base pixel to which pixel belongs*

Description

The base pixel to which pixel p belongs at resolution j

Usage

```
p2bp(p, j)
```

Arguments

`p` The pixel index at resolution j , in nested order.
`j` The resolution parameter $n_{side} = 2^j$

Examples

`p2bp(5, 0)`
`p2bp(5, 1)`

`p2ibp`

Return pixel index within its base pixel

Description

Convert a pixel index p to its index within the base pixel to which p belongs

Usage

`p2ibp(p, j)`

Arguments

`p` The pixel index at resolution j , in nested order.
`j` The resolution parameter $n_{side} = 2^j$

Examples

`p2ibp(6, 0)`
`p2ibp(6, 1)`

`parent`

Return index of parent pixel

Description

Gives the pixel at resolution $j - 1$ that contains p , where p is specified at resolution j (notice it does not depend on j).

Usage

`parent(p)`

Arguments

`p` A pixel index specified in nested order.

Examples

```
parent(4)
parent(5)
```

| | |
|------------------|--------------------|
| <code>pix</code> | <i>pix generic</i> |
|------------------|--------------------|

Description

Detailed descriptions and examples can be found in documentation for specific `pix` functions [`pix.CMBDataFrame`](#), [`pix.HPDataFrame`](#)

Usage

```
pix(x, ...)
```

Arguments

`x` An object.
`...` Extra arguments.

See Also

[`pix.CMBDataFrame`](#) [`pix.HPDataFrame`](#)

| | |
|-------------------------------|--|
| <code>pix.CMBDataFrame</code> | <i>HEALPix pixel indices from CMBDataFrame</i> |
|-------------------------------|--|

Description

If `new.pix` is unspecified then this function returns the vector of HEALPix pixel indices from a `CMBDataFrame`. If `new.pix` is specified then this function returns a new `CMBDataFrame` with the same number of rows as `cmbdf`, but with `pix` attribute `new.pix`. Thus, `new.pix` must have length equal to `nrow(cmbdf)`.

Usage

```
## S3 method for class 'CMBDataFrame'
pix(x, new.pix, ...)
```

Arguments

x A CMBDataFrame.
 new.pix Optional vector of pixel indices with length equal to nrow(x).
 ... Unused arguments.

Value

The vector of HEALPix pixel indices or, if new.pix is specified, a new CMBDataFrame.

Examples

```
## First download the map
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits", sample.size = 800000)
# pix(df)

df <- CMBDataFrame(nside = 16, sample.size = 10, ordering = "nested")
pix(df)
```

pix.HPDataFrame *HEALPix pixel indices from HPDataFrame*

Description

If new.pix is unspecified then this function returns the vector of HEALPix pixel indices from a HPDataFrame. If new.pix is specified then this function returns a new HPDataFrame with the same number of rows as x, but with pix attribute new.pix. Thus, new.pix must have length equal to nrow(x).

Usage

```
## S3 method for class 'HPDataFrame'
pix(x, new.pix, ...)
```

Arguments

x a [HPDataFrame](#).
 new.pix optional vector of pixel indices with length equal to nrow(x)
 ... Unused arguments.

Value

The vector of HEALPix pixel indices (integers) or, if new.pix is specified, a new HPDataFrame.

Examples

```
df <- HPDataFrame(I = rep(0,12), nside = 1)
pix(df)
```

pix2coords *Convert pixel indices to cartesian/spherical coordinates*

Description

Convert HEALPix pixel indices to cartesian or spherical coordinates

Usage

```
pix2coords(nside, coords = "cartesian", ordering = "nested", spix)
```

Arguments

nside the nside parameter (integer number 2^k)
 coords 'cartesian' or 'spherical' coordinates
 ordering 'ring' or 'nested' ordering
 spix optional integer or vector of sample pixel indices

Value

a data.frame with columns 'x', 'y', 'z' (cartesian) or 'theta', 'phi' (spherical)

Examples

```
pix2coords(nside=1, spix=c(2,5))
pix2coords(nside=1, coords = "spherical", spix=c(2,5))
```

pixelArea *Area of a HEALPix pixel*

Description

Get the area of a single HEALPix pixel

Usage

```
pixelArea(nsideObject)
```

Arguments

nsideObject CMBDataFrame, a HPDataFrame, or an integer giving the nside parameter.

Value

the area of a single HEALPix pixel at the nside resolution of nsideObject

Examples

```
## First download the map
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# pixelArea(df)

df1 <- CMBDataFrame(nside = 64,
                    coords = "cartesian",
                    ordering = "nested")

pixelArea(df1)
```

pixelWindow

Find high resolution pixels falling in a lower resolution window

Description

Find all pixels in a higher resolution that fall within the specified pixel area at a lower resolution. All pixels are assumed to be in nested ordering.

Usage

```
pixelWindow(j1, j2, pix.j1)
```

Arguments

j1 An integer. The lower resolution, with $j1 \leq j2$. Note that $\text{resolution} = \log_2(\text{nside})$.

j2 An integer. The upper resolution.

pix.j1 An integer. The pixel index at resolution j1 within which all pixels from resolution j2 will be returned. pix.j1 can also be a vector of non-zero pixel indices.

Value

All pixels in resolution j2 that fall within the pixel pix.j1 specified at resolution j1

Examples

```
pixelWindow(3, 3, 2)
pixelWindow(3, 4, 2)
pixelWindow(3, 5, 2)
```

plot.CMBCorrelation *Plot sample CMBCorrelation*

Description

Plots sample (empirical) correlation function. Uses `plot.variogram` from **geoR** package.

Usage

```
## S3 method for class 'CMBCorrelation'
plot(x, ...)
```

Arguments

`x` An object of class `CMBCorrelation`.
`...` Extra arguments as in `plot.variogram` passed to `plot.default`.

Value

Produces a plot with the sample correlation function.

References

geoR package, `corrCMB`, `variog`, `plot.variogram`

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 100000)
# corcmb <- corrCMB(cmbdf, max.dist = 0.03, num.bins = 10, sample.size=1000)
# plot(corcmb)
```

plot.CMBCovariance *Plot sample CMBCovariance*

Description

Plots sample (empirical) covariance function. Uses [plot.variogram](#) from **geoR** package.

Usage

```
## S3 method for class 'CMBCovariance'  
plot(x, ...)
```

Arguments

x An object of class CMBCovariance.
... Extra arguments as in [plot.variogram](#) passed to plot.default.

Value

Produces a plot with the sample covariance function.

#' @references **geoR** package, [covCMB](#), [variog](#), [plot.variogram](#)

Examples

```
## Download the map first  
# downloadCMBMap(foreground = "smica", nside = 1024)  
# df <- CMBDataFrame("CMB_map_smica1024.fits")  
# cmbdf <- sampleCMB(df, sample.size = 100000)  
# Cov <- covCMB(cmbdf, max.dist = 0.03, num.bins = 10)  
# plot(Cov)
```

plot.CMBDataFrame *Plot CMB Data*

Description

This function produces a plot from a [CMBDataFrame](#).

Usage

```
## S3 method for class 'CMBDataFrame'
plot(
  x,
  intensities = "I",
  add = FALSE,
  sample.size,
  type = "p",
  size = 1,
  box = FALSE,
  axes = FALSE,
  aspect = FALSE,
  col,
  back.col = "black",
  labels,
  hp.boundaries = 0,
  hpb.col = "gray",
  depth_test = "less",
  lab_depth_test = "always",
  ...
)
```

Arguments

| | |
|-------------|---|
| x | A CMBDataFrame . |
| intensities | The name of a column that specifies CMB intensities. This is only used if col is unspecified. |
| add | If TRUE then this plot will be added to any existing plot. Note that if back.col (see below) is specified then a new plot window will be opened and add = TRUE will have no effect. |
| sample.size | Optionally specifies the size of a simple random sample to take before plotting. This can make the plot less computationally intensive. |
| type | A single character indicating the type of item to plot. Supported types are: 'p' for points, 's' for spheres, 'l' for lines, 'h' for line segments from z = 0, and 'n' for nothing. |
| size | The size of plotted points. |
| box | Whether to draw a box. |
| axes | Whether to draw axes. |
| aspect | Either a logical indicating whether to adjust the aspect ratio, or a new ratio. |
| col | Specify the colour(s) of the plotted points. |
| back.col | Optionally specifies the background colour of the plot. This argument is passed to rgl::bg3d. |
| labels | Optionally specify a vector of labels to plot, such as words or vertex indices. If this is specified then rgl::text3d is used instead of rgl::plot3d. Then length(labels) must equal nrow(x). |

| | |
|----------------|---|
| hp.boundaries | Integer. If greater than 0 then HEALPix pixel boundaries at nside = hp.boundaries will be added to the plot. |
| hpb.col | Colour for the hp.boundaries. |
| depth_test | The depth test to be applied to the plotted points. This controls how resistant the plotted object is to being obscured. See rgl.material |
| lab_depth_test | The rgl depth test to be applied to the labels and pixel boundaries if present. See rgl.material |
| ... | Arguments passed to rgl::plot3d. |

Value

A plot of the CMB data

Examples

```
## First download the map
# downloadCMBMap(foreground = "smica", nside = 1024)
# sky <- CMBDataFrame("CMB_map_smica1024.fits")
# plot(sky, sample.size = 800000)
```

| | |
|----------------|------------------------------|
| plot.CMBWindow | <i>Visualise a CMBWindow</i> |
|----------------|------------------------------|

Description

Visualise a [CMBWindow](#)

Usage

```
## S3 method for class 'CMBWindow'
plot(
  x,
  add = TRUE,
  type = "l",
  col = "red",
  size = 2,
  box = FALSE,
  axes = FALSE,
  aspect = FALSE,
  back.col,
  depth_test = "always",
  ...
)
```

Arguments

| | |
|------------|--|
| x | A CMBWindow. |
| add | if TRUE then this plot will be added to any existing plot. Note that if <code>back.col</code> (see below) is specified then a new plot window will be opened and <code>add = TRUE</code> will have no effect |
| type | a single character indicating the type of item to plot. Supported types are: 'p' for points, 's' for spheres, 'l' for lines, 'h' for line segments from $z = 0$, and 'n' for nothing. |
| col | specify the colour(s) of the plotted points |
| size | the size of plotted points |
| box | whether to draw a box |
| axes | whether to draw axes |
| aspect | either a logical indicating whether to adjust the aspect ratio, or a new ratio. |
| back.col | specifies the background colour of the plot. This argument is passed to <code>rgl::bg3d</code> . |
| depth_test | The depth test to be applied. This controls how resistant the plotted object is to being obscured. See rgl.material |
| ... | arguments passed to <code>rgl::plot3d</code> |

Examples

```
win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
win2 <- CMBWindow(theta = c(2*pi/3,3*pi/4,3*pi/4, 2*pi/3), phi = c(pi/4,pi/4,pi/3,pi/3))
plot(win1)
plot(win2)
```

plot.HPDataFrame

Plot HPDataFrame

Description

This function produces a plot from a [HPDataFrame](#). If columns `x,y,z` (cartesian) or `theta,phi` (colatitude and longitude respectively) are present in `x`, then these will be used as coordinates for plotting. Otherwise, the HEALPix indices as in `pix(x)` will be used. If HEALPix indices are used and multiple rows correspond to a single pixel index, then beware that values may be obfuscated in the plot, and all locations are pixel centers.

Usage

```
## S3 method for class 'HPDataFrame'
plot(
  x,
  intensities = "I",
  add = FALSE,
  sample.size,
  type = "p",
  size = 1,
  box = FALSE,
  axes = FALSE,
  aspect = FALSE,
  col = "blue",
  back.col = "black",
  labels,
  hp.boundaries = 0,
  hpb.col = "gray",
  depth_test = "less",
  lab_depth_test = "always",
  ...
)
```

Arguments

| | |
|--------------------------|---|
| <code>x</code> | A HPDataFrame. |
| <code>intensities</code> | The column name for the data in <code>x</code> that is to be treated as intensities for plotting. |
| <code>add</code> | if TRUE then this plot will be added to any existing plot. Note that if <code>back.col</code> (see below) is specified then a new plot window will be opened and <code>add = TRUE</code> will have no effect |
| <code>sample.size</code> | optionally specifies the size of a simple random sample to take before plotting. This can make the plot less computationally intensive |
| <code>type</code> | a single character indicating the type of item to plot. Supported types are: 'p' for points, 's' for spheres, 'l' for lines, 'h' for line segments from $z = 0$, and 'n' for nothing. |
| <code>size</code> | the size of plotted points |
| <code>box</code> | whether to draw a box |
| <code>axes</code> | whether to draw axes |
| <code>aspect</code> | either a logical indicating whether to adjust the aspect ratio, or a new ratio. |
| <code>col</code> | specify the colour(s) of the plotted points |
| <code>back.col</code> | optionally specifies the background colour of the plot. This argument is passed to <code>rgl::bg3d</code> . |
| <code>labels</code> | optionally specify a vector of labels to plot, such as words or vertex indices. If this is specified then <code>rgl::text3d</code> is used instead of <code>rgl::plot3d</code> . Then <code>length(labels)</code> must equal <code>nrow(x)</code> |

| | |
|-----------------------------|--|
| <code>hp.boundaries</code> | integer. If greater than 0 then HEALPix pixel boundaries at <code>nside = hp.boundaries</code> will be added to the plot |
| <code>hpb.col</code> | colour for the <code>hp.boundaries</code> |
| <code>depth_test</code> | The depth test to be applied to the plotted points. This controls how resistant the plotted object is to being obscured. This controls how resistant the plotted |
| <code>lab_depth_test</code> | The <code>rgl</code> depth test to be applied to the labels and pixel boundaries if present. See <code>rgl.material</code> |
| <code>...</code> | arguments passed to <code>rgl::plot3d</code> |

Value

A plot of the data locations according to coordinate columns or HEALPix index

Examples

```
hpdf <- HPDataFrame(I = rep(0,12), nside = 1)
plot(hpdf, size = 5, col = "yellow", back.col = "black",
      hp.boundaries = 1)
```

| | |
|-----------------------------|------------------------------|
| <code>plot.variogram</code> | <i>Plot sample variogram</i> |
|-----------------------------|------------------------------|

Description

Plots sample (empirical) variogram. Uses [`plot.variogram`](#) from **geoR** package.

Arguments

| | |
|------------------|---|
| <code>x</code> | An object of class <code>variogram</code> . |
| <code>...</code> | Extra arguments as in <code>plot.variogram</code> passed to <code>plot.default</code> . |

Value

Produces a plot with the sample variogram.

References

geoR package, [`variogramCMB`](#), [`variog`](#), [`plot.variogram`](#)

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 100000)
# varcmb <- variogramCMB(cmbdf, max.dist = 0.1, num.bins = 30, sample.size=1000)
# plot(varcmb)
```

plotAngDis

Plot angular scatterplots and means

Description

For specified measurements from [CMBDataFrame](#) this function produces scatterplots and binned means versus theta and phi angles.

Usage

```
plotAngDis(cmbdf, intensities = "I")
```

Arguments

`cmbdf` A [CMBDataFrame](#) object.
`intensities` The name of a column of `cmbdf`, containing measured values.

Value

2x2 plot. The first row shows scatterplots. The second row gives barplots of the corresponding means computed over bins. The first column corresponds to the values of theta and the second one is for phi.

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# df.sample <- CMBDataFrame(df, sample.size = 80000)
# win <- CMBWindow(theta = c(pi/4,pi/2,pi/2,pi/4), phi = c(0,0,pi/2,pi/2))
# cmbdf.win <- window(df.sample, new.window = win)
#
# intensities <- "I"
# plotAngDis(cmbdf.win, intensities)
```

plotcovmodelCMB *Plot theoretical CMB Covariance*

Description

Plots theoretical covariance functions from the list defined in [covmodelCMB](#)

Usage

```
plotcovmodelCMB(
  cov.model = "matern",
  sigmasq = 1,
  phi = pi,
  kappa = 0.5,
  from = 0,
  to = pi,
  ...
)
```

Arguments

| | |
|-----------|--|
| cov.model | A type of the correlation function. Available choices are: "matern", "exponential", "spherical", "powered.exponential", "cauchy", "gencauchy", "pure.nugget", "askey", "c2wendland", "c4wendland", "sinpower", "multiquadric". The default is "matern" |
| sigmasq | The variance parameter as documented in covmodelCMB . The default is 1. |
| phi | The range parameter as documented in covmodelCMB . The default is pi. |
| kappa | A smoothness parameter of the correlation function. The default is 0.5. |
| from | A lower range of the plotting region. The default is lb = 0 |
| to | An upper range of the plotting region. The default is ub = pi. |
| ... | optional plotting parameters. |

Value

Produces a plot with the theoretical covariance function.

References

[covmodelCMB](#)

Examples

```
plotcovmodelCMB("matern", sigmasq = 5)
plotcovmodelCMB("askey", phi = pi/4, to = pi/2, kappa = 4)
```

plotvariogram *Plot theoretical variogram*

Description

Plots theoretical variogram functions from the list defined in [covmodelCMB](#)

Usage

```
plotvariogram(  
  cov.model = "matern",  
  sigmasq = 1,  
  phi = pi,  
  kappa = 0.5,  
  from = 0,  
  to = pi,  
  ...  
)
```

Arguments

| | |
|-----------|--|
| cov.model | A type of the variogram function. Available choices are: "matern", "exponential", "spherical", "powered.exponential", "cauchy", "gencauchy", "pure.nugget", "askey", "c2wendland", "c4wendland", "sinpower", "multiquadric". The default is "matern" |
| sigmasq | The variance parameter as documented in covmodelCMB . The default is 1. |
| phi | The range parameter as documented in covmodelCMB . The default is pi. |
| kappa | A smoothness parameter of the variogram function. The default is 0.5. |
| from | A lower range of the plotting region. The default is lb = 0 |
| to | An upper range of the plotting region. The default is ub = pi. |
| ... | optional plotting parameters. |

Value

Produces a plot with the theoretical variogram.

References

[covmodelCMB](#)

Examples

```
plotvariogram("matern", sigmasq = 5)  
plotvariogram("askey", phi = pi/4, to = pi/2, kappa = 4)
```

practicalRangeCMB *Practical range for covariance function*

Description

This function computes the practical range for covariance functions on spheres. The function extends [practicalRange](#) from the package **geoR** to additional covariance models on spheres.

Usage

```
practicalRangeCMB(cov.model, phi, kappa = 0.5, correlation = 0.05, ...)
```

Arguments

| | |
|-------------|--|
| cov.model | A type of the correlation function. Available choices are: "matern", "exponential", "spherical", "powered.exponential", "cauchy", "gencauchy", "pure.nugget", "askey", "c2wendland", "c4wendland", "sinpower", "multiquadric". |
| phi | The range parameter as documented in covmodelCMB |
| kappa | A smoothness parameter of the correlation function. |
| correlation | A correlation threshold (default is 0.05) |
| ... | other optimisation parameters |

Details

The practical(effective) range for a covariance function is the distance at which a covariance function first time reaches the specified value `correlation`. For covariance functions on spheres the practical range does not exceed ϕ , the distance beyond which a covariance function is not defined. For the covariance functions "spherical", "askey", "c2wendland", "c4wendland" their practical ranges are equal to lengths of their support.

Value

Value of the practical range for the covariance function specified in [covmodelCMB](#)

References

geoR package, [practicalRange](#), [covmodelCMB](#)

Examples

```
practicalRangeCMB(cov.model = "sinpower", phi = 0.1, kappa = 0.5)
practicalRangeCMB(cov.model = "askey", phi = 0.1, kappa = 0.5)
```

print.CMBDataFrame *Print CMBDataFrame*

Description

This function neatly prints the contents of a CMBDataFrame.

Usage

```
## S3 method for class 'CMBDataFrame'  
print(x, ...)
```

Arguments

x A [CMBDataFrame](#).
... arguments passed to [print.tbl_df](#)

Value

Prints contents of the CMB data frame to the console.

Examples

```
## First download the map  
# downloadCMBMap(foreground = "smica", nside = 1024)  
# df <- CMBDataFrame("CMB_map_smica1024.fits")  
# print(df)
```

print.HPDataFrame *Print a HPDataFrame*

Description

This function neatly prints the contents of a HPDataFrame.

Usage

```
## S3 method for class 'HPDataFrame'  
print(x, ...)
```

Arguments

x A HPDataFrame.
... arguments passed to [print.tbl_df](#)

Value

Prints contents of the HPDataFrame to the console.

Examples

```
df <- HPDataFrame(I = rep(0,12), nside = 1, ordering = "nested")
print(df)
df
```

pwSpCorr

Power spectra estimate via correlation

Description

This function provides an angular power spectra estimate using the values of the sample correlations. The approach is based on Lawson-Hanson algorithm for non-negative least squares.

Usage

```
pwSpCorr(corcmb, lmax = 20 * length(corcmb$u))
```

Arguments

corcmb An object of the class CMBCorrelation.
lmax A number of angular power spectra components to estimate

Value

A data frame which first column is 1-d grid of l values from 0 to lmax. The second column is estimated angular power spectra components on this grid.

References

Formula (2.1) in Baran A., Terdik G. Power spectrum estimation of spherical random fields based on covariances. *Annales Mathematicae et Informaticae* 44 (2015) pp. 15–22.

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# Corrf <- corrCMB(df, max.dist = 0.1, num.bins = 30,
# sample.size=10000)
# pw <- pwSpCorr(Corrf)
```

| | |
|-----------|-------------------------------------|
| qqnormWin | <i>Normal QQ plot for CMBWindow</i> |
|-----------|-------------------------------------|

Description

This function is a modification of standard [qqnorm](#) functions to work with [CMBWindow](#) regions.

Usage

```
qqnormWin(cmbdf, win, intensities = "I")
```

Arguments

| | |
|-------------|---|
| cmbdf | A CMBDataFrame . |
| win | A CMBWindow |
| intensities | A CMBDataFrame column with measured values. |

Details

[qqnormWin](#) returns a normal QQ plot of for the specified [CMBDataFrame](#) column [intensities](#) and [CMBWindow](#) region. The function automatically adds a line of a “theoretical” normal quantile-quantile plot.

Value

A list with quantile components x and y and a normal QQ plot with QQ line

References

[qqnorm](#), [qqplot](#), [qqplotWin](#)

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 1000)

# win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
# qqnormWin(cmbdf, win1)
```

 qqplotWin

Quantile-Quantile plots for CMBWindows

Description

This function is a modification of standard [qqplot](#) functions to work with [CMBWindow](#) regions.

Usage

```
qqplotWin(cmbdf, win1, win2, intensities = "I")
```

Arguments

| | |
|-------------|---|
| cmbdf | A CMBDataFrame . |
| win1 | A CMBWindow |
| win2 | A CMBWindow |
| intensities | A CMBDataFrame column with measured values. |

Details

[qqplotWin](#) produces a QQ plot of quantiles of observations in two [CMBWindows](#) against each other for the specified [CMBDataFrame](#) column intensities. The function automatically adds a diagonal line.

Value

A list with quantile components x and y and a QQ plot with a diagonal line

References

[qqnormWin](#), [qqnorm](#), [qqplot](#)

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 10000)

# win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
# win2 <- CMBWindow(theta = c(2*pi/3,3*pi/4,3*pi/4, 2*pi/3),
#                   phi = c(pi/4,pi/4,pi/3,pi/3))

# qqplotWin(cmbdf, win1, win2)
```

| | |
|-------|--------------------|
| qstat | <i>q-statistic</i> |
|-------|--------------------|

Description

This function returns an estimated q-statistic for the specified column intensities in a [CMBDataFrame](#) and the list of [CMBWindows](#).

Usage

```
qstat(cmbdf, listwin, intensities = "I")
```

Arguments

| | |
|-------------|---|
| cmbdf | A CMBDataFrame . |
| listwin | A list of CMBWindows |
| intensities | A CMBDataFrame column with measured values. |

Details

The q-statistics is used to measure spatial stratified heterogeneity and takes values in [0, 1]. It gives the percent of the variance of intensities explained by the stratification. 0 corresponds to no spatial stratified heterogeneity, 1 to perfect spatial stratified heterogeneity.

Value

Estimated q-statistics for observations in a list of [CMBWindows](#)

References

Wang, J.F, Zhang, T.L, Fu, B.J. (2016). A measure of spatial stratified heterogeneity. *Ecological Indicators*. 67: 250–256.

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 1000)
# win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
# win2 <- CMBWindow(theta = c(pi/2,pi,pi/2), phi = c(0,0,pi/2))
#
# lw <- list(win1, win2)
# qstat(cmbdf, lw)
```

 rbind.CMBDataFrame [rbind](#) for CMBDataFrames

Description

Add a new row or rows to a [CMBDataFrame](#). All arguments passed to `...` must be [CMBDataFrames](#). If the [CMBDataFrame](#) arguments have overlapping pixel indices then all but one of the non-unique rows will be deleted unless `unsafe = TRUE`. If `unsafe = TRUE` then a [HPDataFrame](#) will be returned instead of a [CMBDataFrame](#).

Usage

```
## S3 method for class 'CMBDataFrame'
rbind(..., deparse.level = 1, unsafe = FALSE)
```

Arguments

| | |
|----------------------------|---|
| <code>...</code> | A number of CMBDataFrames |
| <code>deparse.level</code> | See documentation for rbind.data.frame . |
| <code>unsafe</code> | A boolean. If the CMBDataFrame arguments have overlapping pixel indices then all but one of the non-unique rows will be deleted unless <code>unsafe = TRUE</code> . If <code>unsafe = TRUE</code> then a HPDataFrame will be returned instead of a CMBDataFrame . |

See Also

See the documentation for [rbind](#)

Examples

```
df <- CMBDataFrame(nside = 1, I = 1:12)

df.123 <- CMBDataFrame(df, spix = c(1,2,3))
df.123
df.234 <- CMBDataFrame(df, spix = c(2,3,4))
df.234

df.1234 <- rbind(df.123, df.234)
df.1234
class(df.1234) # A CMBDataFrame
pix(df.1234)

df.123234 <- rbind(df.123, df.234, unsafe = TRUE)
df.123234
class(df.123234) # A HPDataFrame
pix(df.123234)
```


Description

Handling and Analysing Spherical, Healpix and Cosmic Microwave Background data on a HEALPix grid.

Details

The package `rcosmo` offers various tools for

- Downloading and transforming Cosmic Microwave Background radiation (CMB) and spherical data
- Working with Hierarchical Equal Area isoLatitude Pixelation of a sphere (Healpix)
- Spherical geometry
- Statistical analysis of CMB and spherical data
- Visualisation of Healpix data

Most of `rcosmo` features were developed for CMB, but it can also be used for other spherical data. It contains tools for transforming spherical data in cartesian and geographic coordinates to the Healpix representation.

Update

Current updates are available through URL: <https://github.com/frycast/rcosmo>

BugReports

<https://github.com/frycast/rcosmo/issues>

Author(s)

Daniel Fryer <d.fryer@latrobe.edu.au>, Andriy Olenko <a.olenko@latrobe.edu.au>, Ming Li <Ming.Li@latrobe.edu.au>, Yuguang Wang.

| | |
|------------|--|
| resolution | <i>Get the arcmin resolution from a CMBDataFrame</i> |
|------------|--|

Description

Get the arcmin resolution from a [CMBDataFrame](#)

Usage

```
resolution(cmbdf)
```

Arguments

cmbdf a [CMBDataFrame](#).

Value

The arcmin resolution as specified by the FITS file where the data was sourced

Examples

```
## First download the map
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# resolution(df)
```

| | |
|-----------|---------------------------------------|
| ring2nest | <i>Convert ring to nest ordering.</i> |
|-----------|---------------------------------------|

Description

ring2nest converts HEALPix pixel indices in the 'ring' ordering scheme to HEALPix pixel indices in the 'nested' ordering scheme.

Usage

```
ring2nest(nside, pix)
```

Arguments

nside is the HEALPix nside parameter (integer number 2^k)
 pix is a vector of HEALPix pixel indices, in the 'ring' ordering scheme.

Value

the output is a vector of HEALPix pixel indices in the 'nested' ordering scheme.

Examples

```
## Convert (1,2,23) from ring to nest at nside = 8
nside <- 8
pix <-c(1,2,23)
ring2nest(nside,pix)
```

sampleCMB

Take a simple random sample from a [CMBDataFrame](#)

Description

This function returns a [CMBDataFrame](#) which size equals to `sample.size`, whose rows comprise a simple random sample of the rows from the input `CMBDataFrame`.

Usage

```
sampleCMB(cmbdf, sample.size)
```

Arguments

`cmbdf` a [CMBDataFrame](#).
`sample.size` the desired sample size.

Value

A [CMBDataFrame](#) which size equals to `sample.size`, whose rows comprise a simple random sample of the rows from the input `CMBDataFrame`.

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# plot(sampleCMB(df, sample.size = 800000))

df <- CMBDataFrame(nside = 16, I = rnorm(12 * 16 ^ 2), ordering = "nested")
df.sample <- sampleCMB(df, sample.size = 100)
df.sample
```

| | |
|----------|---------------------------------|
| siblings | <i>Return siblings of pixel</i> |
|----------|---------------------------------|

Description

The siblings of pixel p are defined as the children of the parent of p . Note this is resolution independent.

Usage

```
siblings(p)
```

Arguments

| | |
|-----|------------------------------|
| p | Pixel index in nested order. |
|-----|------------------------------|

Examples

```
siblings(11)
siblings(12)
```

| | |
|--------------------|---|
| sphericalHarmonics | <i>Compute spherical harmonic values at given points on the sphere.</i> |
|--------------------|---|

Description

The function sphericalHarmonics computes the spherical harmonic values for the given 3D Cartesian coordinates.

Usage

```
sphericalHarmonics(L, m, xyz)
```

Arguments

| | |
|-------|--|
| L | The degree of spherical harmonic ($L=0,1,2,\dots$) |
| m | The order number of the degree- L spherical harmonic ($m=-L,-L+1,\dots,L-1,L$) |
| xyz | Dataframe for given points in 3D cartesian coordinates |

Value

values of spherical harmonics

References

See https://en.wikipedia.org/wiki/Table_of_spherical_harmonics

It uses equation (7) in Hesse, K., Sloan, I. H., & Womersley, R. S. (2010). Numerical integration on the sphere. In Handbook of Geomathematics (pp. 1185-1219). Springer Berlin Heidelberg, but instead of the order $k=1, \dots, 2L+1$ in the book we use $m=k-L-1$.

Examples

```
## Calculate spherical harmonic value at
## the point (0,1,0) with L=5, m=2
point<-data.frame(x=0,y=1,z=0)
sphericalHarmonics(5,2,point)

## Calculate spherical harmonic values at
## the point (1,0,0), (0,1,0), (0,0,1) with L=5, m=2
points<-data.frame(diag(3))
sphericalHarmonics(5,2,points)
```

summary.CMBDataFrame *Summarise a* [CMBDataFrame](#)

Description

This function produces a summary from a CMBDataFrame.

Usage

```
## S3 method for class 'CMBDataFrame'
summary(object, intensities = "I", ...)
```

Arguments

| | |
|-------------|---|
| object | A CMBDataFrame . |
| intensities | the name of a column specifying CMB intensities (or potentially another numeric quantity of interest) |
| ... | Unused arguments. |

Value

A summary includes window's type and area, total area covered by observations, and main statistics for intensity values

Examples

```
## First download the map
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# df.sample <- CMBDataFrame(df, sample.size = 800000)
# summary(df.sample)

ns <- 16
df <- CMBDataFrame(I = rnorm(12*ns^2), nside = ns,
                   ordering = "nested")

win1 <- CMBWindow(x=0,y=3/5,z=4/5,r=0.8)
df.sample1 <- window(df, new.window = win1)
summary(df)
```

summary.CMBWindow *Summarise a CMBWindow*

Description

This function produces a summary from a CMBWindow

Usage

```
## S3 method for class 'CMBWindow'
summary(object, ...)
```

Arguments

| | |
|--------|-------------------|
| object | A CMBWindow. |
| ... | Unused arguments. |

Value

A summary includes window's type and area

Examples

```
win <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
summary(win)

win1 <- CMBWindow(x=0,y=3/5,z=4/5,r=0.8, set.minus = TRUE)
summary(win1)
```

summary.HPDataFrame *Summarise a [HPDataFrame](#)*

Description

This function produces a summary from a HPDataFrame.

Usage

```
## S3 method for class 'HPDataFrame'
summary(object, intensities = "I", ...)
```

Arguments

| | |
|-------------|---|
| object | A HPDataFrame. |
| intensities | the name of a column specifying intensities (or potentially another numeric quantity of interest) |
| ... | Unused arguments. |

Value

A summary includes window's type and area, total area covered by observations, and main statistics for intensity values

Examples

```
ns <- 2
hpdf <- HPDataFrame(I = rnorm(12*ns^2), nside = 2,
                    ordering = "nested")
win <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
hpdf.win <- window(hpdf, new.window = win)
summary(hpdf.win)
```

triangulate *Triangulate a polygonal [CMBWindow](#)*

Description

Triangulate a polygonal [CMBWindow](#)

Usage

```
triangulate(win)
```

Arguments

win a CMBWindow object

Value

a list of CMBWindow polygons or minus.polygons, each having 3 vertices and representing a triangle. If winType of win does not include "minus" then these triangles have pairwise disjoint interiors and their union is equal to the original polygon, win. Otherwise, if winType of win does include "minus" the triangles are the same as for the non-minus type above, but have "minus" types.

Examples

```
## Example 1

win <- CMBWindow(theta = c(2*pi/3,3*pi/4,3*pi/4, 2*pi/3),
                  phi = c(pi/4,pi/4,pi/3,pi/3))

win
plot(win)
win1 <- triangulate(win)
win1
summary(win1[[1]])
plot(win1[[1]], add= FALSE, col="green")
plot(win1[[2]], col="blue")

## Example 2: triangulation minus-type polygon

win <- CMBWindow(theta = c(pi/5,pi/3,pi/4, pi/3, pi/5),
                  phi = c(pi/5,pi/5, pi/4 ,pi/3,pi/3), set.minus =TRUE)

win
plot(win)
summary(win)
win1 <- triangulate(win)
win1
plot(win1[[1]], add= FALSE, col="green")
plot(win1[[2]], col="blue")
plot(win1[[3]], col="yellow")
summary(win1[[1]])
summary(win1[[2]])
summary(win1[[3]])
```

Description

This function estimates variogram parameters by fitting a parametric model from [covmodelCMB](#) to a sample variogram. The function extends [variofit](#) from the package **geoR** to additional covariance models on spheres.

Usage

```

variofitCMB(
  vario,
  ini.cov.pars,
  cov.model,
  fix.nugget = FALSE,
  nugget = 0,
  fix.kappa = TRUE,
  kappa = 0.5,
  simul.number = NULL,
  max.dist = vario$max.dist,
  weights,
  minimisation.function,
  limits = geoR::pars.limits(),
  messages,
  ...
)

```

Arguments

| | |
|------------------------------------|--|
| <code>vario</code> | An object of the class <code>variogram</code> obtained as an output of the function <code>variogramCMB</code> . |
| <code>ini.cov.pars</code> | A vector with initial values for the variogram parameters. The first parameter corresponds to the variance σ^2 . The second parameter corresponds to the range ϕ of the correlation function. |
| <code>cov.model</code> | A type of the variogram function. Available choices are: "matern", "exponential", "spherical", "powered.exponential", "cauchy", "gencauchy", "pure.nugget", "askey", "c2wendland", "c4wendland", "sinpower", "multiquadric". The default is "matern" |
| <code>fix.nugget</code> | logical. Indicates whether the nugget variance should be regarded as fixed or be estimated. The default is FALSE. |
| <code>nugget</code> | A value for the nugget parameter. Regarded as a fixed values if <code>fix.nugget = TRUE</code> or as a initial value for the minimization algorithm if <code>fix.nugget = FALSE</code> . The default is zero. |
| <code>fix.kappa</code> | logical. Indicates whether the parameter κ should be regarded as fixed or be estimated. The default is TRUE. |
| <code>kappa</code> | A value for the smoothness parameter. Regarded as a fixed values if <code>fix.kappa = TRUE</code> or as a initial value for the minimization algorithm if <code>fix.kappa = FALSE</code> . Required not in all covariance models, see <code>covmodelCMB</code> . The default is 0.5. |
| <code>simul.number</code> | number of simulation. Used if <code>vario</code> has empirical variograms for more than one data-set (simulations). The default is NULL |
| <code>max.dist</code> | A maximum distance to fit a variogram model. The default is <code>x\$max.dist</code> . |
| <code>weights</code> | Weights used in the loss function in the minimization algorithm. |
| <code>minimisation.function</code> | Minimization function ("optim", "nlm", "nls") to estimate the parameters. |

| | |
|----------|--|
| limits | Lower and upper limits for the model parameters used in the numerical minimisation by <code>minimisation.function = "optim"</code> . |
| messages | logical. Indicates whether or not status messages are printed on the screen. |
| ... | other minimisation parameters |

Details

The parameter values of a variogram function from `covmodelCMB` are found by numerical optimization using one of the functions: `optim`, `nlm` and `nls`.

The function extends `variofit` from the package `geoR` to additional variogram models on spheres. Available models are: "matern", "exponential", "spherical", "powered.exponential", "cauchy", "gen-cauchy", "pure.nugget", "askey", "c2wendland", "c4wendland", "sinepower", "multiquadric".

Additionally it rescales an empirical variogram to the range $[0,1]$ before numerical optimisation and then transforms all obtained results to the original scale. If `ini.cov.pars` are not provided then the 5×5 grid (`seq(0,max(vario$v),l=5)`, `seq(0,vario$max.dist,l=5)`) of initial values of σ^2 and ϕ is used.

Value

An object of the class `variomodel` and `variofit`, see `variofit`

References

`geoR` package, `variofit`, `covmodelCMB`

Examples

```
#
# df <- CMBDataFrame("../CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 10000)
# varcmb <- variogramCMB(cmbdf, max.dist = 0.1, num.bins = 30)
# varcmb
#
# ols <- variofitCMB(varcmb, fix.nug=FALSE, wei="equal", cov.model= "matern")
# plot(varcmb)
# lines(ols, lty=2)
# str(ols)
#
# ols <- variofitCMB(varcmb, fix.nug = TRUE, kappa = 3, wei = "equal",
# cov.model = "askey")
# plot(varcmb, main = ols$cov.model)
# linesCMB(ols, lty = 2)
# str(ols)
```

| | |
|--------------|-------------------------|
| variogramCMB | <i>Sample variogram</i> |
|--------------|-------------------------|

Description

This function provides an empirical variogram for data in a [CMBDataFrame](#) or `data.frame`. It assumes that data are from a stationary spherical random field and the covariance depends only on a geodesic distance between locations. Output is a binned variogram.

Usage

```
variogramCMB(
  cmbdf,
  num.bins = 10,
  sample.size,
  max.dist = pi,
  breaks,
  equiareal = TRUE,
  calc.max.dist = FALSE
)
```

Arguments

| | |
|----------------------------|--|
| <code>cmbdf</code> | is a CMBDataFrame or <code>data.frame</code> |
| <code>num.bins</code> | specifies the number of bins |
| <code>sample.size</code> | optionally specify the size of a simple random sample to take before calculating variogram. This may be useful if the full covariance computation is too slow. |
| <code>max.dist</code> | an optional number between 0 and pi specifying the maximum geodesic distance to use for calculating covariance. Only used if <code>breaks</code> are unspecified. |
| <code>breaks</code> | optionally specify the breaks manually using a vector giving the break points between cells. This vector has length <code>num.bins</code> since the last break point is taken as <code>max.dist</code> . If <code>equiareal = TRUE</code> then these breaks should be $\cos(r_i)$ where r_i are radii. If <code>equiareal = FALSE</code> then these breaks should be r_i . |
| <code>equiareal</code> | if TRUE then the bins have equal spherical area. If false then the bins have equal annular widths. Default is TRUE. |
| <code>calc.max.dist</code> | if TRUE then the <code>max.dist</code> will be calculated from the locations in <code>cmbdf</code> . Otherwise either <code>max.dist</code> must be specified or <code>max.dist</code> will default to pi. |

Value

An object of class `variog` specified in the package **geoR**.

The attribute "breaks" contains the break points used to create bins. The result has `num.bins + 1` values since the first value at distance 0 is not counted as a bin.

u a vector with distances.

v a vector with estimated variogram values at distances given in **u**.
n number of pairs in each bin
sd standard deviation of the values in each bin
bins.lim limits defining the interval spanned by each bin
ind.bin a logical vector indicating whether the number of pairs in each bin is greater or equal to the value in the argument **pairs.min**
var.mark variance of the data
beta.ols parameters of the mean part of the model fitted by ordinary least squares
output.type echoes the option argument
max.dist maximum distance between pairs allowed in the variogram calculations
n.data number of data
direction direction for which the variogram was computed
call the function call

References

geoR package, [variog](#), [covCMB](#), [corrCMB](#)

Examples

```
## Download the map first
# downloadCMBMap(foreground = "smica", nside = 1024)
# df <- CMBDataFrame("CMB_map_smica1024.fits")
# cmbdf <- sampleCMB(df, sample.size = 100000)
# varcmb <- variogramCMB(cmbdf, max.dist = 0.1, num.bins = 30, sample.size=100)
# varcmb
```

window

window generic

Description

Detailed descriptions and examples can be found in documentation for specific window functions [window.CMBDataFrame](#), [window.HPDataFrame](#), [window.data.frame](#)

Usage

```
window(x, ...)
```

Arguments

x An object.
... Extra arguments.

See Also

[window.CMBDataFrame](#) [window.HPDataFrame](#) [window.data.frame](#)

window.CMBDat

Get a sub window from a [CMBDat](#) object

Description

This function returns a data.frame containing the data in `x` restricted to the CMBWindow `new.window`

Usage

```
## S3 method for class 'CMBDat'
window(x, new.window, intersect = TRUE, ...)
```

Arguments

| | |
|-------------------------|--|
| <code>x</code> | a CMBDat object. |
| <code>new.window</code> | A single CMBWindow object or a list of them. |
| <code>intersect</code> | A boolean that determines the behaviour when <code>new.window</code> is a list containing BOTH regular type and "minus" type windows together (see details). |
| <code>...</code> | Unused arguments. |

Details

Windows that are tagged with `set.minus` (see [CMBWindow](#)) are treated differently from other windows.

If the argument is a list of CMBWindows, then interiors of all windows whose `winType` does not include "minus" are united (let A be their union) and exteriors of all windows whose `winType` does include "minus" are intersected, (let B be their intersection). Then, provided that `intersect = TRUE` (the default), the returned data.frame will be the points of `cmbdat$data` in the the intersection of A and B . Otherwise, if `intersect = FALSE`, the returned data.frame consists of the points of `x$data` in the union of A and B .

Note that if A (resp. B) is empty then the returned data.frame will be the points of x in B (resp. A).

Value

A [CMBDataFrame](#) containing the data in `x` restricted to the CMBWindow `new.window`

Examples

```
win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))

## Ensure you have a FITS file with correct path
## before uncommenting and running the rest of the example:
# cmbdat <- CMBDat("CMB_map_smica1024.fits", mmap = TRUE)
# class(cmbdat)
# cmbdat.win <- window(cmbdat, new.window = win1)
# class(cmbdat.win)
```

window.CMBDataFrame *Get a sub window from CMBDataFrame*

Description

When `new.window` or `in.pixels` is unspecified this function returns the `CMBWindow` attribute of a `CMBDataFrame`. The return value is `NULL` if the window is full sky. When `new.window` is specified this function instead returns a new `CMBDataFrame` whose `CMBWindow` attribute is `new.window`

Usage

```
## S3 method for class 'CMBDataFrame'
window(x, new.window, intersect = TRUE, in.pixels, in.pixels.res = 0, ...)
```

Arguments

| | |
|----------------------------|--|
| <code>x</code> | A <code>CMBDataFrame</code> . |
| <code>new.window</code> | Optionally specify a new window in which case a new <code>CMBDataFrame</code> is returned whose <code>CMBWindow</code> is <code>new.window</code> . <code>new.window</code> may also be a list (see details section and examples). |
| <code>intersect</code> | A boolean that determines the behaviour when <code>new.window</code> is a list containing BOTH regular type and "minus" type windows together (see details). |
| <code>in.pixels</code> | A vector of pixels at resolution <code>in.pixels.res</code> whose union contains the window(s) <code>new.window</code> entirely, or if <code>new.window</code> is unspecified then this whole pixel is returned. |
| <code>in.pixels.res</code> | An integer. Resolution (i.e., j such that $n_{side} = 2^j$) at which the <code>in.pixels</code> parameter is specified |
| <code>...</code> | Unused arguments. |

Details

Windows that are tagged with `set.minus` (see [CMBWindow](#)) are treated differently from other windows.

If the argument `new.window` is a list of `CMBWindows`, then interiors of all windows whose `winType` does not include "minus" are united (let A be their union) and exteriors of all windows whose `winType` does include "minus" are intersected, (let B be their intersection). Then, provided that `intersect = TRUE` (the default), the returned `CMBDataFrame` will be the points of `cmbdf` in the intersection of A and B . Otherwise, if `intersect = FALSE`, the returned `CMBDataFrame` consists of the points of x in the union of A and B .

Note that if A (resp. B) is empty then the returned `CMBDataFrame` will be the points of x in B (resp. A).

Value

The window attribute of x or, if `new.window/in.pixels` is specified, a new `CMBDataFrame`.

Examples

```
## Example 1: Create a new CMBDataFrame with a window

cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian",
                     ordering = "nested")
win <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
cmbdf.win <- window(cmbdf, new.window = win)
plot(cmbdf.win)
window(cmbdf.win)

## Example 2: Change the window of an existing CMBDataFrame

cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian", ordering = "nested")
window(cmbdf) <- win2 <- CMBWindow(theta = c(pi/6,pi/3,pi/3, pi/6),
                                   phi = c(0,0,pi/6,pi/6))

plot(cmbdf)

## Example 3: union of windows

## Create 2 windows
win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
win2 <- CMBWindow(theta = c(2*pi/3,3*pi/4,3*pi/4, 2*pi/3),
                 phi = c(pi/4,pi/4,pi/3,pi/3))

plot(win1)
plot(win2)

## Create CMBDataFrame with points in the union of win1 and win2

cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian", ordering = "nested")
cmbdf.win <- window(cmbdf, new.window = list(win1, win2), intersect = FALSE)
plot(cmbdf.win)
```

```

## Example 4: intersection of windows

## Create 2 windows
win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
win2 <- CMBWindow(theta = c(pi/4,pi/3,pi/3, pi/4),
                  phi = c(pi/4,pi/4,pi/3,pi/3))

plot(win1)
plot(win2)

## Create CMBDataFrame with points in the intersection of win1 and win2

cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian", ordering = "nested")
cmbdf.win1 <- window(cmbdf, new.window = win1)
cmbdf.win12 <- window(cmbdf.win1, new.window = win2)
plot(cmbdf.win12)
plot(win1)
plot(win2)

## Example 5: intersection of windows with "minus" type

## Create 2 windows with "minus" type
win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2),
                  set.minus =TRUE)
win2 <- CMBWindow(theta = c(pi/4,pi/3,pi/3, pi/4),
                  phi = c(pi/4,pi/4,pi/3,pi/3),
                  set.minus =TRUE)

plot(win1)
plot(win2)

## Create CMBDataFrame with points in the intersection of win1 and win2

cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian", ordering = "nested")
cmbdf.win <- window(cmbdf, new.window = list(win1, win2))
plot(cmbdf.win)

## Example 6: intersection of windows with different types

##Create 2 windows, one with "minus" type

win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
win2 <- CMBWindow(theta = c(pi/4,pi/3,pi/3, pi/4),
                  phi = c(pi/4,pi/4,pi/3,pi/3),
                  set.minus =TRUE)

plot(win1)
plot(win2)

## Create CMBDataFrame with points in the intersection of win1 and win2

cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian", ordering = "nested")
cmbdf.win <- window(cmbdf, new.window = list(win1, win2), intersect = TRUE)

```



```

plot(cmbdf.win)

## Example 7: union of windows with different types

win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2), set.minus =TRUE)
win2 <- CMBWindow(theta = c(pi/4,pi/3,pi/3, pi/4), phi = c(pi/4,pi/4,pi/3,pi/3))
plot(win1)
plot(win2)

## Create CMBDataFrame with points in the union of win1 and win2

cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian", ordering = "nested")
cmbdf.win <- window(cmbdf, new.window = list(win1, win2), intersect = FALSE)
plot(cmbdf.win)

```

window.data.frame *Get a sub window from a data.frame*

Description

This function returns a data.frame containing the data in `x` restricted to the `CMBWindow` `new.window`

Usage

```

## S3 method for class 'data.frame'
window(x, new.window, intersect = TRUE, ...)

```

Arguments

| | |
|-------------------------|---|
| <code>x</code> | A data.frame. Must have columns labelled <code>x,y,z</code> specifying cartesian coordinates, or columns labelled <code>theta, phi</code> specifying colatitude and longitude respectively. |
| <code>new.window</code> | A single <code>CMBWindow</code> object or a list of them. |
| <code>intersect</code> | A boolean that determines the behaviour when <code>new.window</code> is a list containing BOTH regular type and "minus" type windows together (see details). |
| <code>...</code> | Unused arguments. |

Details

Windows that are tagged with `set.minus` (see `CMBWindow`) are treated differently from other windows.

If the argument is a list of `CMBWindows`, then interiors of all windows whose `winType` does not include "minus" are united (let A be their union) and exteriors of all windows whose `winType` does include "minus" are intersected, (let B be their intersection). Then, provided that `intersect = TRUE` (the default), the returned data.frame will be the points of `x` in the the intersection of A and B .

Otherwise, if `intersect = FALSE`, the returned data.frame consists of the points of `x` in the union of `A` and `B`.

Note that if `A` (resp. `B`) is empty then the returned data.frame will be the points of `x` in `B` (resp. `A`).

Value

A data.frame containing the data in `x` restricted to the `CMBWindow` `new.window`

Examples

```
win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))

cmbdf <- CMBDataFrame(nside = 4)
df2 <- coords(cmbdf, new.coords = "cartesian")
df <- as.data.frame(df2[,1:3])
df
df.win <- window(df, new.window = win1)
df.win
```

`window.HPDataFrame` *Get a sub window from a [HPDataFrame](#)*

Description

This function returns a `HPDataFrame` containing the data in `hpdf` restricted to the `CMBWindow` `new.window`. If the `HPDataFrame` has columns `x,y,z` or `theta, phi` then these will be used to determine locations with priority over the `HEALPix` indices in `pix(hpdf)` unless `healpixCentered = TRUE` is given. Note that if `healpixCentered = TRUE` then columns `x,y,z` or `theta, phi` will be discarded and replaced with pixel center locations.

Usage

```
## S3 method for class 'HPDataFrame'
window(x, new.window, intersect = TRUE, healpixCentered = FALSE, ...)
```

Arguments

| | |
|------------------------------|---|
| <code>x</code> | A HPDataFrame . |
| <code>new.window</code> | Optional. A single CMBWindow object or a list of them. |
| <code>intersect</code> | A boolean that determines the behaviour when <code>new.window</code> is a list containing BOTH regular type and "minus" type windows together (see details). |
| <code>healpixCentered</code> | A boolean. If the <code>HPDataFrame</code> has columns <code>x,y,z</code> or <code>theta, phi</code> then these will be used to determine locations with priority over the <code>HEALPix</code> indices in <code>pix(x)</code> unless <code>healpixCentered = TRUE</code> is given. Note that if <code>healpixCentered = TRUE</code> then columns <code>x,y,z</code> or <code>theta, phi</code> will be discarded and replaced with pixel center locations. |

... Unused arguments.

Details

Windows that are tagged with `set.minus` (see [CMBWindow](#)) are treated differently from other windows.

If the argument is a list of `CMBWindows`, then interiors of all windows whose `winType` does not include "minus" are united (let A be their union) and exteriors of all windows whose `winType` does include "minus" are intersected, (let B be their intersection). Then, provided that `intersect = TRUE` (the default), the returned data.frame will be the points of `df` in the intersection of A and B . Otherwise, if `intersect = FALSE`, the returned data.frame consists of the points of `df` in the union of A and B .

Note that if A (resp. B) is empty then the returned data.frame will be the points of `df` in B (resp. A).

Value

A `HPDataFrame` containing the data in `x` restricted to the `CMBWindow` `new.window`. Or, if `new.window` is unspecified, then the window attribute of `x` is returned instead (and may be `NULL`).

Examples

```
ns <- 16
hpdf <- HPDataFrame(nside = ns, I = 1:(12*ns^2))
hpdf

win1 <- CMBWindow(theta = c(0,pi/2,pi/2), phi = c(0,0,pi/2))
plot(hpdf); plot(win1)

hpdf.win <- window(hpdf, new.window = win1)
plot(hpdf.win, col = "yellow", size = 4, add = TRUE)
attributes(hpdf.win)
window(hpdf.win)
hpdf.win
```

winType

Get/change winType

Description

Get/change the `winType` (polygon or disk) of a `CMBWindow`. If `new.type` is missing then the `winType` of `win` is returned. Otherwise, a new window is returned with `winType` equal to `new.type`. If you want to change the `winType` of `win` directly, then use `winType<-`, see the examples below.

Usage

```
winType(win, new.type)
```

Arguments

`win` a CMBWindow object or a list of such
`new.type` optionally specify a new type. Use this to change between "polygon" and "minus.polygon" or to change between "disc" and "minus.disc"

Value

If `new.type` is missing then the `winType` of `win` is returned. Otherwise a new window is returned with `winType` equal to `new.type`

Examples

```
win <- CMBWindow(theta = c(pi/2,pi/2,pi/3, pi/3), phi = c(0,pi/3,pi/3,0))
winType(win)
```

```
win1 <- CMBWindow(x=0,y=3/5,z=4/5,r=0.8)
winType(win1)
cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian",
                     ordering = "nested")
cmbdf.win1 <- window(cmbdf, new.window = win1)
plot(cmbdf.win1)
```

```
winType(win1) <- "minus.disc"
winType(win1)
cmbdf <- CMBDataFrame(nside = 64, coords = "cartesian",
                     ordering = "nested")
cmbdf.win1 <- window(cmbdf, new.window = win1)
plot(cmbdf.win1)
```

Index

ancestor, 4
areCompatibleCMBDFs, 4
as.CMBDataFrame, 5
assumedConvex, 6
assumedUniquePix, 7

baseNeighbours, 8

cbind, 8, 9
cbind.CMBDataFrame, 8
chi2.empirical, 9
chi2CMB, 9
children, 10, 42, 53
CMBDat, 10, 93
CMBDataFrame, 4, 7–9, 11, 15, 19, 21, 28,
30–34, 37, 40, 41, 49, 51, 55, 57, 60,
63, 65, 66, 71, 75, 77–80, 82, 83, 85,
91, 94
CMBWindow, 6, 9, 12, 13, 16, 30–32, 38, 50, 67,
77–79, 86, 87, 93–95, 97–99
coords, 14
coords.CMBDataFrame, 14, 15
coords.CMBWindow, 14, 16
coords.data.frame, 14, 17
coords.HPDataFrame, 14, 18
corrCMB, 19, 22, 64, 92
cov.spatial, 22–24
covCMB, 20, 21, 65, 92
covmodelCMB, 22, 48, 72–74, 88–90
covPwSp, 24
curve, 48

data.frame, 5, 11, 19, 21, 36, 39, 91
displayPixelBoundaries, 25
displayPixels, 26
download.file, 28
downloadCMBMap, 27
downloadCMBPS, 29

entropy, 30

entropyCMB, 30
exprob, 31
extrCMB, 32

fmf, 33
fRen, 34

geo2sph, 35
geoAngle, 36
geoArea, 36
geoArea.CMBDataFrame, 36, 37, 37
geoArea.CMBWindow, 36, 37, 38
geoArea.HPDataFrame, 36, 37, 38
geoDist, 39

header, 40
healpixCentered, 41
HPDataFrame, 7, 12, 18, 38, 41, 41, 47, 49, 51,
55, 58, 61, 63, 68, 75, 80, 87, 98

ibp2p, 44
is.CMBDat, 45
is.CMBDataFrame, 46
is.CMBWindow, 46
is.HPDataFrame, 47

lines.variomodel.variofit, 47, 48
linesCMB, 47

maxDist, 49
maxWindowDist, 50
minDist, 50
mmap, 10, 11

neighbours, 51
nest2ring, 52
nestSearch, 53
nlm, 90
nls, 90
nside, 54
nside.CMBDataFrame, 54, 55

nside.HPDataFrame, 54, 55
numeric2col, 56

optim, 90
ordering, 56
ordering.CMBDataFrame, 56, 57, 57
ordering.HPDataFrame, 56, 57, 58

p2bp, 58
p2ibp, 59
palette, 56
parent, 59
pix, 60
pix.CMBDataFrame, 60, 60
pix.HPDataFrame, 60, 61
pix2coords, 62
pixelArea, 62
pixelWindow, 63
plot.CMBCorrelation, 64
plot.CMBCovariance, 65
plot.CMBDataFrame, 65
plot.CMBWindow, 67
plot.HPDataFrame, 68
plot.variogram, 64, 65, 70, 70
plotAngDis, 71
plotcovmodelCMB, 72
plotvariogram, 73
practicalRange, 74
practicalRangeCMB, 74
print.CMBDataFrame, 75
print.HPDataFrame, 75
print.tbl_df, 75
pwSpCorr, 76

qqnorm, 77, 78
qqnormWin, 77, 77, 78
qqplot, 77, 78
qqplotWin, 77, 78, 78
qstat, 79

rbind, 80
rbind.CMBDataFrame, 80
rbind.data.frame, 80
rcosmo, 81, 81
rcosmo-package (rcosmo), 81
resolution, 82
rgl, 67, 70
rgl.material, 26, 67, 68, 70
ring2nest, 82

sampleCMB, 83
siblings, 84
sphericalHarmonics, 84
subWindow, 13
summary.CMBDataFrame, 85
summary.CMBWindow, 86
summary.HPDataFrame, 87
suppressMessages, 5

triangulate, 87

variofit, 88, 90
variofitCMB, 47, 48, 88
variog, 20–22, 64, 65, 70, 91, 92
variogramCMB, 20, 22, 70, 89, 91

window, 92
window.CMBDat, 93
window.CMBDataFrame, 92, 93, 94
window.data.frame, 92, 93, 97
window.HPDataFrame, 92, 93, 98
winType, 99