

Package ‘simstudy’

January 20, 2022

Type Package

Title Simulation of Study Data

Version 0.4.0

Date 2022-01-18

Description Simulates data sets in order to explore modeling techniques or better understand data generating processes. The user specifies a set of relationships between covariates, and generates data based on these specifications. The final data sets can represent data from randomized control trials, repeated measure (longitudinal) designs, and cluster randomized trials. Missingness can be generated using various mechanisms (MCAR, MAR, NMAR).

License GPL-3

URL <https://github.com/kgoldfeld/simstudy>,
<https://kgoldfeld.github.io/simstudy/>,
<https://kgoldfeld.github.io/simstudy/dev/>

BugReports <https://github.com/kgoldfeld/simstudy/issues>

Depends R (>= 3.3.0)

Imports data.table, glue, methods, mvnfast, mvtnorm, Rcpp, backports

Suggests covr, dplyr, formatR, gee, ggplot2, grid, gridExtra, hedgehog, knitr, magrittr, Matrix, mgcv, ordinal, pracma, rmarkdown, scales, splines, survival, testthat, gtsummary

LinkingTo Rcpp

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.1.2

NeedsCompilation yes

Author Keith Goldfeld [aut, cre] (<<https://orcid.org/0000-0002-0292-8780>>),
Jacob Wujciak-Jens [aut] (<<https://orcid.org/0000-0002-7281-3989>>)

Maintainer Keith Goldfeld <keith.goldfeld@nyulangone.org>

Repository CRAN

Date/Publication 2022-01-20 16:00:02 UTC

R topics documented:

addColumns	3
addCondition	4
addCorData	5
addCorFlex	6
addCorGen	8
addMarkov	12
addMultiFac	13
addPeriods	14
betaGetShapes	16
defCondition	17
defData	18
defDataAdd	20
defMiss	21
defRead	22
defReadAdd	23
defReadCond	24
defRepeat	25
defRepeatAdd	27
defSurv	28
delColumns	29
distributions	30
gammaGetShapeRate	31
genCatFormula	32
genCluster	33
genCorData	34
genCorFlex	35
genCorGen	36
genCorMat	38
genData	39
genDummy	40
genFactor	41
genFormula	42
genMarkov	43
genMiss	44
genMixFormula	45
genMultiFac	46
genNthEvent	47
genObs	48
genOrdCat	49
genSpline	52
genSurv	53
iccRE	54
mergeData	55
negbinomGetSizeProb	56
simstudy-deprecated	57
trimData	57

addColumnns 3

trtAssign	58
trtObserve	60
trtStepWedge	61
updateDef	62
updateDefAdd	63
viewBasis	65
viewSplines	65

Index 67

addColumnns *Add columns to existing data set*

Description

Add columns to existing data set

Usage

```
addColumnns(dtDefs, dtOld, envir = parent.frame())
```

Arguments

dtDefs name of definitions for added columns
dtOld name of data table that is to be updated
envir Environment the data definitions are evaluated in. Defaults to [base::parent.frame](#).

Value

an updated data.table that contains the added simulated data

Examples

```
# New data set

def <- defData(varname = "xNr", dist = "nonrandom", formula = 7, id = "idnum")
def <- defData(def, varname = "xUni", dist = "uniform", formula = "10;20")

dt <- genData(10, def)

# Add columns to dt

def2 <- defDataAdd(varname = "y1", formula = 10, variance = 3)
def2 <- defDataAdd(def2, varname = "y2", formula = .5, dist = "binary")
def2

dt <- addColumns(def2, dt)
dt
```

addCondition	<i>Add a single column to existing data set based on a condition</i>
--------------	--

Description

Add a single column to existing data set based on a condition

Usage

```
addCondition(condDefs, dtOld, newvar, envir = parent.frame())
```

Arguments

condDefs	Name of definitions for added column
dtOld	Name of data table that is to be updated
newvar	Name of new column to add
envir	Environment the data definitions are evaluated in. Defaults to base::parent.frame .

Value

An updated data.table that contains the added simulated data

Examples

```
# New data set

def <- defData(varname = "x", dist = "categorical", formula = ".33;.33")
def <- defData(def, varname = "y", dist = "uniform", formula = "-5;5")

dt <- genData(1000, def)

# Define conditions

defC <- defCondition(
  condition = "x == 1", formula = "5 + 2*y-.5*y^2",
  variance = 1, dist = "normal"
)
defC <- defCondition(defC,
  condition = "x == 2",
  formula = "3 - 3*y + y^2", variance = 2, dist = "normal"
)
defC <- defCondition(defC,
  condition = "x == 3",
  formula = "abs(y)", dist = "poisson"
)

# Add column
```

```
dt <- addCondition(defC, dt, "NewVar")

# Plot data

library(ggplot2)

ggplot(data = dt, aes(x = y, y = NewVar, group = x)) +
  geom_point(aes(color = factor(x)))
```

addCorData	<i>Add correlated data to existing data.table</i>
------------	---

Description

Add correlated data to existing data.table

Usage

```
addCorData(
  dtOld,
  idname,
  mu,
  sigma,
  corMatrix = NULL,
  rho,
  corstr = "ind",
  cnames = NULL
)
```

Arguments

dtOld	Data table that is the new columns will be appended to.
idname	Character name of id field, defaults to "id".
mu	A vector of means. The length of mu must be nvars.
sigma	Standard deviation of variables. If standard deviation differs for each variable, enter as a vector with the same length as the mean vector mu. If the standard deviation is constant across variables, as single value can be entered.
corMatrix	Correlation matrix can be entered directly. It must be symmetrical and positive semi-definite. It is not a required field; if a matrix is not provided, then a structure and correlation coefficient rho must be specified.
rho	Correlation coefficient, $-1 \leq \rho \leq 1$. Use if corMatrix is not provided.
corstr	Correlation structure of the variance-covariance matrix defined by sigma and rho. Options include "ind" for an independence structure, "cs" for a compound symmetry structure, and "ar1" for an autoregressive structure.
cnames	Explicit column names. A single string with names separated by commas. If no string is provided, the default names will be V#, where # represents the column.

Value

The original data table with the additional correlated columns

Examples

```
def <- defData(varname = "xUni", dist = "uniform", formula = "10;20", id = "myID")
def <- defData(def,
  varname = "xNorm", formula = "xUni * 2", dist = "normal",
  variance = 8
)

dt <- genData(250, def)

mu <- c(3, 8, 15)
sigma <- c(1, 2, 3)

dtAdd <- addCorData(dt, "myID",
  mu = mu, sigma = sigma,
  rho = .7, corstr = "cs"
)
dtAdd

round(var(dtAdd[, .(V1, V2, V3)]), 3)
round(cor(dtAdd[, .(V1, V2, V3)]), 2)

dtAdd <- addCorData(dt, "myID",
  mu = mu, sigma = sigma,
  rho = .7, corstr = "ar1"
)
round(cor(dtAdd[, .(V1, V2, V3)]), 2)

corMat <- matrix(c(1, .2, .8, .2, 1, .6, .8, .6, 1), nrow = 3)

dtAdd <- addCorData(dt, "myID",
  mu = mu, sigma = sigma,
  corMatrix = corMat
)
round(cor(dtAdd[, .(V1, V2, V3)]), 2)
```

 addCorFlex

Create multivariate (correlated) data - for general distributions

Description

Create multivariate (correlated) data - for general distributions

Usage

```
addCorFlex(
  dt,
  defs,
  rho = 0,
  tau = NULL,
  corstr = "cs",
  corMatrix = NULL,
  envir = parent.frame()
)
```

Arguments

dt	Data table that will be updated.
defs	Field definition table created by function defDataAdd.
rho	Correlation coefficient, $-1 \leq \rho \leq 1$. Use if corMatrix is not provided.
tau	Correlation based on Kendall's tau. If tau is specified, then it is used as the correlation even if rho is specified. If tau is NULL, then the specified value of rho is used, or rho defaults to 0.
corstr	Correlation structure of the variance-covariance matrix defined by sigma and rho. Options include "cs" for a compound symmetry structure and "ar1" for an autoregressive structure. Defaults to "cs".
corMatrix	Correlation matrix can be entered directly. It must be symmetrical and positive semi-definite. It is not a required field; if a matrix is not provided, then a structure and correlation coefficient rho must be specified.
envir	Environment the data definitions are evaluated in. Defaults to base::parent.frame .

Value

data.table with added column(s) of correlated data

Examples

```
defC <- defData(
  varname = "nInds", formula = 50, dist = "noZeroPoisson",
  id = "idClust"
)

dc <- genData(10, defC)
#### Normal only

dc <- addCorData(dc,
  mu = c(0, 0, 0, 0), sigma = c(2, 2, 2, 2), rho = .2,
  corstr = "cs", cnames = c("a", "b", "c", "d"),
  idname = "idClust"
)

di <- genCluster(dc, "idClust", "nInds", "id")
```

```

defI <- defDataAdd(
  varname = "A", formula = "-1 + a", variance = 3,
  dist = "normal"
)
defI <- defDataAdd(defI,
  varname = "B", formula = "4.5 + b", variance = .5,
  dist = "normal"
)
defI <- defDataAdd(defI,
  varname = "C", formula = "5*c", variance = 3,
  dist = "normal"
)
defI <- defDataAdd(defI,
  varname = "D", formula = "1.6 + d", variance = 1,
  dist = "normal"
)

#### Generate new data

di <- addCorFlex(di, defI, rho = 0.4, constr = "cs")

# Check correlations by cluster

for (i in 1:nrow(dc)) {
  print(cor(di[idClust == i, list(A, B, C, D)]))
}

# Check global correlations - should not be as correlated
cor(di[, list(A, B, C, D)])

```

addCorGen

Create multivariate (correlated) data - for general distributions

Description

Create multivariate (correlated) data - for general distributions

Usage

```

addCorGen(
  dtOld,
  nvars,
  idvar = "id",
  rho,
  constr,
  corMatrix = NULL,
  dist,
  param1,

```



```

    param2 = NULL,
    cnames = NULL,
    method = "copula",
    formSpec = NULL,
    periodvar = "period"
)

```

Arguments

dtOld	If an existing data.table is specified, then wide will be set to TRUE and n will be set to the nrow(dt) without any warning or error.
nvars	Number of new variables to create for each id.
idvar	String variable name of column represents individual level id for correlated data.
rho	Correlation coefficient, $-1 \leq \rho \leq 1$. Use if corMatrix is not provided.
corstr	Correlation structure of the variance-covariance matrix defined by sigma and rho. Options include "cs" for a compound symmetry structure and "ar1" for an autoregressive structure.
corMatrix	Correlation matrix can be entered directly. It must be symmetrical and positive semi-definite. It is not a required field; if a matrix is not provided, then a structure and correlation coefficient rho must be specified.
dist	A string indicating "normal", "binary", "poisson" or "gamma".
param1	A string that represents the column in dtOld that contains the parameter for the mean of the distribution. In the case of the uniform distribution the column specifies the minimum.
param2	A string that represents the column in dtOld that contains a possible second parameter for the distribution. For the normal distribution, this will be the variance; for the gamma distribution, this will be the dispersion; and for the uniform distribution, this will be the maximum.
cnames	Explicit column names. A single string with names separated by commas. If no string is provided, the default names will be V#, where # represents the column.
method	Two methods are available to generate correlated data. (1) "copula" uses the multivariate Gaussian copula method that is applied to all other distributions; this applies to all available distributions. (2) "ep" uses an algorithm developed by Emrich and Piedmonte (1991).
formSpec	The formula (as a string) that was used to generate the binary outcome in the 'defDataAdd' statement. This is only necessary when method "ep" is requested.
periodvar	A string value that indicates the name of the field that indexes the repeated measurement for an individual unit. The value defaults to "period".

Value

Original data.table with added column(s) of correlated data

References

Emrich LJ, Piedmonte MR. A Method for Generating High-Dimensional Multivariate Binary Variates. *The American Statistician* 1991;45:302-4.

Examples

```

# Wide example

def <- defData(varname = "xbase", formula = 5, variance = .4, dist = "gamma", id = "cid")
def <- defData(def, varname = "lambda", formula = ".5 + .1*xbase", dist = "nonrandom", link = "log")
def <- defData(def, varname = "p", formula = "-2 + .3*xbase", dist = "nonrandom", link = "logit")

dt <- genData(500, def)

dtX1 <- addCorGen(
  dtOld = dt, idvar = "cid", nvars = 3, rho = .7, corstr = "cs",
  dist = "poisson", param1 = "lambda"
)

dtX2 <- addCorGen(
  dtOld = dt, idvar = "cid", nvars = 4, rho = .4, corstr = "ar1",
  dist = "binary", param1 = "p"
)

# Long example

def <- defData(varname = "xbase", formula = 5, variance = .4, dist = "gamma", id = "cid")
def <- defData(def, "nperiods", formula = 3, dist = "noZeroPoisson")

def2 <- defDataAdd(
  varname = "lambda", formula = ".5+.5*period + .1*xbase",
  dist = "nonrandom", link = "log"
)
def2 <- defDataAdd(def2,
  varname = "p", formula = "-3+.2*period + .3*xbase",
  dist = "nonrandom", link = "logit"
)
def2 <- defDataAdd(def2,
  varname = "gammaMu", formula = ".2*period + .3*xbase",
  dist = "nonrandom", link = "log"
)
def2 <- defDataAdd(def2,
  varname = "gammaDis",
  formula = 1, dist = "nonrandom"
)
def2 <- defDataAdd(def2,
  varname = "normMu",
  formula = "5+period + .5*xbase", dist = "nonrandom"
)
def2 <- defDataAdd(def2,
  varname = "normVar", formula = 4,
  dist = "nonrandom"
)
def2 <- defDataAdd(def2,
  varname = "unifMin",
  formula = "5 + 2*period + .2*xbase", dist = "nonrandom"
)

```

```

def2 <- defDataAdd(def2,
  varname = "unifMax",
  formula = "unifMin + 20", dist = "nonrandom"
)

dt <- genData(1000, def)

dtLong <- addPeriods(dt, idvars = "cid", nPeriods = 3)
dtLong <- addColumns(def2, dtLong)

# Poisson distribution

dtX3 <- addCorGen(
  dtOld = dtLong, idvar = "cid", nvars = 3, rho = .6, constr = "cs",
  dist = "poisson", param1 = "lambda", cnames = "NewPois"
)
dtX3

# Binomial distribution - copula method

dtX4 <- addCorGen(
  dtOld = dtLong, idvar = "cid", nvars = 3, rho = .6, constr = "cs",
  dist = "binary", param1 = "p", cnames = "NewBin"
)

dtX4

# Gamma distribution

dtX6 <- addCorGen(
  dtOld = dtLong, idvar = "cid", nvars = 3, rho = .6, constr = "ar1",
  dist = "gamma", param1 = "gammaMu", param2 = "gammaDis",
  cnames = "NewGamma"
)

dtX6

# Normal distribution

dtX7 <- addCorGen(
  dtOld = dtLong, idvar = "cid", nvars = 3, rho = .6, constr = "ar1",
  dist = "normal", param1 = "normMu", param2 = "normVar",
  cnames = "NewNorm"
)

# Binary outcome - ep method

probform <- "-2 + .3*period"

def1 <- defDataAdd(
  varname = "p", formula = probform,
  dist = "nonrandom", link = "logit"
)

```

```

dx <- genData(100)
dx <- addPeriods(dx, nPeriods = 4)
dx <- addColumns(def1, dx)

dg <- addCorGen(dx,
  nvars = 4,
  corMatrix = NULL, rho = .3, constr = "cs",
  dist = "binary", param1 = "p",
  method = "ep", formSpec = probform,
  periodvar = "period"
)

```

addMarkov

Add Markov chain

Description

Generate a Markov chain for n individuals or units by specifying a transition matrix.

Usage

```

addMarkov(
  dd,
  transMat,
  chainLen,
  wide = FALSE,
  id = "id",
  pername = "period",
  varname = "state",
  widePrefix = "S",
  start@lab = NULL,
  trimvalue = NULL
)

```

Arguments

dd	data.table with a unique identifier
transMat	Square transition matrix where the sum of each row must equal 1. The dimensions of the matrix equal the number of possible states.
chainLen	Length of each chain that will be generated for each chain; minimum chain length is 2.
wide	Logical variable (TRUE or FALSE) indicating whether the resulting data table should be returned in wide or long format. The wide format includes all elements of a chain on a single row; the long format includes each element of a chain in its own row. The default is wide = FALSE, so the long format is returned by default.

id	Character string that represents name of "id" field. Defaults to "id".
pername	Character string that represents the variable name of the chain sequence in the long format. Defaults "period",
varname	Character string that represents the variable name of the state in the long format. Defaults to "state".
widePrefix	Character string that represents the variable name prefix for the state fields in the wide format. Defaults to "S".
start0lab	Character string that represents name of the integer field containing starting state (State 0) of the chain for each individual. If it is NULL, starting state defaults to 1. Default is NULL.
trimvalue	Integer value indicating end state. If trimvalue is not NULL, all records after the first instance of state = trimvalue will be deleted.

Value

A data table with n rows if in wide format, or n by chainLen rows if in long format.

Examples

```
def1 <- defData(varname = "x1", formula = 0, variance = 1)
def1 <- defData(def1, varname = "x2", formula = 0, variance = 1)
def1 <- defData(def1,
  varname = "S0", formula = ".6;.3;.1",
  dist = "categorical"
)

dd <- genData(20, def1)

# Transition matrix P

P <- t(matrix(c(
  0.7, 0.2, 0.1,
  0.5, 0.3, 0.2,
  0.0, 0.7, 0.3
),
nrow = 3
))

d1 <- addMarkov(dd, P, chainLen = 3)
d2 <- addMarkov(dd, P, chainLen = 5, wide = TRUE)
d3 <- addMarkov(dd, P, chainLen = 5, wide = TRUE, start0lab = "S0")
d4 <- addMarkov(dd, P, chainLen = 5, start0lab = "S0", trimvalue = 3)
```

Description

Add multi-factorial data

Usage

```
addMultiFac(dtOld, nFactors, levels = 2, coding = "dummy", colNames = NULL)
```

Arguments

dtOld	data.table that is to be modified
nFactors	Number of factors (columns) to generate.
levels	Vector or scalar. If a vector is specified, it must be the same length as nFactors. Each value of the vector represents the number of levels of each corresponding factor. If a scalar is specified, each factor will have the same number of levels. The default is 2 levels for each factor.
coding	String value to specify if "dummy" or "effect" coding is used. Defaults to "dummy".
colNames	A vector of strings, with a length of nFactors. The strings represent the name for each factor.

Value

A data.table that contains the added simulated data. Each new column contains an integer.

Examples

```
defD <- defData(varname = "x", formula = 0, variance = 1)

DT <- genData(360, defD)
DT <- addMultiFac(DT, nFactors = 3, levels = c(2, 3, 3), colNames = c("A", "B", "C"))
DT
DT[, .N, keyby = .(A, B, C)]

DT <- genData(300, defD)
DT <- addMultiFac(DT, nFactors = 3, levels = 2)
DT[, .N, keyby = .(Var1, Var2, Var3)]
```

addPeriods

Create longitudinal/panel data

Description

Create longitudinal/panel data

Usage

```
addPeriods(
  dtName,
  nPeriods = NULL,
  idvars = "id",
  timevars = NULL,
  timevarName = "timevar",
  timeid = "timeID",
  perName = "period"
)
```

Arguments

dtName	Name of existing data table
nPeriods	Number of time periods for each record
idvars	Names of index variables (in a string vector) that will be repeated during each time period
timevars	Names of time dependent variables. Defaults to NULL.
timevarName	Name of new time dependent variable
timeid	Variable name for new index field. Defaults to "timevar"
perName	Variable name for period field. Defaults to "period"

Value

An updated data.table that that has multiple rows per observation in dtName

Examples

```
tdef <- defData(varname = "T", dist = "binary", formula = 0.5)
tdef <- defData(tdef, varname = "Y0", dist = "normal", formula = 10, variance = 1)
tdef <- defData(tdef, varname = "Y1", dist = "normal", formula = "Y0 + 5 + 5 * T", variance = 1)
tdef <- defData(tdef, varname = "Y2", dist = "normal", formula = "Y0 + 10 + 5 * T", variance = 1)

dtTrial <- genData(5, tdef)
dtTrial

dtTime <- addPeriods(dtTrial,
  nPeriods = 3, idvars = "id",
  timevars = c("Y0", "Y1", "Y2"), timevarName = "Y"
)
dtTime

# Varying # of periods and intervals - need to have variables
# called nCount and mInterval

def <- defData(varname = "xbase", dist = "normal", formula = 20, variance = 3)
def <- defData(def, varname = "nCount", dist = "noZeroPoisson", formula = 6)
def <- defData(def, varname = "mInterval", dist = "gamma", formula = 30, variance = .01)
```

```
def <- defData(def, varname = "vInterval", dist = "nonrandom", formula = .07)

dt <- genData(200, def)
dt[id %in% c(8, 121)]

dtPeriod <- addPeriods(dt)
dtPeriod[id %in% c(8, 121)] # View individuals 8 and 121 only
```

betaGetShapes

Convert beta mean and precision parameters to two shape parameters

Description

Convert beta mean and precision parameters to two shape parameters

Usage

```
betaGetShapes(mean, precision)
```

Arguments

mean	The mean of a beta distribution
precision	The precision parameter (phi) of a beta distribution

Details

In simstudy, users specify the beta distribution as a function of two parameters - a mean and precision, where $0 < \text{mean} < 1$ and $\text{precision} > 0$. In this case, the variance of the specified distribution is $(\text{mean}) * (1 - \text{mean}) / (1 + \text{precision})$. The base R function `rbeta` uses the two shape parameters to specify the beta distribution. This function converts the mean and precision into the `shape1` and `shape2` parameters.

Value

A list that includes the shape parameters of the beta distribution

Examples

```
set.seed(12345)
mean <- 0.3
precision <- 1.6
rs <- betaGetShapes(mean, precision)
c(rs$shape1, rs$shape2)
vec <- rbeta(1000, shape1 = rs$shape1, shape2 = rs$shape2)
(estMoments <- c(mean(vec), var(vec)))
(theoryMoments <- c(mean, mean * (1 - mean) / (1 + precision)))
(theoryMoments <- with(rs, c(
  shape1 / (shape1 + shape2),
  (shape1 * shape2) / ((shape1 + shape2)^2 * (1 + shape1 + shape2))
)))
```

defCondition	<i>Add single row to definitions table of conditions that will be used to add data to an existing definitions table</i>
--------------	---

Description

Add single row to definitions table of conditions that will be used to add data to an existing definitions table

Usage

```
defCondition(  
  dtDefs = NULL,  
  condition,  
  formula,  
  variance = 0,  
  dist = "normal",  
  link = "identity"  
)
```

Arguments

dtDefs	Name of definition table to be modified. Null if this is a new definition.
condition	Formula specifying condition to be checked
formula	An R expression for mean (string)
variance	Number
dist	Distribution. For possibilities, see details
link	The link function for the mean, see details

Value

A data.table named dtName that is an updated data definitions table

See Also

[distributions](#)

Examples

```
# New data set  
  
def <- defData(varname = "x", dist = "noZeroPoisson", formula = 5)  
def <- defData(def, varname = "y", dist = "normal", formula = 0, variance = 9)  
  
dt <- genData(10, def)  
  
# Add columns to dt
```

```

defC <- defCondition(
  condition = "x == 1", formula = "5 + 2*y",
  variance = 1, dist = "normal"
)

defC <- defCondition(defC,
  condition = "x <= 5 & x >= 2", formula = "3 - 2*y",
  variance = 1, dist = "normal"
)

defC <- defCondition(defC,
  condition = "x >= 6", formula = 1,
  variance = 1, dist = "normal"
)

defC

# Add conditional column with field name "z"

dt <- addCondition(defC, dt, "z")
dt

```

defData

Add single row to definitions table

Description

Add single row to definitions table

Usage

```

defData(
  dtDefs = NULL,
  varname,
  formula,
  variance = 0,
  dist = "normal",
  link = "identity",
  id = "id"
)

```

Arguments

dtDefs	Definition data.table to be modified
varname	Name (string) of new variable
formula	An R expression for mean (string)
variance	Number

dist	Distribution. For possibilities, see details
link	The link function for the mean, see details
id	A string indicating the field name for the unique record identifier

Details

The possible data distributions are: normal, binary, binomial, poisson, noZeroPoisson, uniform, categorical, gamma, beta, nonrandom, uniformInt, negBinomial, exponential, mixture, trtAssign.

Value

A data.table named dtName that is an updated data definitions table

See Also

[distributions](#)

Examples

```
extVar <- 2.3
def <- defData(varname = "xNr", dist = "nonrandom", formula = 7, id = "idnum")
def <- defData(def, varname = "xUni", dist = "uniform", formula = "10;20")
def <- defData(def,
  varname = "xNorm", formula = "xNr + xUni * 2", dist = "normal",
  variance = 8
)
def <- defData(def,
  varname = "xPois", dist = "poisson", formula = "xNr - 0.2 * xUni",
  link = "log"
)
def <- defData(def, varname = "xCat", formula = "0.3;0.2;0.5", dist = "categorical")
def <- defData(def,
  varname = "xGamma", dist = "gamma", formula = "5+xCat",
  variance = 1, link = "log"
)
def <- defData(def,
  varname = "xBin", dist = "binary", formula = "-3 + xCat",
  link = "logit"
)
def <- defData(def,
  varname = "external", dist = "nonrandom",
  formula = "xBin * log(.extVar)"
)
def
```

defDataAdd	<i>Add single row to definitions table that will be used to add data to an existing data.table</i>
------------	--

Description

Add single row to definitions table that will be used to add data to an existing data.table

Usage

```
defDataAdd(  
  dtDefs = NULL,  
  varname,  
  formula,  
  variance = 0,  
  dist = "normal",  
  link = "identity"  
)
```

Arguments

dtDefs	Name of definition table to be modified. Null if this is a new definition.
varname	Name (string) of new variable
formula	An R expression for mean (string)
variance	Number
dist	Distribution. For possibilities, see details
link	The link function for the mean, see details

Value

A data.table named dtName that is an updated data definitions table

See Also

[distributions]

Examples

```
# New data set  
  
def <- defData(varname = "xNr", dist = "nonrandom", formula = 7, id = "idnum")  
def <- defData(def, varname = "xUni", dist = "uniform", formula = "10;20")  
  
dt <- genData(10, def)  
  
# Add columns to dt
```

```
def2 <- defDataAdd(varname = "y1", formula = 10, variance = 3)
def2 <- defDataAdd(def2, varname = "y2", formula = .5, dist = "binary")
def2

dt <- addColumns(def2, dt)
dt
```

defMiss

*Definitions for missing data***Description**

Add single row to definitions table for missing data

Usage

```
defMiss(
  dtDefs = NULL,
  varname,
  formula,
  logit.link = FALSE,
  baseline = FALSE,
  monotonic = FALSE
)
```

Arguments

dtDefs	Definition data.table to be modified
varname	Name of variable with missingness
formula	Formula to describe pattern of missingness
logit.link	Indicator set to TRUE when the probability of missingness is based on a logit model.
baseline	Indicator is set to TRUE if the variable is a baseline measure and should be missing throughout an entire observation period. This is applicable to repeated measures/longitudinal data.
monotonic	Indicator set to TRUE if missingness at time t is followed by missingness at all follow-up times > t.

Value

A data.table named dtName that is an updated data definitions table

See Also

[genMiss](#), [genObs](#)

Examples

```

def1 <- defData(varname = "m", dist = "binary", formula = .5)
def1 <- defData(def1, "u", dist = "binary", formula = .5)
def1 <- defData(def1, "x1", dist = "normal", formula = "20*m + 20*u", variance = 2)
def1 <- defData(def1, "x2", dist = "normal", formula = "20*m + 20*u", variance = 2)
def1 <- defData(def1, "x3", dist = "normal", formula = "20*m + 20*u", variance = 2)

dtAct <- genData(1000, def1)

defM <- defMiss(varname = "x1", formula = .15, logit.link = FALSE)
defM <- defMiss(defM, varname = "x2", formula = ".05 + m * 0.25", logit.link = FALSE)
defM <- defMiss(defM, varname = "x3", formula = ".05 + u * 0.25", logit.link = FALSE)
defM <- defMiss(defM, varname = "u", formula = 1, logit.link = FALSE) # not observed
defM

# Generate missing data matrix

missMat <- genMiss(dtName = dtAct, missDefs = defM, idvars = "id")
missMat

# Generate observed data from actual data and missing data matrix

dtObs <- genObs(dtAct, missMat, idvars = "id")
dtObs

```

defRead

*Read external csv data set definitions***Description**

Read external csv data set definitions

Usage

```
defRead(filename, id = "id")
```

Arguments

filename	String file name, including full path. Must be a csv file.
id	string that includes name of id field. Defaults to "id"

Value

A data.table with data set definitions

See Also

[distributions]

Examples

```
# Create temporary external "csv" file

test1 <- c(
  "varname,formula,variance,dist,link",
  "nr,7, 0,nonrandom,identity",
  "x1,.4, 0,binary,identity",
  "y1,nr + x1 * 2,8,normal,identity",
  "y2,nr - 0.2 * x1,0,poisson, log"
)

tfcsv <- tempfile()
writeLines(test1, tfcsv)

# Read external csv file stored in file "tfcsv"

defs <- defRead(tfcsv, id = "myID")
defs

unlink(tfcsv)

# Generate data based on external definition

genData(5, defs)
```

defReadAdd

Read external csv data set definitions for adding columns

Description

Read external csv data set definitions for adding columns

Usage

```
defReadAdd(filename)
```

Arguments

filename String file name, including full path. Must be a csv file.

Value

A data.table with data set definitions

See Also

[distributions]

Examples

```
# Create temporary external "csv" files

test1 <- c(
  "varname,formula,variance,dist,link",
  "nr,7, 0,nonrandom,identity"
)

tfcsv1 <- tempfile()
writeLines(test1, tfcsv1)

test2 <- c(
  "varname,formula,variance,dist,link",
  "x1,.4, 0,binary,identity",
  "y1,nr + x1 * 2,8,normal,identity",
  "y2,nr - 0.2 * x1,0,poisson, log"
)

tfcsv2 <- tempfile()
writeLines(test2, tfcsv2)

# Generate data based on external definitions

defs <- defRead(tfcsv1)
dt <- genData(5, defs)
dt

# Add additional data based on external definitions

defs2 <- defReadAdd(tfcsv2)
dt <- addColumns(defs2, dt)
dt

unlink(tfcsv1)
unlink(tfcsv2)
```

defReadCond*Read external csv data set definitions for adding columns*

Description

Read external csv data set definitions for adding columns

Usage

```
defReadCond(filen)
```

Arguments

filen String file name, including full path. Must be a csv file.

Value

A data.table with data set definitions

See Also

[distributions]

Examples

```
# Create temporary external "csv" files

test1 <- c(
  "varname,formula,variance,dist,link",
  "x,0.3;0.4;0.3,0,categorical,identity"
)

tfcsv1 <- tempfile()
writeLines(test1, tfcsv1)

test2 <- c(
  "condition,formula,variance,dist,link",
  "x == 1, 0.4,0,binary,identity",
  "x == 2, 0.6,0,binary,identity",
  "x >= 3, 0.8,0,binary,identity"
)

tfcsv2 <- tempfile()
writeLines(test2, tfcsv2)

# Generate data based on external definitions

defs <- defRead(tfcsv1)
dt <- genData(2000, defs)
dt

# Add column based on

defsCond <- defReadCond(tfcsv2)
dt <- addCondition(defsCond, dt, "y")
dt

dt[, mean(y), keyby = x]

unlink(tfcsv1)
unlink(tfcsv2)
```

Description

Add multiple (similar) rows to definitions table

Usage

```
defRepeat(
  dtDefs = NULL,
  nVars,
  prefix,
  formula,
  variance = 0,
  dist = "normal",
  link = "identity",
  id = "id"
)
```

Arguments

dtDefs	Definition data.table to be modified
nVars	Number of new variables to define
prefix	Prefix (character) for new variables
formula	An R expression for mean (string)
variance	Number or formula
dist	Distribution. For possibilities, see details
link	The link function for the mean, see details
id	A string indicating the field name for the unique record identifier

Details

The possible data distributions are: `'r paste0(.getDists()),collapse = ", ")'`.

Value

A data.table named dtName that is an updated data definitions table

See Also

[distributions]

Examples

```
def <- defRepeat(
  nVars = 4, prefix = "g", formula = "1/3;1/3;1/3",
  variance = 0, dist = "categorical"
)
def <- defData(def, varname = "a", formula = "1;1", dist = "trtAssign")
def <- defRepeat(def, 8, "b", formula = "5 + a", variance = 3, dist = "normal")
def <- defData(def, "y", formula = "0.10", dist = "binary")
```

```
def
```

defRepeatAdd	<i>Add multiple (similar) rows to definitions table that will be used to add data to an existing data.table</i>
--------------	---

Description

Add multiple (similar) rows to definitions table that will be used to add data to an existing data.table

Usage

```
defRepeatAdd(
  dtDefs = NULL,
  nVars,
  prefix,
  formula,
  variance = 0,
  dist = "normal",
  link = "identity",
  id = "id"
)
```

Arguments

dtDefs	Definition data.table to be modified
nVars	Number of new variables to define
prefix	Prefix (character) for new variables
formula	An R expression for mean (string)
variance	Number or formula
dist	Distribution. For possibilities, see details
link	The link function for the mean, see details
id	A string indicating the field name for the unique record identifier

Details

The possible data distributions are: `'r paste0(.getDists(),collapse = ", ")'`.

Value

A data.table named dtName that is an updated data definitions table

See Also

[distributions]

Examples

```
def <- defRepeatAdd(
  nVars = 4, prefix = "g", formula = "1/3;1/3;1/3",
  variance = 0, dist = "categorical"
)
def <- defDataAdd(def, varname = "a", formula = "1;1", dist = "trtAssign")
def <- defRepeatAdd(def, 8, "b", formula = "5 + a", variance = 3, dist = "normal")
def <- defDataAdd(def, "y", formula = "0.10", dist = "binary")

def
```

defSurv

*Add single row to survival definitions***Description**

Add single row to survival definitions

Usage

```
defSurv(dtDefs = NULL, varname, formula = 0, scale, shape = 1)
```

Arguments

dtDefs	Definition data.table to be modified
varname	Variable name
formula	Covariates predicting survival
scale	Scale parameter for the Weibull distribution.
shape	The shape of the Weibull distribution. Shape = 1 for an exponential distribution

Value

A data.table named dtName that is an updated data definitions table

Examples

```
# Baseline data definitions

def <- defData(varname = "x1", formula = .5, dist = "binary")
def <- defData(def, varname = "x2", formula = .5, dist = "binary")
def <- defData(def, varname = "grp", formula = .5, dist = "binary")

# Survival data definitions

sdef <- defSurv(
  varname = "survTime", formula = "1.5*x1",
  scale = "grp*50 + (1-grp)*25", shape = "grp*1 + (1-grp)*1.5"
)
```

```

sdef <- defSurv(sdef, varname = "censorTime", scale = 80, shape = 1)

sdef

# Baseline data definitions

dtSurv <- genData(300, def)

# Add survival times

dtSurv <- genSurv(dtSurv, sdef)

head(dtSurv)

```

delColumns	<i>Delete columns from existing data set</i>
------------	--

Description

Delete columns from existing data set

Usage

```
delColumns(dtOld, vars)
```

Arguments

dtOld	Name of data table that is to be updated.
vars	Vector of column names (as strings).

Value

An updated data.table without vars.

Examples

```

# New data set

def <- defData(varname = "x", dist = "noZeroPoisson", formula = 7, id = "idnum")
def <- defData(def, varname = "xUni", dist = "uniformInt", formula = "x-3;x+3")

dt <- genData(10, def)
dt

# Delete column

dt <- delColumns(dt, "x")
dt

```

distributions

*Distributions for Data Definitions***Description**

This help file describes the distributions used for data creation in `simstudy`.

Arguments

<code>formula</code>	Desired mean as a Number or an R expression for mean as a String. Variables defined via <code>defData()</code> and variables within the parent environment (prefixed with <code>..</code>) can be used within the formula. Functions from the parent environment can be used without a prefix.
<code>variance</code>	Number. Default is 0.
<code>link</code>	String identifying the link function to be used. Default is <code>identity</code> .

Details

For details about the statistical distributions please see [stats::distributions](#), any non-statistical distributions will be explained below. Required variables and expected pattern for each distribution can be found in this table:

name	formula	format	variance	link
<code>beta</code>	mean	String or Number	dispersion value	identity or log
<code>binary</code>	probability for 1	String or Number	NA	identity or log
<code>binomial</code>	probability of success	String or Number	number of trials	identity or log
<code>categorical</code>	probabilities	$p_1;p_2;...;p_n$	category labels: a;b;c , 50;130;20	identity or log
<code>exponential</code>	mean (lambda)	String or Number	NA	identity or log
<code>gamma</code>	mean	String or Number	dispersion value	identity or log
<code>mixture</code>	formula	$x_1 p_1 + x_2 p_2 \dots x_n p_n$	NA	NA
<code>negBinomial</code>	mean	String or Number	dispersion value	identity or log
<code>nonrandom</code>	formula	String or Number	NA	NA
<code>normal</code>	mean	String or Number	variance	NA
<code>noZeroPoisson</code>	mean	String or Number	NA	identity or log
<code>poisson</code>	mean	String or Number	NA	identity or log
<code>trtAssign</code>	ratio	$r_1;r_2;...;r_n$	stratification	identity or no
<code>uniform</code>	range	from;to	NA	NA
<code>uniformInt</code>	range	from;to	NA	NA

Mixture

The mixture distribution makes it possible to mix to previously defined distributions/variables. Each variable that should be part of the new distribution x_1, \dots, X_n is assigned a probability p_1, \dots, p_n . For more information see [rdatagen.net](#).

Examples

```

ext_var <- 2.9
def <- defData(varname = "external", formula = "3 + log(.ext_var)", variance = .5)
def
genData(5, def)

```

gammaGetShapeRate	<i>Convert gamma mean and dispersion parameters to shape and rate parameters</i>
-------------------	--

Description

Convert gamma mean and dispersion parameters to shape and rate parameters

Usage

```
gammaGetShapeRate(mean, dispersion)
```

Arguments

mean	The mean of a gamma distribution
dispersion	The dispersion parameter of a gamma distribution

Details

In simstudy, users specify the gamma distribution as a function of two parameters - a mean and dispersion. In this case, the variance of the specified distribution is $(\text{mean}^2) * \text{dispersion}$. The base R function `rgamma` uses the shape and rate parameters to specify the gamma distribution. This function converts the mean and dispersion into the shape and rate.

Value

A list that includes the shape and rate parameters of the gamma distribution

Examples

```

set.seed(12345)
mean <- 5
dispersion <- 1.5
rs <- gammaGetShapeRate(mean, dispersion)
c(rs$shape, rs$rate)
vec <- rgamma(1000, shape = rs$shape, rate = rs$rate)
(estMoments <- c(mean(vec), var(vec)))
(theoryMoments <- c(mean, mean^2 * dispersion))
(theoryMoments <- c(rs$shape / rs$rate, rs$shape / rs$rate^2))

```

genCatFormula	<i>Generate Categorical Formula</i>
---------------	-------------------------------------

Description

Create a semi-colon delimited string of probabilities to be used to define categorical data.

Usage

```
genCatFormula(..., n = 0)
```

Arguments

...	one or more numeric values to be concatenated, delimited by ";".
n	Number of probabilities (categories) to be generated - all with equal probability.

Details

The function accepts a number of probabilities or a value of n, but not both.

If probabilities are passed, the string that is returned depends on the nature of those probabilities. If the sum of the probabilities is less than 1, an additional category is created with the probability $1 - \text{sum}(\text{provided probabilities})$. If the sum of the probabilities is equal to 1, then the number of categories is set to the number of probabilities provided. If the sum of the probabilities exceeds one (and there is more than one probability), the probabilities are standardized by dividing by the sum of the probabilities provided.

If n is provided, n probabilities are included in the string, each with a probability equal to $1/n$.

Value

string with multinomial probabilities.

Examples

```
genCatFormula(0.25, 0.25, 0.50)
genCatFormula(1 / 3, 1 / 2)
genCatFormula(1, 2, 3)
genCatFormula(n = 5)
```

genCluster *Simulate clustered data*

Description

Simulate data set that is one level down in a multilevel data context. The level "2" data set must contain a field that specifies the number of individual records in a particular cluster.

Usage

```
genCluster(dtClust, cLevelVar, numIndsVar, level1ID, allLevel2 = TRUE)
```

Arguments

dtClust	Name of existing data set that contains the level "2" data
cLevelVar	Variable name (string) of cluster id in dtClust
numIndsVar	Variable name (string) of number of observations per cluster in dtClust. Can also be a single integer value that will be used for all clusters.
level1ID	Name of id field in new level "1" data set
allLevel2	Indicator: if set to TRUE (default), the returned data set includes all of the Level 2 data columns. If FALSE, the returned data set only includes the Levels 1 and 2 ids.

Value

A simulated data table with level "1" data

Examples

```
gen.school <- defData(
  varname = "s0", dist = "normal",
  formula = 0, variance = 3, id = "idSchool"
)
gen.school <- defData(gen.school,
  varname = "nClasses",
  dist = "noZeroPoisson", formula = 3
)

dtSchool <- genData(3, gen.school) #'
dtSchool

dtClass <- genCluster(dtSchool,
  cLevelVar = "idSchool",
  numIndsVar = "nClasses", level1ID = "idClass"
)
dtClass

dtClass <- genCluster(dtSchool,
```

```

    cLevelVar = "idSchool",
    numIndsVar = 3, level1ID = "idClass"
  )
  dtClass

```

genCorData

Create correlated data

Description

Create correlated data

Usage

```

genCorData(
  n,
  mu,
  sigma,
  corMatrix = NULL,
  rho,
  corstr = "ind",
  cnames = NULL,
  idname = "id"
)

```

Arguments

n	Number of observations
mu	A vector of means. The length of mu must be nvars.
sigma	Standard deviation of variables. If standard deviation differs for each variable, enter as a vector with the same length as the mean vector mu. If the standard deviation is constant across variables, as single value can be entered.
corMatrix	Correlation matrix can be entered directly. It must be symmetrical and positive semi-definite. It is not a required field; if a matrix is not provided, then a structure and correlation coefficient rho must be specified.
rho	Correlation coefficient, $-1 \leq \rho \leq 1$. Use if corMatrix is not provided.
corstr	Correlation structure of the variance-covariance matrix defined by sigma and rho. Options include "ind" for an independence structure, "cs" for a compound symmetry structure, and "ar1" for an autoregressive structure.
cnames	Explicit column names. A single string with names separated by commas. If no string is provided, the default names will be V#, where # represents the column.
idname	The name of the index id name. Defaults to "id."

Value

A data.table with n rows and the k + 1 columns, where k is the number of means in the vector mu.

Examples

```

mu <- c(3, 8, 15)
sigma <- c(1, 2, 3)

corMat <- matrix(c(1, .2, .8, .2, 1, .6, .8, .6, 1), nrow = 3)

dtcor1 <- genCorData(1000, mu = mu, sigma = sigma, rho = .7, corstr = "cs")
dtcor2 <- genCorData(1000, mu = mu, sigma = sigma, corMatrix = corMat)

dtcor1
dtcor2

round(var(dtcor1[, .(V1, V2, V3)]), 3)
round(cor(dtcor1[, .(V1, V2, V3)]), 2)

round(var(dtcor2[, .(V1, V2, V3)]), 3)
round(cor(dtcor2[, .(V1, V2, V3)]), 2)

```

genCorFlex

*Create multivariate (correlated) data - for general distributions***Description**

Create multivariate (correlated) data - for general distributions

Usage

```
genCorFlex(n, defs, rho = 0, tau = NULL, corstr = "cs", corMatrix = NULL)
```

Arguments

n	Number of observations
defs	Field definition table created by function 'defData'. All definitions must be scalar. Definition specifies distribution, mean, and variance, with all caveats for each of the distributions. (See defData).
rho	Correlation coefficient, $-1 \leq \rho \leq 1$. Use if corMatrix is not provided.
tau	Correlation based on Kendall's tau. If tau is specified, then it is used as the correlation even if rho is specified. If tau is NULL, then the specified value of rho is used, or rho defaults to 0.
corstr	Correlation structure of the variance-covariance matrix defined by sigma and rho. Options include "cs" for a compound symmetry structure and "ar1" for an autoregressive structure. Defaults to "cs".
corMatrix	Correlation matrix can be entered directly. It must be symmetrical and positive semi-definite. It is not a required field; if a matrix is not provided, then a structure and correlation coefficient rho must be specified. This is only used if tau is not specified.

Value

data.table with added column(s) of correlated data

Examples

```
def <- defData(varname = "xNorm", formula = 0, variance = 4, dist = "normal")
def <- defData(def, varname = "xGamma1", formula = 15, variance = 2, dist = "gamma")
def <- defData(def, varname = "xBin", formula = 0.5, dist = "binary")
def <- defData(def, varname = "xUnif1", formula = "0;10", dist = "uniform")
def <- defData(def, varname = "xPois", formula = 15, dist = "poisson")
def <- defData(def, varname = "xUnif2", formula = "23;28", dist = "uniform")
def <- defData(def, varname = "xUnif3", formula = "100;150", dist = "uniform")
def <- defData(def, varname = "xGamma2", formula = 150, variance = 0.003, dist = "gamma")
def <- defData(def, varname = "xNegBin", formula = 5, variance = .8, dist = "negBinomial")

dt <- genCorFlex(1000, def, tau = 0.3, corstr = "cs")

cor(dt[, -"id"])
cor(dt[, -"id"], method = "kendall")
var(dt[, -"id"])
apply(dt[, -"id"], 2, mean)
```

genCorGen

Create multivariate (correlated) data - for general distributions

Description

Create multivariate (correlated) data - for general distributions

Usage

```
genCorGen(
  n,
  nvars,
  params1,
  params2 = NULL,
  dist,
  rho,
  corstr,
  corMatrix = NULL,
  wide = FALSE,
  cnames = NULL,
  method = "copula",
  idname = "id"
)
```

Arguments

n	Number of observations
nvars	Number of variables
params1	A single vector specifying the mean of the distribution. The vector is of length 1 if the mean is the same across all observations, otherwise the vector is of length nvars. In the case of the uniform distribution the vector specifies the minimum.
params2	A single vector specifying a possible second parameter for the distribution. For the normal distribution, this will be the variance; for the gamma distribution, this will be the dispersion; and for the uniform distribution, this will be the maximum. The vector is of length 1 if the mean is the same across all observations, otherwise the vector is of length nvars.
dist	A string indicating "binary", "poisson" or "gamma", "normal", or "uniform".
rho	Correlation coefficient, $-1 \leq \rho \leq 1$. Use if corMatrix is not provided.
corstr	Correlation structure of the variance-covariance matrix defined by sigma and rho. Options include "cs" for a compound symmetry structure and "ar1" for an autoregressive structure.
corMatrix	Correlation matrix can be entered directly. It must be symmetrical and positive semi-definite. It is not a required field; if a matrix is not provided, then a structure and correlation coefficient rho must be specified.
wide	The layout of the returned file - if wide = TRUE, all new correlated variables will be returned in a single record, if wide = FALSE, each new variable will be its own record (i.e. the data will be in long form). Defaults to FALSE.
cnames	Explicit column names. A single string with names separated by commas. If no string is provided, the default names will be V#, where # represents the column.
method	Two methods are available to generate correlated data. (1) "copula" uses the multivariate Gaussian copula method that is applied to all other distributions; this applies to all available distributions. (2) "ep" uses an algorithm developed by Emrich and Piedmonte (1991).
idname	Character value that specifies the name of the id variable.

Value

data.table with added column(s) of correlated data

References

Emrich LJ, Piedmonte MR. A Method for Generating High-Dimensional Multivariate Binary Variates. *The American Statistician* 1991;45:302-4.

Examples

```
set.seed(23432)
l <- c(8, 10, 12)

genCorGen(1000, nvars = 3, params1 = 1, dist = "poisson", rho = .7, corstr = "cs")
genCorGen(1000, nvars = 3, params1 = 5, dist = "poisson", rho = .7, corstr = "cs")
```

```

genCorGen(1000, nvars = 3, params1 = 1, dist = "poisson", rho = .7, corstr = "cs", wide = TRUE)
genCorGen(1000, nvars = 3, params1 = 5, dist = "poisson", rho = .7, corstr = "cs", wide = TRUE)

genCorGen(1000,
  nvars = 3, params1 = 1, dist = "poisson", rho = .7, corstr = "cs",
  cnames = "new_var"
)
genCorGen(1000,
  nvars = 3, params1 = 1, dist = "poisson", rho = .7, corstr = "cs",
  wide = TRUE, cnames = "a, b, c"
)

genCorGen(1000, nvars = 3, params1 = c(.3, .5, .7), dist = "binary", rho = .3, corstr = "cs")
genCorGen(1000,
  nvars = 3, params1 = 1, params2 = c(1, 1, 1), dist = "gamma", rho = .3,
  corstr = "cs", wide = TRUE
)

genCorGen(1000,
  nvars = 3, params1 = c(.3, .5, .7), dist = "binary",
  corMatrix = genCorMat(3), method = "ep"
)
genCorGen(1000,
  nvars = 3, params1 = c(.3, .5, .7), dist = "binary",
  corMatrix = genCorMat(3), method = "copula"
)

```

genCorMat

Create a correlation matrix

Description

Create a correlation matrix

Usage

```
genCorMat(nvars, cors = NULL)
```

Arguments

nvars	number of rows and columns (i.e. number of variables) for correlation matrix
cors	vector of correlations.

Details

If the vector cors is not specified, a random correlation matrix is generated with no assumptions. If the vector is provided, it should be interpreted as the lower triangle of the correlation matrix, and is specified by reading down the columns. For example, if CM is the correlation matrix and nvars = 3, then $CM[2,1] = cors[1]$, $CM[3,1] = cors[2]$, and $CM[3,2] = cors[3]$.

Value

correlation matrix of size nvars x nvars

Examples

```
genCorMat(3, c(.3, -.2, .1))
genCorMat(3)

genCorMat(5, c(.3, -.2, .1, .2, .5, .2, -.1, .3, .1, .2))
genCorMat(5)
```

genData	<i>Calling function to simulate data</i>
---------	--

Description

Calling function to simulate data

Usage

```
genData(n, dtDefs = NULL, id = "id", envir = parent.frame())
```

Arguments

n	the number of observations required in the data set.
dtDefs	name of definitions data.table/data.frame. If no definitions are provided a data set with ids only is generated.
id	The string defining the id of the record. Will override previously set id name with a warning (unless the old value is 'id'). If the id attribute in dtDefs is NULL will default to 'id'.
envir	Environment the data definitions are evaluated in. Defaults to base::parent.frame .

Value

A data.table that contains the simulated data.

Examples

```
genData(5)
genData(5, id = "grpID")

def <- defData(
  varname = "xNr", dist = "nonrandom", formula = 7,
  id = "idnum"
)
def <- defData(def,
  varname = "xUni", dist = "uniform",
  formula = "10;20"
```

```

)
def <- defData(def,
  varname = "xNorm", formula = "xNr + xUni * 2",
  dist = "normal", variance = 8
)
def <- defData(def,
  varname = "xPois", dist = "poisson",
  formula = "xNr - 0.2 * xUni", link = "log"
)
def <- defData(def,
  varname = "xCat", formula = "0.3;0.2;0.5",
  dist = "categorical"
)
def <- defData(def,
  varname = "xGamma", dist = "gamma", formula = "5+xCat",
  variance = 1, link = "log"
)
def <- defData(def,
  varname = "xBin", dist = "binary", formula = "-3 + xCat",
  link = "logit"
)
def

genData(5, def)

```

genDummy

Create dummy variables from a factor or integer variable

Description

Create dummy variables from a factor or integer variable

Usage

```
genDummy(dtName, varname, sep = ".", replace = FALSE)
```

Arguments

dtName	Data table with column
varname	Name of factor
sep	Character to be used in creating new name for dummy fields. Valid characters include all letters and "_". Will default to ".". If an invalid character is provided, it will be replaced by default.
replace	If replace is set to TRUE (defaults to FALSE) the field referenced varname will be removed.

Examples

```
# First example:

def <- defData(varname = "cat", formula = ".2;.3;.5", dist = "categorical")
def <- defData(def, varname = "x", formula = 5, variance = 2)

dx <- genData(200, def)
dx

dx <- genFactor(dx, "cat", labels = c("one", "two", "three"), replace = TRUE)
dx <- genDummy(dx, varname = "fcat", sep = "_")

dx

# Second example:

dx <- genData(15)
dx <- trtAssign(dtName = dx, 3, grpName = "arm")
dx <- genDummy(dx, varname = "arm")
dx
```

genFactor

Create factor variable from an existing (non-double) variable

Description

Create factor variable from an existing (non-double) variable

Usage

```
genFactor(dtName, varname, labels = NULL, prefix = "f", replace = FALSE)
```

Arguments

dtName	Data table with columns.
varname	Name of field(s) to be converted.
labels	Factor level labels. If not provided, the generated factor levels will be used as the labels. Can be a vector (if only one new factor or all factors have the same labels) or a list of character vectors of the same length as varname.
prefix	By default, the new field name will be a concatenation of "f" and the old field name. A prefix string can be provided.
replace	If replace is set to TRUE (defaults to FALSE) the field referenced varname will be removed.

Examples

```
# First example:

def <- defData(varname = "cat", formula = ".2;.3;.5", dist = "categorical")
def <- defData(def, varname = "x", formula = 5, variance = 2)

dx <- genData(200, def)
dx

dx <- genFactor(dx, "cat", labels = c("one", "two", "three"))
dx

# Second example:

dx <- genData(10)
dx <- trtAssign(dtName = dx, 2, grpName = "studyArm")
dx <- genFactor(dx, varname = "studyArm", labels = c("control", "treatment"), prefix = "t_")
dx
```

genFormula

Generate a linear formula

Description

Formulas for additive linear models can be generated with specified coefficient values and variable names.

Usage

```
genFormula(coefs, vars)
```

Arguments

coefs	A numerical vector that contains the values of the coefficients. If <code>length(coefs) == length(vars)</code> , then no intercept is assumed. Otherwise, an intercept is assumed.
vars	A vector of strings that specify the names of the explanatory variables in the equation.

Value

A string that represents the desired formula

Examples

```

genFormula(c(.5, 2, 4), c("A", "B", "C"))
genFormula(c(.5, 2, 4), c("A", "B"))

changeX <- c(7, 10)
genFormula(c(.5, 2, changeX[1]), c("A", "B"))
genFormula(c(.5, 2, changeX[2]), c("A", "B"))
genFormula(c(.5, 2, changeX[2]), c("A", "B", "C"))

newForm <- genFormula(c(-2, 1), c("A"))

def1 <- defData(varname = "A", formula = 0, variance = 3, dist = "normal")
def1 <- defData(def1, varname = "B", formula = newForm, dist = "binary", link = "logit")

set.seed(2001)
dt <- genData(500, def1)
summary(glm(B ~ A, data = dt, family = binomial))

```

genMarkov

Generate Markov chain

Description

Generate a Markov chain for n individuals or units by specifying a transition matrix.

Usage

```

genMarkov(
  n,
  transMat,
  chainLen,
  wide = FALSE,
  id = "id",
  pername = "period",
  varname = "state",
  widePrefix = "S",
  trimvalue = NULL
)

```

Arguments

n	number of individual chains to generate
transMat	Square transition matrix where the sum of each row must equal 1. The dimensions of the matrix equal the number of possible states.
chainLen	Length of each chain that will be generated for each chain; minimum chain length is 2.

wide	Logical variable (TRUE or FALSE) indicating whether the resulting data table should be returned in wide or long format. The wide format includes all elements of a chain on a single row; the long format includes each element of a chain in its own row. The default is wide = FALSE, so the long format is returned by default.
id	Character string that represents name of "id" field. Defaults to "id".
pername	Character string that represents the variable name of the chain sequence in the long format. Defaults "period",
varname	Character string that represents the variable name of the state in the long format. Defaults to "state".
widePrefix	Character string that represents the variable name prefix for the state fields in the wide format. Defaults to "S".
trimvalue	Integer value indicating end state. If trimvalue is not NULL, all records after the first instance of state = trimvalue will be deleted.

Value

A data table with n rows if in wide format, or n by chainLen rows if in long format.

Examples

```
# Transition matrix P

P <- t(matrix(c(
  0.7, 0.2, 0.1,
  0.5, 0.3, 0.2,
  0.0, 0.1, 0.9
), nrow = 3, ncol = 3))

d1 <- genMarkov(n = 10, transMat = P, chainLen = 5)
d2 <- genMarkov(n = 10, transMat = P, chainLen = 5, wide = TRUE)
d3 <- genMarkov(
  n = 10, transMat = P, chainLen = 5,
  pername = "seq", varname = "health",
  trimvalue = 3
)
```

genMiss

Generate missing data

Description

Generate missing data

Usage

```
genMiss(dtName, missDefs, idvars, repeated = FALSE, periodvar = "period")
```

Arguments

dtName	Name of complete data set
missDefs	Definitions of missingness
idvars	Index variables
repeated	Indicator for longitudinal data
periodvar	Name of variable that contains period

Value

Missing data matrix indexed by idvars (and period if relevant)

See Also

[defMiss](#), [genObs](#)

Examples

```
def1 <- defData(varname = "m", dist = "binary", formula = .5)
def1 <- defData(def1, "u", dist = "binary", formula = .5)
def1 <- defData(def1, "x1", dist = "normal", formula = "20*m + 20*u", variance = 2)
def1 <- defData(def1, "x2", dist = "normal", formula = "20*m + 20*u", variance = 2)
def1 <- defData(def1, "x3", dist = "normal", formula = "20*m + 20*u", variance = 2)

dtAct <- genData(1000, def1)

defM <- defMiss(varname = "x1", formula = .15, logit.link = FALSE)
defM <- defMiss(defM, varname = "x2", formula = ".05 + m * 0.25", logit.link = FALSE)
defM <- defMiss(defM, varname = "x3", formula = ".05 + u * 0.25", logit.link = FALSE)
defM <- defMiss(defM, varname = "u", formula = 1, logit.link = FALSE) # not observed
defM

# Generate missing data matrix

missMat <- genMiss(dtAct, defM, idvars = "id")
missMat

# Generate observed data from actual data and missing data matrix

dtObs <- genObs(dtAct, missMat, idvars = "id")
dtObs
```

genMixFormula

Generate Mixture Formula

Description

Generates a mixture formula from a vector of variable names and an optional vector of probabilities.

Usage

```
genMixFormula(vars, probs = NULL, varLength = NULL)
```

Arguments

vars	Character vector/list of variable names.
probs	Numeric vector/list of probabilities. Has to be same length as vars or NULL. Probabilities will be normalized if the sum to > 1.
varLength	If vars is of length one and varLength is set to any integer > 0, vars will be interpreted as array of length varLength and all elements will used in sequence.

Value

The mixture formula as a string.

Examples

```
genMixFormula(c("a", "..b[..i]", "c"))
genMixFormula(c("a", "..b", "c"), c(.2, .5, .3))

# Shorthand to use external vectors/lists
genMixFormula("..arr", varLength = 5)
```

genMultiFac

Generate multi-factorial data

Description

Generate multi-factorial data

Usage

```
genMultiFac(
  nFactors,
  each,
  levels = 2,
  coding = "dummy",
  colNames = NULL,
  idName = "id"
)
```

Arguments

nFactors	Number of factors (columns) to generate.
each	Number of replications for each combination of factors. Must be specified.
levels	Vector or scalar. If a vector is specified, it must be the same length as nFactors. Each value of the vector represents the number of levels of each corresponding factor. If a scalar is specified, each factor will have the same number of levels. The default is 2 levels for each factor.
coding	String value to specify if "dummy" or "effect" coding is used. Defaults to "dummy".
colNames	A vector of strings, with a length of nFactors. The strings represent the name for each factor.
idName	A string that specifies the id of the record. Defaults to "id".

Value

A data.table that contains the added simulated data. Each column contains an integer.

Examples

```
genMultiFac(nFactors = 2, each = 5)
genMultiFac(nFactors = 2, each = 4, levels = c(2, 3))
genMultiFac(
  nFactors = 3, each = 1, coding = "effect",
  colNames = c("Fac1", "Fac2", "Fac3"), id = "block"
)
```

genNthEvent	<i>Generate event data using longitudinal data, and restrict output to time until the nth event.</i>
-------------	--

Description

Generate event data using longitudinal data, and restrict output to time until the nth event.

Usage

```
genNthEvent(dtName, defEvent, nEvents = 1, perName = "period", id = "id")
```

Arguments

dtName	name of existing data table
defEvent	data definition table (created with defDataAdd) that determines the event generating process.
nEvents	maximum number of events that will be generated (the nth event).
perName	variable name for period field. Defaults to "period"
id	string representing name of the id field in table specified by dtName

Value

data.table that stops after "nEvents" are reached.

Examples

```
defD <- defData(  
  varname = "effect", formula = 0, variance = 1,  
  dist = "normal"  
)  
defE <- defDataAdd(  
  varname = "died", formula = "-2.5 + 0.3*period + effect",  
  dist = "binary", link = "logit"  
)  
  
d <- genData(1000, defD)  
d <- addPeriods(d, 10)  
dx <- genNthEvent(d, defEvent = defE, nEvents = 3)
```

genObs

Create an observed data set that includes missing data

Description

Create an observed data set that includes missing data

Usage

```
genObs(dtName, dtMiss, idvars)
```

Arguments

dtName	Name of complete data set
dtMiss	Name of missing data matrix
idvars	Index variables that cannot be missing

Value

A data table that represents observed data, including missing data

See Also

[defMiss](#), [genMiss](#)

Examples

```

def1 <- defData(varname = "m", dist = "binary", formula = .5)
def1 <- defData(def1, "u", dist = "binary", formula = .5)
def1 <- defData(def1, "x1", dist = "normal", formula = "20*m + 20*u", variance = 2)
def1 <- defData(def1, "x2", dist = "normal", formula = "20*m + 20*u", variance = 2)
def1 <- defData(def1, "x3", dist = "normal", formula = "20*m + 20*u", variance = 2)

dtAct <- genData(1000, def1)

defM <- defMiss(varname = "x1", formula = .15, logit.link = FALSE)
defM <- defMiss(defM, varname = "x2", formula = ".05 + m * 0.25", logit.link = FALSE)
defM <- defMiss(defM, varname = "x3", formula = ".05 + u * 0.25", logit.link = FALSE)
defM <- defMiss(defM, varname = "u", formula = 1, logit.link = FALSE) # not observed
defM

# Generate missing data matrix

missMat <- genMiss(dtAct, defM, idvars = "id")
missMat

# Generate observed data from actual data and missing data matrix

dtObs <- genObs(dtAct, missMat, idvars = "id")
dtObs

```

genOrdCat

Generate ordinal categorical data

Description

Ordinal categorical data is added to an existing data set. Correlations can be added via correlation matrix or rho and corstr.

Usage

```

genOrdCat(
  dtName,
  adjVar = NULL,
  baseprobs,
  catVar = "cat",
  asFactor = TRUE,
  idname = "id",
  prefix = "grp",
  rho = 0,
  corstr = "ind",
  corMatrix = NULL,
  npVar = NULL,
  npAdj = NULL
)

```

Arguments

dtName	Name of complete data set
adjVar	Adjustment variable name in dtName - determines logistic shift. This is specified assuming a cumulative logit link.
baseprobs	Baseline probability expressed as a vector or matrix of probabilities. The values (per row) must sum to ≤ 1 . If $\text{rowSums}(\text{baseprobs}) < 1$, an additional category is added with probability $1 - \text{rowSums}(\text{baseprobs})$. The number of rows represents the number of new categorical variables. The number of columns represents the number of possible responses - if an particular category has fewer possible responses, assign zero probability to non-relevant columns.
catVar	Name of the new categorical field. Defaults to "cat". Can be a character vector with a name for each new variable defined via baseprobs. Will be overridden by prefix if more than one variable is defined and $\text{length}(\text{catVar}) == 1$.
asFactor	If $\text{asFactor} == \text{TRUE}$ (default), new field is returned as a factor. If $\text{asFactor} == \text{FALSE}$, new field is returned as an integer.
idname	Name of the id column in dtName.
prefix	A string. The names of the new variables will be a concatenation of the prefix and a sequence of integers indicating the variable number.
rho	Correlation coefficient, $-1 < \rho < 1$. Use if corMatrix is not provided.
corstr	Correlation structure of the variance-covariance matrix defined by sigma and rho. Options include "ind" for an independence structure, "cs" for a compound symmetry structure, and "ar1" for an autoregressive structure.
corMatrix	Correlation matrix can be entered directly. It must be symmetrical and positive definite. It is not a required field; if a matrix is not provided, then a structure and correlation coefficient rho must be specified. (The matrix created via rho and corstr must also be positive definite.)
npVar	Vector of variable names that indicate which variables are to violate the proportionality assumption.
npAdj	Matrix with a row for each npVar and a column for each category. Each value represents the deviation from the proportional odds assumption on the logistic scale.

Value

Original data.table with added categorical field.

Examples

```
# Ordinal Categorical Data ----

def1 <- defData(
  varname = "male",
  formula = 0.45, dist = "binary", id = "idG"
)
def1 <- defData(def1,
  varname = "z",
```

```

    formula = "1.2*male", dist = "nonrandom"
  )
  def1

## Generate data

set.seed(20)

dx <- genData(1000, def1)

probs <- c(0.40, 0.25, 0.15)

dx <- genOrdCat(dx,
  adjVar = "z", idname = "idG", baseprobs = probs,
  catVar = "grp"
)
dx

# Correlated Ordinal Categorical Data ----

baseprobs <- matrix(c(
  0.2, 0.1, 0.1, 0.6,
  0.7, 0.2, 0.1, 0,
  0.5, 0.2, 0.3, 0,
  0.4, 0.2, 0.4, 0,
  0.6, 0.2, 0.2, 0
),
nrow = 5, byrow = TRUE
)

set.seed(333)
dT <- genData(1000)

dX <- genOrdCat(dT,
  adjVar = NULL, baseprobs = baseprobs,
  prefix = "q", rho = .125, corstr = "cs", asFactor = FALSE
)
dX

dM <- data.table::melt(dX, id.vars = "id")
dProp <- dM[, prop.table(table(value)), by = variable]
dProp[, response := c(1:4, 1:3, 1:3, 1:3, 1:3)]

data.table::dcast(dProp, variable ~ response,
  value.var = "V1", fill = 0
)

# proportional odds assumption violated

d1 <- defData(varname = "rx", formula = "1;1", dist = "trtAssign")
d1 <- defData(d1, varname = "z", formula = "0 - 1.2*rx", dist = "nonrandom")

dd <- genData(1000, d1)

```

```

baseprobs <- c(.4, .3, .2, .1)
npAdj <- c(0, 1, 0, 0)

dn <- genOrdCat(
  dtName = dd, adjVar = "z",
  baseprobs = baseprobs,
  npVar = "rx", npAdj = npAdj
)

```

genSpline

Generate spline curves

Description

Generate spline curves

Usage

```

genSpline(
  dt,
  newvar,
  predictor,
  theta,
  knots = c(0.25, 0.5, 0.75),
  degree = 3,
  newrange = NULL,
  noise.var = 0
)

```

Arguments

dt	data.table that will be modified
newvar	Name of new variable to be created
predictor	Name of field in old data.table that is predicting new value
theta	A vector or matrix of values between 0 and 1. Each column of the matrix represents the weights/coefficients that will be applied to the basis functions determined by the knots and degree. Each column of theta represents a separate spline curve.
knots	A vector of values between 0 and 1, specifying quantile cut-points for splines. Defaults to c(0.25, 0.50, 0.75).
degree	Integer specifying polynomial degree of curvature.
newrange	Range of the spline function , specified as a string with two values separated by a semi-colon. The first value represents the minimum, and the second value represents the maximum. Defaults to NULL, which sets the range to be between 0 and 1.

noise.var Add to normally distributed noise to observation - where mean is value of spline curve.

Value

A modified data.table with an added column named newvar.

Examples

```
ddef <- defData(varname = "age", formula = "0;1", dist = "uniform")

theta1 <- c(0.1, 0.8, 0.6, 0.4, 0.6, 0.9, 0.9)
knots <- c(0.25, 0.5, 0.75)

viewSplines(knots = knots, theta = theta1, degree = 3)

set.seed(234)
dt <- genData(1000, ddef)

dt <- genSpline(
  dt = dt, newvar = "weight",
  predictor = "age", theta = theta1,
  knots = knots, degree = 3,
  noise.var = .025
)

dt
```

genSurv

Generate survival data

Description

Survival data is added to an existing data set.

Usage

```
genSurv(dtName, survDefs, digits = 3)
```

Arguments

dtName	Name of complete data set
survDefs	Definitions of survival
digits	Number of digits for rounding

Value

Original matrix with survival time

Examples

```

# Baseline data definitions

def <- defData(varname = "x1", formula = .5, dist = "binary")
def <- defData(def, varname = "x2", formula = .5, dist = "binary")
def <- defData(def, varname = "grp", formula = .5, dist = "binary")

# Survival data definitions

sdef <- defSurv(
  varname = "survTime", formula = "1.5*x1",
  scale = "grp*50 + (1-grp)*25", shape = "grp*1 + (1-grp)*1.5"
)

sdef <- defSurv(sdef, varname = "censorTime", scale = 80, shape = 1)

sdef

# Baseline data definitions

dtSurv <- genData(300, def)

# Add survival times

dtSurv <- genSurv(dtSurv, sdef)

head(dtSurv)

```

iccRE

Generate variance for random effects that produce desired intra-class coefficients (ICCs) for clustered data.

Description

Generate variance for random effects that produce desired intra-class coefficients (ICCs) for clustered data.

Usage

```
iccRE(ICC, dist, varTotal = NULL, varWithin = NULL, lambda = NULL, disp = NULL)
```

Arguments

ICC	Vector of values between 0 and 1 that represent the target ICC levels
dist	The distribution that describes the outcome data at the individual level. Possible distributions include "normal", "binary", "poisson", or "gamma"
varTotal	Numeric value that represents the total variation for a normally distributed model. If "normal" distribution is specified, either varTotal or varWithin must be specified, but not both.

varWithin	Numeric value that represents the variation within a cluster for a normally distributed model. If "normal" distribution is specified, either varTotal or varWithin must be specified, but not both.
lambda	Numeric value that represents the grand mean. Must be specified when distribution is "poisson" or "negative binomial".
disp	Numeric value that represents the dispersion parameter that is used to define a gamma or negative binomial distribution with a log link. Must be specified when distribution is "gamma".

Value

A vector of values that represents the variances of random effects at the cluster level that correspond to the ICC vector.

Examples

```
targetICC <- seq(0.05, 0.20, by = .01)
iccRE(targetICC, "poisson", lambda = 30)
iccRE(targetICC, "binary")
iccRE(targetICC, "normal", varTotal = 100)
iccRE(targetICC, "normal", varWithin = 100)
iccRE(targetICC, "gamma", disp = .5)
iccRE(targetICC, "negBinomial", lambda = 40, disp = .5)
```

mergeData	<i>Merge two data tables</i>
-----------	------------------------------

Description

Merge two data tables

Usage

```
mergeData(dt1, dt2, idvars)
```

Arguments

dt1	Name of first data.table
dt2	Name of second data.table
idvars	Vector of string names to merge on

Value

A new data table that merges dt2 with dt1

Examples

```
def1 <- defData(varname = "x", formula = 0, variance = 1)
def1 <- defData(varname = "xcat", formula = ".3;.2", dist = "categorical")

def2 <- defData(varname = "yBin", formula = 0.5, dist = "binary", id = "xcat")
def2 <- defData(def2, varname = "yNorm", formula = 5, variance = 2)

dt1 <- genData(20, def1)
dt2 <- genData(3, def2)

dtMerge <- mergeData(dt1, dt2, "xcat")
dtMerge
```

negbinomGetSizeProb	<i>Convert negative binomial mean and dispersion parameters to size and prob parameters</i>
---------------------	---

Description

Convert negative binomial mean and dispersion parameters to size and prob parameters

Usage

```
negbinomGetSizeProb(mean, dispersion)
```

Arguments

mean	The mean of a gamma distribution
dispersion	The dispersion parameter of a gamma distribution

Details

In simstudy, users specify the negative binomial distribution as a function of two parameters - a mean and dispersion. In this case, the variance of the specified distribution is $\text{mean} + (\text{mean}^2) * \text{dispersion}$. The base R function `rbinom` uses the size and prob parameters to specify the negative binomial distribution. This function converts the mean and dispersion into the size and probability parameters.

Value

A list that includes the size and prob parameters of the neg binom distribution

Examples

```

set.seed(12345)
mean <- 5
dispersion <- 0.5
sp <- negbinomGetSizeProb(mean, dispersion)
c(sp$size, sp$prob)
vec <- rnbinom(1000, size = sp$size, prob = sp$prob)
(estMoments <- c(mean(vec), var(vec)))
(theoryMoments <- c(mean, mean + mean^2 * dispersion))
(theoryMoments <- c(sp$size * (1 - sp$prob) / sp$prob, sp$size * (1 - sp$prob) / sp$prob^2))

```

simstudy-deprecated *Deprecated functions in simstudy*

Description

These functions are provided for compatibility with older versions of simstudy only, and will be defunct in the future.

Details

- [genCorOrdCat](#): This function is deprecated, and will be removed in the future. Use [genOrdCat](#) with `asFactor = FALSE` instead.
- [catProbs](#): This function is deprecated, and will be removed in the future. Use [genCatFormula](#) with the same functionality instead.

trimData *Trim longitudinal data file once an event has occurred*

Description

Trim longitudinal data file once an event has occurred

Usage

```
trimData(dtOld, seqvar, eventvar, idvar = "id")
```

Arguments

dtOld	name of data table to be trimmed
seqvar	string referencing column that indexes the sequence or period
eventvar	string referencing event data column
idvar	string referencing id column

Value

an updated data.table removes all rows following the first event for each individual

Examples

```
eDef <- defDataAdd(varname = "e", formula = "u==4", dist = "nonrandom")

P <- t(matrix(c(
  0.4, 0.3, 0.2, 0.1,
  0.0, 0.4, 0.3, 0.3,
  0.0, 0.0, 0.5, 0.5,
  0.0, 0.0, 0.0, 1.0
),
),
nrow = 4
))

dp <- genMarkov(
  n = 100, transMat = P,
  chainLen = 8, id = "id",
  pername = "period",
  varname = "u"
)

dp <- addColumns(eDef, dp)
dp <- trimData(dp, seqvar = "period", eventvar = "e", idvar = "id")

dp
```

trtAssign

Assign treatment

Description

Assign treatment

Usage

```
trtAssign(
  dtName,
  nTrt = 2,
  balanced = TRUE,
  strata = NULL,
  grpName = "trtGrp",
  ratio = NULL
)
```

Arguments

dtName	data table
nTrt	number of treatment groups
balanced	indicator for treatment assignment process
strata	vector of strings representing stratifying variables
grpName	string representing variable name for treatment or exposure group
ratio	vector of values indicating relative proportion of group assignment

Value

An integer (group) ranging from 1 to length of the probability vector

See Also

[trtObserve](#)

Examples

```
dt <- genData(15)

dt1 <- trtAssign(dt, nTrt = 3, balanced = TRUE)
dt1[, .N, keyby = trtGrp]

dt2 <- trtAssign(dt, nTrt = 3, balanced = FALSE)
dt2[, .N, keyby = trtGrp]

def <- defData(varname = "male", formula = .4, dist = "binary")
dt <- genData(1000, def)
dt

dt3 <- trtAssign(dt, nTrt = 5, strata = "male", balanced = TRUE, grpName = "Group")
dt3
dt3[, .N, keyby = .(male, Group)]
dt3[, .N, keyby = .(Group)]

dt4 <- trtAssign(dt, nTrt = 5, strata = "male", balanced = FALSE, grpName = "Group")
dt4[, .N, keyby = .(male, Group)]
dt4[, .N, keyby = .(Group)]

dt5 <- trtAssign(dt, nTrt = 5, balanced = TRUE, grpName = "Group")
dt5[, .N, keyby = .(male, Group)]
dt5[, .N, keyby = .(Group)]

dt6 <- trtAssign(dt, nTrt = 3, ratio = c(1, 2, 2), grpName = "Group")
dt6[, .N, keyby = .(Group)]
```

trtObserve	<i>Observed exposure or treatment</i>
------------	---------------------------------------

Description

Observed exposure or treatment

Usage

```
trtObserve(dt, formulas, logit.link = FALSE, grpName = "trtGrp")
```

Arguments

dt	data table
formulas	collection of formulas that determine probabilities
logit.link	indicator that specifies link. If TRUE, then logit link is used. If FALSE, the identity link is used.
grpName	character string representing name of treatment/exposure group variable

Value

An integer (group) ranging from 1 to length of the probability vector

See Also

[trtAssign](#)

Examples

```
def <- defData(varname = "male", dist = "binary", formula = .5, id = "cid")
def <- defData(def, varname = "over65", dist = "binary", formula = "-1.7 + .8*male", link = "logit")
def <- defData(def, varname = "baseDBP", dist = "normal", formula = 70, variance = 40)

dtstudy <- genData(1000, def)
dtstudy

formula1 <- c("-2 + 2*male - .5*over65", "-1 + 2*male + .5*over65")
dtObs <- trtObserve(dtstudy, formulas = formula1, logit.link = TRUE, grpName = "exposure")
dtObs

# Check actual distributions

dtObs[, .(pctMale = round(mean(male), 2)), keyby = exposure]
dtObs[, .(pctMale = round(mean(over65), 2)), keyby = exposure]

dtSum <- dtObs[, .N, keyby = .(male, over65, exposure)]
dtSum[, grpPct := round(N / sum(N), 2), keyby = .(male, over65)]
dtSum
```

trtStepWedge *Assign treatment for stepped-wedge design*

Description

Assign treatment for stepped-wedge design

Usage

```
trtStepWedge(  
  dtName,  
  clustID,  
  nWaves,  
  lenWaves,  
  startPer,  
  perName = "period",  
  grpName = "rx",  
  lag = 0,  
  xrName = "xr"  
)
```

Arguments

dtName	data table
clustID	string representing name of column of cluster level ids
nWaves	number of treatment waves
lenWaves	the number of periods between waves
startPer	the starting period of the first wave
perName	string representing name of column of time periods
grpName	string representing variable name for treatment or exposure group
lag	integer representing length of transition period
xrName	string representing name of the field that indicates whether the cluster status is in transition status

Value

A data.table with the added treatment assignment

See Also

[trtObserve](#) [trtAssign](#)

Examples

```

defc <- defData(
  varname = "ceffect", formula = 0, variance = 0.10,
  dist = "normal", id = "cluster"
)
defc <- defData(defc, "m", formula = 10, dist = "nonrandom")

# Will generate 3 waves of 4 clusters each - starting 2, 5, and 8

dc <- genData(12, defc)
dp <- addPeriods(dc, 12, "cluster")
dp <- trtStepWedge(dp, "cluster",
  nWaves = 3,
  lenWaves = 3, startPer = 2
)
dp

dp <- addPeriods(dc, 12, "cluster")
dp <- trtStepWedge(dp, "cluster",
  nWaves = 2,
  lenWaves = 1, startPer = 4, lag = 3
)
dp

```

updateDef

Update definition table

Description

Updates row definition table created by function `defData` or `defRead`. (For tables created using `defDataAdd` and `defReadAdd` use `updateDefAdd`.) Does not modify in-place.

Usage

```

updateDef(
  dtDefs,
  changevar,
  newformula = NULL,
  newvariance = NULL,
  newdist = NULL,
  newlink = NULL,
  remove = FALSE
)

```

Arguments

<code>dtDefs</code>	Definition table that will be modified
<code>changevar</code>	Name of field definition that will be changed

newformula	New formula definition (defaults to NULL)
newvariance	New variance specification (defaults to NULL)
newdist	New distribution definition (defaults to NULL)
newlink	New link specification (defaults to NULL)
remove	If set to TRUE, remove 'changevar' from definition (defaults to FALSE).

Value

The updated data definition table.

Examples

```
# Example 1

defs <- defData(varname = "x", formula = 0, variance = 3, dist = "normal")
defs <- defData(defs, varname = "y", formula = "2 + 3*x", variance = 1, dist = "normal")
defs <- defData(defs, varname = "z", formula = "4 + 3*x - 2*y", variance = 1, dist = "normal")

defs

updateDef(dtDefs = defs, changevar = "y", newformula = "x + 5", newvariance = 2)
updateDef(dtDefs = defs, changevar = "z", newdist = "poisson", newlink = "log")

# Example 2

defs <- defData(varname = "w", formula = 0, variance = 3, dist = "normal")
defs <- defData(defs, varname = "x", formula = "1 + w", variance = 1, dist = "normal")
defs <- defData(defs, varname = "z", formula = 4, variance = 1, dist = "normal")

defs

updateDef(dtDefs = defs, changevar = "x", remove = TRUE)
updateDef(dtDefs = defs, changevar = "z", remove = TRUE)

# No changes to original definition:
defs
```

updateDefAdd

Update definition table

Description

Updates row definition table created by functions defDataAdd and defReadAdd. (For tables created using defData or defRead use updateDef.)

Usage

```
updateDefAdd(
  dtDefs,
  changevar,
  newformula = NULL,
  newvariance = NULL,
  newdist = NULL,
  newlink = NULL,
  remove = FALSE
)
```

Arguments

dtDefs	Definition table that will be modified
changevar	Name of field definition that will be changed
newformula	New formula definition (defaults to NULL)
newvariance	New variance specification (defaults to NULL)
newdist	New distribution definition (defaults to NULL)
newlink	New link specification (defaults to NULL)
remove	If set to TRUE, remove definition (defaults to FALSE)

Value

A string that represents the desired formula

Examples

```
# Define original data

defs <- defData(varname = "w", formula = 0, variance = 3, dist = "normal")
defs <- defData(defs, varname = "x", formula = "1 + w", variance = 1, dist = "normal")
defs <- defData(defs, varname = "z", formula = 4, variance = 1, dist = "normal")

# Define additional columns

defsA <- defDataAdd(varname = "a", formula = "w + x + z", variance = 2, dist = "normal")

set.seed(2001)
dt <- genData(10, defs)
dt <- addColumns(defsA, dt)
dt

# Modify definition of additional column

defsA <- updateDefAdd(dtDefs = defsA, changevar = "a", newformula = "w+z", newvariance = 1)

set.seed(2001)
dt <- genData(10, defs)
```



```
dt <- addColumns(defsA, dt)
dt
```

viewBasis *Plot basis spline functions*

Description

Plot basis spline functions

Usage

```
viewBasis(knots, degree)
```

Arguments

knots A vector of values between 0 and 1, specifying cut-points for splines
degree Integer specifying degree of curvature.

Value

A ggplot object that contains a plot of the basis functions. In total, there will be $\text{length}(\text{knots}) + \text{degree} + 1$ functions plotted.

Examples

```
knots <- c(0.25, 0.50, 0.75)
viewBasis(knots, degree = 1)
```

```
knots <- c(0.25, 0.50, 0.75)
viewBasis(knots, degree = 2)
```

```
knots <- c(0.25, 0.50, 0.75)
viewBasis(knots, degree = 3)
```

viewSplines *Plot spline curves*

Description

Plot spline curves

Usage

```
viewSplines(knots, degree, theta)
```

Arguments

knots	A vector of values between 0 and 1, specifying cut-points for splines
degree	Integer specifying degree of curvature.
theta	A vector or matrix of values between 0 and 1. Each column of the matrix represents the weights/coefficients that will be applied to the basis functions determined by the knots and degree. Each column of theta represents a separate spline curve.

Value

A ggplot object that contains a plot of the spline curves. The number of spline curves in the plot will equal the number of columns in the matrix (or it will equal 1 if theta is a vector).

Examples

```
knots <- c(0.25, 0.5, 0.75)
theta1 <- c(0.1, 0.8, 0.4, 0.9, 0.2, 1.0)

viewSplines(knots, degree = 2, theta1)

theta2 <- matrix(c(
  0.1, 0.2, 0.4, 0.9, 0.2, 0.3,
  0.1, 0.3, 0.3, 0.8, 1.0, 0.9,
  0.1, 0.4, 0.3, 0.8, 0.7, 0.5,
  0.1, 0.9, 0.8, 0.2, 0.1, 0.6
),
ncol = 4
)

viewSplines(knots, degree = 2, theta2)
```

Index

- * **categorical**
 - genOrdCat, 49
 - * **condition**
 - addCondition, 4
 - defCondition, 17
 - defRead, 22
 - * **correlated**
 - addCorData, 5
 - addCorFlex, 6
 - addCorGen, 8
 - genCorData, 34
 - genCorFlex, 35
 - genCorGen, 36
 - genCorMat, 38
 - genOrdCat, 49
 - * **define_data**
 - defCondition, 17
 - defData, 18
 - defDataAdd, 20
 - defRead, 22
 - defReadAdd, 23
 - defReadCond, 24
 - defRepeat, 25
 - defRepeatAdd, 27
 - defSurv, 28
 - updateDef, 62
 - updateDefAdd, 63
 - * **generate_data**
 - addColumns, 3
 - addCondition, 4
 - addMarkov, 12
 - addMultiFac, 13
 - genData, 39
 - genDummy, 40
 - genFactor, 41
 - genFormula, 42
 - genMarkov, 43
 - genMultiFac, 46
 - genOrdCat, 49
 - genSpline, 52
 - genSurv, 53
 - * **group_data**
 - addPeriods, 14
 - genCluster, 33
 - genNthEvent, 47
 - trtAssign, 58
 - trtObserve, 60
 - trtStepWedge, 61
 - * **missing**
 - defMiss, 21
 - genMiss, 44
 - genObs, 48
 - * **splines**
 - genSpline, 52
 - viewBasis, 65
 - viewSplines, 65
 - * **utility**
 - betaGetShapes, 16
 - delColumns, 29
 - gammaGetShapeRate, 31
 - genCatFormula, 32
 - genMixFormula, 45
 - iccRE, 54
 - mergeData, 55
 - negbinomGetSizeProb, 56
 - trimData, 57
 - updateDef, 62
 - updateDefAdd, 63
 - viewBasis, 65
 - viewSplines, 65
- addColumns, 3
 - addCondition, 4
 - addCorData, 5
 - addCorFlex, 6
 - addCorGen, 8
 - addMarkov, 12
 - addMultiFac, 13
 - addPeriods, 14

- base::parent.frame, [3](#), [4](#), [7](#), [39](#)
- beta (distributions), [30](#)
- betaGetShapes, [16](#)
- binary (distributions), [30](#)
- binomial (distributions), [30](#)

- categorical (distributions), [30](#)
- catProbs, [57](#)

- defCondition, [17](#)
- defData, [18](#)
- defData(), [30](#)
- defDataAdd, [20](#)
- defMiss, [21](#), [45](#), [48](#)
- defRead, [22](#)
- defReadAdd, [23](#)
- defReadCond, [24](#)
- defRepeat, [25](#)
- defRepeatAdd, [27](#)
- defSurv, [28](#)
- delColumns, [29](#)
- distributions, [17](#), [19](#), [30](#)

- exponential (distributions), [30](#)

- gamma (distributions), [30](#)
- gammaGetShapeRate, [31](#)
- genCatFormula, [32](#), [57](#)
- genCluster, [33](#)
- genCorData, [34](#)
- genCorFlex, [35](#)
- genCorGen, [36](#)
- genCorMat, [38](#)
- genCorOrdCat, [57](#)
- genData, [39](#)
- genDummy, [40](#)
- genFactor, [41](#)
- genFormula, [42](#)
- genMarkov, [43](#)
- genMiss, [21](#), [44](#), [48](#)
- genMixFormula, [45](#)
- genMultiFac, [46](#)
- genNthEvent, [47](#)
- genObs, [21](#), [45](#), [48](#)
- genOrdCat, [49](#), [57](#)
- genSpline, [52](#)
- genSurv, [53](#)

- iccRE, [54](#)

- mergeData, [55](#)
- mixture (distributions), [30](#)

- negbinomGetSizeProb, [56](#)
- negBinomial (distributions), [30](#)
- nonrandom (distributions), [30](#)
- normal (distributions), [30](#)
- noZeroPoisson (distributions), [30](#)

- poisson (distributions), [30](#)

- simstudy-deprecated, [57](#)
- stats::distributions, [30](#)

- trimData, [57](#)
- trtAssign, [58](#), [60](#), [61](#)
- trtObserve, [59](#), [60](#), [61](#)
- trtStepWedge, [61](#)

- uniform (distributions), [30](#)
- updateDef, [62](#)
- updateDefAdd, [63](#)

- viewBasis, [65](#)
- viewSplines, [65](#)